

Principal dimensions			Basic load ratings		Speed ratings		Designation
d	D	B	dynamic C	static C ₀	Reference speed	Limiting speed	* SKF Explorer bearing
mm			kN		r/min		-
3	10	4	0,54	0,18	130000	80000	623
3	10	4	0,54	0,18	-	40000	623-2RS1
3	10	4	0,54	0,18	130000	63000	623-2Z
3	10	4	0,54	0,18	-	40000	623-RS1
3	10	4	0,54	0,18	130000	80000	623-Z
4	9	3,5	0,54	0,18	140000	70000	628/4-2Z
4	9	4	0,54	0,18	140000	70000	638/4-2Z
4	9	2,5	0,54	0,18	140000	85000	618/4
4	11	4	0,715	0,232	130000	80000	619/4
4	11	4	0,715	0,232	130000	63000	619/4-2Z
4	12	4	0,806	0,28	120000	75000	604
4	12	4	0,806	0,28	120000	60000	604-2Z
4	12	4	0,806	0,28	120000	60000	604-Z
4	13	5	0,936	0,29	110000	67000	624
4	13	5	0,936	0,29	110000	53000	624-2Z
4	13	5	0,936	0,29	110000	67000	624-Z
4	16	5	1,11	0,38	95000	60000	634
4	16	5	1,11	0,38	-	28000	634-2RS1
4	16	5	1,11	0,38	95000	48000	634-2RZ
4	16	5	1,11	0,38	95000	48000	634-2Z
4	16	5	1,11	0,38	-	28000	634-RS1
4	16	5	1,11	0,38	95000	60000	634-RZ
4	16	5	1,11	0,38	95000	60000	634-Z
5	11	5	0,637	0,255	120000	60000	638/5-2Z
5	11	4	0,637	0,255	120000	60000	628/5-2Z
5	11	3	0,637	0,255	120000	75000	618/5
5	13	4	0,884	0,34	110000	67000	619/5
5	13	4	0,884	0,34	110000	53000	619/5-2Z
5	16	5	1,14	0,38	95000	60000	625 *
5	16	5	1,14	0,38	95000	48000	625-2Z *