Segmentation of Aerial Images for Plausible Detail Synthesis

Oscar Argudo^a, Marc Comino^a, Antonio Chica^a, Carlos Andújar^a, Felipe Lumberras^b

^a*ViRVIG, Computer Science Department, Universitat Politècnica de Catalunya
Jordi Girona 1-3, Barcelona, Spain*

^b*Computer Vision Center, Department of Computer Science, Universitat Autònoma de Barcelona
Edifici O, Bellaterra, Spain*

Abstract

The visual enrichment of digital terrain models with plausible synthetic detail requires the segmentation of aerial images into a suitable collection of categories. In this paper we present a complete pipeline for segmenting high-resolution aerial images into a user-defined set of categories distinguishing e.g. terrain, sand, snow, water, and different types of vegetation. This segmentation-for-synthesis problem implies that per-pixel categories must be established according to the algorithms chosen for rendering the synthetic detail. This precludes the definition of a universal set of labels and hinders the construction of large training sets. Since artists might choose to add new categories on the fly, the whole pipeline must be robust against unbalanced datasets, and fast on both training and inference. Under these constraints, we analyze the contribution of common per-pixel descriptors, and compare the performance of state-of-the-art supervised learning algorithms. We report the findings of two user studies. The first one was conducted to analyze human accuracy when manually labeling aerial images. The second user study compares detailed terrains built using different segmentation strategies, including official land cover maps. These studies demonstrate that our approach can be used to turn digital elevation models into fully-featured, detailed terrains with minimal authoring efforts.

Keywords: Terrain editing, Detail synthesis, Vegetation synthesis, Terrain rendering, Image segmentation

1. Introduction

Publicly available Digital Terrain Models (DTM) and aerial images have opened new possibilities for using real scenarios in video games and entertainment applications. These 2.5D models are readily usable for rendering aerial views of the scenes, but lack resolution and 3D appearance for close-up views. As a consequence, artists often need to enrich DTMs with synthetic detail, such as procedural bedrock and rocks for the ground, realistic water shaders for lakes and rivers, and fully-detailed plant models for the vegetation. When done manually, a substantial amount of effort is required to locate the different elements in the aerial images and to apply a suitable detail synthesis technique to them.

In this paper we address the problem of segmenting high-resolution (25 cm/pixel) aerial images into small sets of classes suitable for detail synthesis (Figures 1 and 2). The *segmentation for synthesis* problem (*S4S* from now on) exhibits a number of unique issues that we summarise below. First, categories in *S4S* are defined according to the different detail synthesis techniques artists might want to apply. For example, in a particular desert scene for a Dakar rally game, one artist might want to distinguish rock, sand, cacti and palm trees, whereas in a tropical forest scene we could be interested in segmenting vegetation and rivers.

Second, we want to give artists the possibility to add new classes dynamically. This way artists can progressively refine the appearance of different materials, which due to their variety are hard to know in advance (e.g. forest, shrub, grass, crops,

sand, bare rock, scree, water courses, inland marshes, snow...) and can decide to distinguish non-anticipated categories (e.g. deciduous forest from coniferous forest). This flexibility means that the pixel classifier should be able to work with relatively small training sets (containing examples from a varying set of classes) and that both training and classification times should be within the range of a few minutes. Notice also that we cannot assume balanced classes in the segmented exemplars, neither the exemplar class distributions to be representative of the true class distributions.

In this context, generating large and varied training sets is unfeasible. Manual image segmentation requires a substantial amount of effort. For example, a 25 cm/pixel image covering 1 km² contains 16M pixels. Even when using the advanced tools found in state-of-the-art object-based image processing applications (multiresolution segmentation, superpixels, manual relabeling...), complete segmentation of a 1 km² image can take several hours of an expert human classifier. Moreover, we will show that resulting labels largely depend on the labeler's judgement and thus cannot be safely taken as ground truth.

This manual labeling effort can be largely alleviated by segmenting only a collection of easy-to-label uniform regions (see Figure 9) and taking the training examples from these regions using a suitable sampling strategy. We adopt this approach (partial, region-based classification) as the only feasible approach in the context of dynamic classes.

Although there is an extensive literature on image segmentation in remote sensing, previous approaches either require

Figure 1: Renders of detailed terrains created from aerial images. The segmentation of the aerial image allows for the application of different techniques depending on the soil cover. In these examples, synthetic trees, bushes and grass for vegetation areas, fractal displacement for the bare soil, rocks and gravel shader for unpaved roads, and specific shaders for snow, lakes and rivers. The last image shows an example of landscape and visual impact assessment.

Figure 2: We address the problem of adding realism to digital terrain models through the segmentation of aerial images (blue box) into a suitable set of classes (e.g. vegetation, rock, water). This way each class can be rendered using specific shaders and procedural content (yellow boxes).

2. Previous work

Despite the specific nature of the S4S problem discussed above, we rely on the great amount of work already done in the field of aerial image analysis and on typical strategies of region analysis based on color and texture.

Classical image segmentation techniques compute per-pixel features based on image values in the pixel’s neighborhood. Many different pixel descriptors have been proposed both for general images and remote sensing images. Ruiz et al. [1] compared different texture and spectral feature descriptors for pixel classification of remote sensing images. Results on different forest scenes showed that there is no universal criteria - the suitable set of features depends on the type of landscape units defined in each application. Similarly, dos Santos et al. [2] also compared the effectiveness of various color and texture descriptors for image classification. Although their task was not pixel based, the best descriptors were also dependant on the type of input dataset. Tokarczyk et al. [3] compare classical feature sets with feature banks computed with the first layers of deep networks. Their results show that features based on patches dominate over those based on individual pixels, i.e. texture holds important information in high-resolution images. However, complex feature extraction methods or even non-linear feature learning yield small or no improvement, while adding a significant computation cost. Penatti and dos Santos [4] studied whether Convolutional Neural Networks trained for classification of everyday objects generalize to aerial and remote sensing images. They used the output of the last fully-connected layer of two networks (OverFeat and CaffeNet) as features, and compared with low-level feature descriptors. On the aerial dataset, deep features achieved the best results, but for remote sensing images they were outperformed by the low-level descriptors. Since we do not know in advance the specific classes artists will require, and training sets are expected to be too small for end-to-end learning, we use a large number of color and texture features from the literature, combined with height, slope and gradient descriptors from the DTM.

Multiple works also compare the accuracy of classification algorithms in the context of segmentation of aerial images, including Bayesian classifiers [5], Random Forests [3], SVM [6, 4] and Deep Learning methods [7]. Frölich et al. presented Iterative Context Forests [8, 9], a classification system

based on Random Forests that builds the trees level-wise and adds the class probability maps of one level as a new input channel for the next level. A similar approach by Tokarczyk et al. [10] uses boosting instead of Random Forests. Castelluccio et al. [7] compared three different options for classification with convolutional neural networks: training from scratch, fine-tuning the last layers using training images, or using the last fully-connected layer as features as in [4]. On the aerial images dataset, the best accuracies were achieved by fine-tuning, then using the feature vector, and finally by training from scratch. On the remote sensing dataset, training from scratch or fine-tuning provided the best results depending on the network used. The authors report that training from scratch the CNN took days or weeks of computation time.

In contrast to the previous techniques, our approach focuses on obtaining segmentations that will be used for detail synthesis. Segmentation classes are dynamically defined by the user, which requires fast training and inference times and prevents the use of massive training sets. Unfortunately, many works in the literature do not focus on inference *and* training times. We compare different state-of-the-art classification algorithms by considering all these criteria and the robustness against unbalanced data, as well as the ability to generate per-class probability maps (besides class labels).

Keeping the class with maximum a posteriori probability as the final pixel class can result in noisy labelings. The smoothness assumption states that nearby pixels tend to have similar labels, thus individual pixels are not independent variables but form a random field. Schindler [11] compared different smoothing strategies that increase accuracy: majority voting in a neighborhood, Gaussian and bilateral filtering, and approximate inference via global methods for random fields such as graph cuts and semiglobal labeling. They also note that including feature descriptors computed on the pixel neighbourhood implicitly produces smoother labelings. We propose a variation of the bilateral filter exploiting domain knowledge on the classes.

3. Overview

Given a small collection of segmented exemplars E , and an input aerial image I of a non-urban area, we aim to classify each pixel of I into a user-defined set of classes including e.g. bare soil and different vegetation types. Figure 3 shows an overview of the complete pipeline. Note that this is a typical supervised classification pipeline. Our contribution though is the analysis of the algorithms for feature extraction, sampling, classification, smoothing, and cost-aware labeling, that achieve the best trade-off between training set size, running times, and accuracy, in the context of dynamic labels.

All images (exemplars and images to be segmented) are assumed to be high-resolution (25 cm per pixel), orthorectified aerial images providing reflected light measurements in the red (R), green (G), blue (B) and near-infrared (I) bands of the electromagnetic spectrum. This kind of aerial images are often publicly available through Web Map Services [12]. We did not consider hyperspectral images [13] employing a larger number of spectral bands because these images are not publicly available

except for specific areas and at lower resolutions. We also assume an elevation map of the region is also available (we used 5 m per pixel elevation data from public Web Coverage Services).

The output of the algorithm is the segmented image, with each pixel classified into one of the user-provided classes, along with the associated class probability maps (one per class). Segmented regions can be used to control the instancing of procedural 3D content (e.g. rocks, tree, grass) whereas probability maps are useful to get smooth transitions across material boundaries and to weight the influence of material shaders.

All our sets include at least the following labels: bare ground, tree/shrub and grass. The choice of these classes is motivated by their prominence in typical terrains, and the clearly different CPU/GPU techniques required for their detailed representation. Terrain regions can be enhanced e.g. through fractal noise [14, 15, 16], by adding bedrocks and rock layers [17], and by synthesizing high resolution detail through multi-resolution dictionary-based approaches [18, 19]. Both trees and shrubs are often rendered as billboard clouds [20] whereas grass is often handled through specific rendering techniques [21, 22].

The training part of the pipeline is shown in Figure 3. A few exemplars are labeled manually, we extract a collection of features for each pixel (Section 4), and train a multi-class classifier on a subset of segmented pixels. As we shall see, we found Random Forest (RF) to be the best option considering accuracy and performance both at training and inference time (Section 5). The user may at any moment add new classes and provide new segmented areas in the existing exemplars, or add new exemplars containing representative areas from these classes. Adding new labels obviously involves retraining the classifier, but not repeating the feature extraction for existing exemplars. Since exemplars are selected and segmented by the user, we cannot assume classes to be balanced, and we cannot either suppose their distribution to be representative of the true class distribution. This means dataset sampling [23] might play a key role in accuracy.

For labeling automatically the input aerial images, we use the trained RF to predict class probabilities. Although per-pixel features are computed on a neighborhood around the pixel, at this stage class probabilities are often noisy. We thus apply a smoothing step (a bilateral filter) to each of the individual class probabilities (Section 8). Finally, we allow the user to apply a cost matrix to choose as final label the one minimizing perceptual misclassification costs (Section 9).

4. Tested features

As stated above, previous studies on the segmentation of aerial images have found that the optimal feature set depends on the specific set of categories [1, 2]. Recent deep learning approaches obviate feature engineering, but for the specific case of pixel-wise aerial image segmentation they have shown little or no improvement with respect to low-level features [3, 4]. Since we want to let artists choose the desired classes, we decided to include a large number of well-known color and texture features from the literature, and test their contribution on

Figure 3: Overview of the segmentation pipeline. Training steps are shown in orange and inference steps in green.

the classification of typical classes (Section 6). For the sake of reproducibility, we list below the 91 features we tested. Please refer to [1, 24, 25] for further details. Features were computed based on the red, green, blue, near infrared and elevation of the pixel itself and its neighborhood, at the original resolution of the input images (25 cm/pixel). An analysis of the features at lower resolutions is provided in Section 6.

Height features [4 values]: we considered the elevation at the pixel location as well as its gradient (orientation and magnitude). Orientation is represented with two sin/cos values to avoid discontinuities. As we shall see, we propose to use gradient magnitude but discard elevation and gradient orientation (see Section 6).

Color features [10 values]: we use the RGB color components of the pixel, as well as its components in HSL and CIELab color spaces. Hue is represented with sin/cos values.

NDVI [1 value]: the Normalized Difference Vegetation Index [26] is the ratio $(I - R)/(I + R)$ where I and R represent the infrared and red values.

GLCM [20 values]: We compute four normalized Grey Level Co-occurrence Matrices on 15×15 windows with displacement vectors $(0, 1)$, $(1, 0)$, $(1, 1)$ and $(-1, 1)$. As in [24], we extract from each matrix five features: energy, entropy, contrast, homogeneity and correlation.

Spectral features [6 values]: The power spectrum of natural images tends to follow the power law $P = 1/f^\beta$, where P is the power as a function of frequency f and β is the spectral slope [25]. We compute P and β on 16×16 windows. We computed four extra features by dividing the frequency domain into 4 ring-shaped regions, and computing the power sum on each region.

HOG features [8 values]: the Histogram of Oriented Gradients was computed on a window of 15 pixels with lightness grouped into 8 bins.

LBP [42 values]: we compute a rotationally invariant version of the Local Binary Pattern descriptor [27] over the HSL and RGB channels, using 8 points and radii 1, 2, 4 and 8, and using 16 points and radii 16, 32 and 64.

5. Comparison of classification algorithms for S4S

We compared the performance of multiple traditional classification algorithms, aiming to obtain the best possible accuracy while achieving interactive training and inference times. We tested the **K Nearest Neighbours** algorithm with $k = 1, 10$ and 20 neighbours, **Multinomial Regression** with and without normalized features and **Random Forests** with $N = 100$

trees and $D \leq 15$ maximum depth. For these tests we averaged execution times over 5 runs. Finally we also tested **SVMs** with linear (gamma and bias set to 1) and RBF ($\sigma = 1$) kernels. Results are reported in Table 1.

Algorithm	Accuracy	Training	Inference
Random Forest ($N=50, D \leq 15$)	94.80%	6 min 9 s	58 s
SVM Polynomial (linear)	93.80%	13 h 26 min	3 h 7 min
SVM RBF ($\sigma = 1.0$)	94.68%	5 h 35 min	2 h 59 min
Logistic Regression	93.78%	1 h 40 min	1 min 42 s
Logistic Regression (norm.)	93.76%	1 h 36 min	45 s
kNN ($k = 20$, norm.)	92.46%	n/a	3 h 52 min
kNN ($k = 10$, norm.)	92.51%	n/a	3 h 36 min
kNN ($k = 1$, norm.)	90.44%	n/a	2 h 59 min

Table 1: Average times and accuracies of the different machine learning algorithms we tried. In some cases features were normalized (indicated as *norm*).

Random Forest, SVM and Logistic Regression all provided similar accuracies. However, Random Forest was much faster to train than the other two, also offering the fastest classification times. We thus claim that Random Forest is a very good option for our purposes.

Random Forests can be tuned using two main parameters: the depth (D) of the trees and number (N) of trees. For each combination of $D \in \{5, 10, 15, 25\}$ and $N \in \{10, 25, 50, 75, 100\}$, we measured the average accuracy obtained on 10 different pairs of training and validation sets from Dataset Andorra. Figure 4 shows the observed accuracies. Unless explicitly stated, all experiments in this article use $N = 50$ and $D \leq 15$ since these values give the best trade-off between performance and accuracy. Our results are similar to the ones obtained by [3], who also chose $N = 50, D \leq 15$. Regarding the number of features each tree can randomly select, all tests were set up to use $\lceil \log_2 91 \rceil = 7$ features.

Since Deep Learning approaches do not use the features discussed above, we discuss Convolutional Neural Networks separately (Section 11).

6. Feature analysis

6.1. Multiresolution features

Some features in the chosen feature set are computed using sliding windows of up to 16 pixels (except LBP, which uses larger radii). Since our input data has a resolution of 25 cm/pixel, our feature set takes into account neighbourhoods up to 4 m wide. We could increase this span either by increasing the sliding window size – which would also significantly

Figure 4: Accuracy of Random Forests depending on number of trees (N) and maximum depth (D) on Dataset Andorra.

play an important role in accuracy. However, it does not depend on the appearance of the patch containing the pixel but on its absolute location, and so the causal relation learned by RF (e.g. snow and water confined to specific height ranges) might be very specific to the chosen exemplars, and could generalize poorly on different scenes. Slope orientation can also introduce bias in the results. In our selected training set, we were not aware that bushes regions had been selected only from a few orientations, and thus when classifying full terrains we obtained incorrect results. Therefore, we decided to remove these two features (height, slope orientation) in our final model, resulting in 88 features. Notice also the contribution of the NDVI feature, which is computed from the near-infrared channel. For datasets lacking this channel, we could still use our pipeline expecting an accuracy around 6% lower.

Figure 5: Accuracy loss after randomly permuting the samples of a certain feature group. Original accuracy 91.6%.

7. Training set sampling

Unlike typical classification problems, with fixed classes and large training sets, we deal with dynamic classes and user-provided exemplars. Given an exemplar image, one easy way to construct a training set is to ask the user to select manually a few homogeneous regions for each class. The system will then properly sample a subset of the labeled pixels and use them as training data. This option puts much less effort on the user than asking for a completely-segmented exemplar.

In this setup, we have to face three different problems:

- **Non-representative neighborhoods:** since training instances will be selected from the manually-identified homogeneous regions, the corresponding pixels are likely to have coherent neighborhoods that are not necessarily representative of arbitrary pixels (in contrast to selecting arbitrary pixels from a completely-segmented exemplar).
- **Imbalanced data:** in some exemplars, the ratio of the majority class (e.g. tree) to the minority class (e.g. scree) instances can be very large. This can be due to the predominance of some classes in the chosen exemplars, or to the fact that some objects (e.g. pathways) can be more difficult to select manually than others (e.g. forest). Therefore some degree of class imbalance is expected.

increase feature extraction costs –, or using an image of the same area at a coarser resolution.

We performed an experiment using again Dataset Andorra to assess whether this multiresolution approach improves accuracy. We used a training set and a validation set, each one containing about 2% of the input image pixels (about 260 K samples), and measured the accuracy of a RF classifier with features computed at varying resolution levels. We averaged the results over 10 executions.

Our baseline performance was given by a minimum feature set which included the four height features H (elevation, gradient magnitude and orientation), as well as the LBP features. LBP was included in the baseline because it is computed using radii up to 64 pixels. We then added the rest of the features (F) computed at varying resolutions: 25 cm/pixel, 50 cm/pixel, 1 m/pixel and 2 m/pixel.

Table 2 shows the resulting accuracies. Since the best accuracies were given by the highest resolution image (25 cm/pixel), we also tried combining the features of this one with one of the downsampled images. Results slightly improved in all three combinations; the best case was adding 1 m/pixel features, yielding a 0.4% gain in accuracy. However, the additional memory and computation time needed to obtain such a small accuracy improvement made us discard the multiresolution approach for S4S purposes.

Feature sets	Accuracy	Training	Inference
LBP, H	78.34%	93 s	22 s
LBP, H, F(0.25 m)	94.85%	91 s	28 s
LBP, H, F(0.50 m)	93.94%	94 s	28 s
LBP, H, F(1 m)	93.09%	97 s	28 s
LBP, H, F(2 m)	91.71%	94 s	28 s
LBP, H, F(0.25 m), F(0.5 m)	95.14%	134 s	37 s
LBP, H, F(0.25 m), F(1 m)	95.26%	106 s	36 s
LBP, H, F(0.25 m), F(2 m)	95.14%	103 s	36 s

Table 2: Average accuracies using different sets of feature resolutions.

6.2. Feature contributions

Figure 5 shows the relevance (as % of accuracy loss, following [28]) of the tested features on randomly selected samples of the training set (Figure 11). The height feature appears to

- Different class distributions: the class distribution largely depends on the scenario the exemplars have been chosen from. Therefore, the class distribution used for training (e.g. 80% trees) might be quite different from the true class distribution at inference.

Figure 6: From left to right: part of the photograph, classification using homogeneous neighborhoods, classification using heterogeneous neighborhoods, and manual classification.

We will first address the non-representative neighborhood problem. We conducted an experiment to evaluate how large was the effect of training with data coming from homogeneous regions. We used again the well-separated Dataset Andorra, for which a complete segmentation was available. Each pixel was considered to be *homogeneous* if all pixels within its $r \times r$ neighborhood had the same class. Otherwise, the pixel was considered to be *heterogeneous*. Then, we built three training sets: one with only homogeneous pixels, one with only heterogeneous pixels and one with 50% of each type. Each training set was randomly undersampled to about 260 K training examples. We trained a RF ($D=15$, $N=50$) for each training set and measured the resulting accuracies on a validation set including pixels from all across the image. Figure 6 compares the resulting segmentations on a small part of the image. Averaged accuracies are shown in Table 3.

Window size	Homogeneous	Half and half	Heterogeneous
$r = 2$	92.9%	95.2%	93.7%
$r = 5$	89.7%	95.1%	94.9%
$r = 10$	86.8%	94.9%	95.1%
$r = 15$	84.6%	94.9%	95.1%

Table 3: Average accuracies depending on the training set selection.

These results show the positive impact of including some examples near the (image-space) class boundaries. Both the heterogeneous and the 50%-50% training sets resulted in high accuracy, since both include examples with representative neighborhoods. However, if training examples are taken from homogeneous regions, we cannot guarantee representative neighborhoods as long as user-selected region boundaries might not match class boundaries. Fortunately, we found that reducing the window size used for the homogeneity criterion (i.e. allowing homogeneous pixels to get closer to class boundaries) led to reasonable accuracy (above 90% in the experiment, see Table 3). Since a complete pixel-wise segmentation of the exemplars is a very time-consuming task, a good trade-off is achieved by asking users to select *nearly-maximal* homogeneous regions, with its boundary near examples from other classes. Following this guideline, exemplars are still easy to label (with respect

to a complete pixel-wise segmentation) while still resulting in reasonably good classification accuracy.

We now address the problems of imbalanced data and dissimilar class distributions. We analyzed the impact of different distributions on Andorra. The real distribution on this set is 74.5% tree, 13.7% grass and 11.8% ground. Figure 7 shows the curve obtained when sampling different percentages of the class tree on the training set, and splitting the rest of the training set equally among grass and ground. As expected, the best segmentation results are achieved when the training distribution roughly matches the target distribution (vertical dashed red line in Figure 7). However, we only observed small changes in the overall accuracy even with completely erroneous distributions. Therefore we decided to give the user the opportunity to provide the expected class distribution on the type of images to be classified (as rough per-class percentages). We sample the training set according to the user-provided distribution, re-train the RF, and use it to segment the input image.

Figure 7: Accuracy obtained for different distributions of the training set samples.

8. Smoothing class probabilities

The output of our classifier is a set of class probabilities rather than just the class label. Therefore, users can apply post-classification filtering techniques to correct noise or small errors in the final labeling.

Schindler [11] compares different smoothing methods that can be used to produce a final labeling from class probabilities. Due to their speed and simplicity, we decided to implement the three filtering methods he presents: majority voting, Gaussian filter and bilateral filter. Additionally, the user can provide, for each label, the minimum expected footprint σ of the objects belonging to this class. For example, a single pixel (0.25 m in our case) labeled as tree surrounded by non-tree pixels is very likely to be erroneous, while a single grass pixel may be plausible. Figure 8 shows an example in which no filtering results in a very noisy classification, while a bilateral filter over-smooths some grass or bush regions. However, filtering with a different σ on each probability map eliminates undesired single-pixel trees while keeping small vegetation clusters.

Figure 8: Top row: input image, classification output without filtering (MAP), bilateral filter with $\sigma = 4$ pixels, bilateral filter with $\sigma_{\text{tree}} = 4$, $\sigma_{\text{bush}} = 2$, $\sigma_{\text{grass}} = 1$ and $\sigma_{\text{ground}} = 0.5$ pixels. Bottom row: probability maps of classes tree, bush, grass and ground.

9. Cost-sensitive classification

Recall that we aim at replacing pixels by synthetic detail in the context of free-camera applications. Misclassified pixels are likely to have a varying perceptual impact, depending on the predicted/true labels and on the specific detail synthesis techniques that will be applied to the output labeled images. For example, misclassifying terrain with any of the other vegetation classes (tree, shrub, grass) is likely to have a higher visual impact than e.g. confusing shrubs and trees.

Given the estimated class probabilities $\hat{p}_k(x)$ for a test pixel x , its final class $\hat{y}(x)$ is computed as the one minimizing the expected misclassification costs,

$$\hat{y}(x) = \arg \min_{i=1,\dots,K} \sum_{j=1}^K c_{ij} \hat{p}_j(x)$$

where c_{ij} is the user-defined cost of misclassifying as class i a pixel whose true label is j . Without loss of generality [29], elements on the diagonal of the cost matrix $C = c_{ij}$ can be assumed to be 0, and elements off-diagonal can be assumed to have a positive cost. Scaling C by a positive constant does not affect the optimal decision, so the minimum non-zero cost can be assumed to be 1. For $K = 4$ classes, the cost matrix requires only 11 values to be provided by the user. In Section 10 we provide some insights on how to derive well-founded cost matrices based on perceptual differences between pairs of classes.

10. Results

10.1. Classification accuracy of human labelers

We conducted a first experiment to analyze how humans classify *regions* in aerial images. The purpose was two-fold: to obtain ground truth labels to test our algorithm with, and to analyze the difficulty and resulting accuracy of human labelers. Since per-pixel classification is a long and tedious task, we selected a total of 56 uniform regions from 8 datasets (Figure 9-top) representing a variety of forest and rural areas around Catalonia.

For each region, we asked users to choose between four labels: tree, bush, grass and ground, as well as three additional labels expressing doubts between two classes: tree or bush, bush or grass, grass or ground. During the test, one region at a time was presented to the user as a blinking, semi-transparent overlay on top of the current aerial photograph. Users were able to zoom in and out using the mouse wheel. Twenty-three users (19 male, 4 female, ages 22-45, normal-sighted, most of them familiar with computer games) participated in the experiment.

Figure 9: Datasets used in the first user study (top), *ground-truth* labels computed following [30] (center), majority class given by our per-pixel classification (bottom). The datasets shown are (from left to right): Andorra, Olot, Garraf, Rocacorb, Peguera, Setcases, Garraf-Quarry, Montserrat.

Ground-truth labels were not directly available, so we computed and compared against the crowdsourced labels. One way to obtain these labels is through majority voting, i.e. taking the most voted label at each region. However, this strategy does not account for how good each individual labeler is, nor the intrinsic difficulty of labeling each particular region. Following Whitehill et al. [30], we inferred the label of each region using a probabilistic graphical model in which observed labels depend on three causal factors: difficulty of the image, expertise of the labeler, and the true label of the image. Using an Expectation-Maximization approach, all three causal factors can be inferred from the observed labels. For our special case in which a user expressed doubt between two classes, we treated this as two different observed labels for that region given by the same user.

Figure 9-middle shows the resulting ground truth labels using the implementation provided in [31]. These labels will be used in Section 10.2 to test our classification pipeline.

Alongside ground truth labels, we can also read from the probabilistic model the region difficulty parameter β . Whitehill et al. [30] model image difficulty as $1/\beta \in [0, \infty)$. When β is close to 0, the image difficulty is very high and even the most skilled users become just pure random labelers. Figure 10 shows the β parameters averaged by input image (left) and by ground truth label (right). Notice that difficulty estimates exhibit large variance across classes and datasets. In particular, bush regions are hard to classify, and consequently images that contain regions similar to bushes are more prone to misclassification errors.

Table 4 shows the resulting users' confusion matrix. Participants were relatively good at distinguish between high and low vegetation (tree/grass), but bushes were easily confused with trees or grass. These confusion matrices provide a perceptual basis to measure how easy a label can be misclassified as an-

Figure 10: Average classification easiness for each dataset (left) and for each class (right). The lower the value, the higher the difficulty.

other label, and thus provide a solid foundation to build perceptual cost matrices: in the context of S4S, the higher the confusion rate between two classes, the lower should be the corresponding misclassification cost.

Class / Predicted	Tree	Bush	Grass	Ground
Tree	85.4%	14.6%	0.0%	0.0%
Bush	11.1%	63.9%	23.7%	1.3%
Grass	0.0%	0.4%	95.4%	4.0%
Ground	0.0%	0.2%	8.3%	91.5%

Table 4: Confusion matrix as percentages per label.

10.2. Classifier accuracy vs human accuracy

The user study above shows that identifying tree, shrub, grass and terrain classes on 25 cm/pixel aerial images is not an easy task, and that users often express doubt or misclassify well-delimited regions. This suggests that a manual segmentation from a single user is just a biased estimate of the *ground truth*. Therefore, we decided to conduct a follow-up study. We asked eight new users (7 male, 1 female, ages 22-32, normal-sighted, all of them familiar with computer games) to classify the regions in Figure 9, but this time only the four classes were available to them, as they were not allowed to express doubt.

The number of regions each user marked differently from the 23-subject ground truth were between 5 and 10, with an average of 7.5 incorrectly classified regions out of 56 (87% accuracy).

We compared this user accuracy with that of our classifier, keeping the majority class inside each of the regions to produce a unique label of the whole region. The classifier output showed 7 misclassified regions (see Figure 9 bottom row), similar to the expected error for human labelers. All but one of these error regions correspond to what users perceived as *ground truth* bush and were confused with trees or grass, a distinction that is also usually hard for humans as we explained in Section 10.1.

10.3. Visual validation of complete segmentations

We used our classifier to perform full per-pixel classifications of different datasets. The first eight datasets consisted of a 3600×3600 aerial image (rgb and infrared), and the corresponding digital elevation model. These datasets were segmented by our algorithm into four classes: tree, bush, grass, and ground. The last three datasets were bigger (16000 × 16000 pixels) and included four additional classes: scree, rock, water, and snow.

The test hardware was a single PC equipped with an Intel Core i7 at 3.40 GHz and 16 GB of RAM. We used OpenCV and Matlab to extract the 88 features of each pixel, with a performance of 36 s/Mpixel. Note that features only need to be extracted once per image.

The classifier, as well as the various tests presented in previous sections, were implemented using KNIME [32]. The training set was randomly sampled from a gallery of nearly-maximal homogeneous regions that was easily segmented by an expert (Figure 11), the proportion of samples of each class being user-adjustable. These training images are not contained in any of the datasets to classify. Training a random forest using 400K samples took about 2 min. Classification took around 21.5 s/Mpixel (5 min 45 s per km²).

Figure 11: The 20 images used as training set with nearly-maximal homogeneous regions segmented. Classes: tree (dark green), bush (light green), grass (yellow), ground (orange), scree (light grey), rock (dark grey), water (blue), snow (cyan).

Figure 12 shows the 11 datasets as well as the output of our classifier – as the most probable class – before applying smoothing or cost matrix. These segmentations can be assessed only visually since no ground-truth is available.

10.4. Detail synthesis application

The most relevant application of the proposed pipeline is to synthesize terrain and vegetation detail depending on the per-pixel labels. Here we show some sample images obtained by a straightforward approach. Regions labeled as trees or shrubs were covered by a blue noise pattern, each point representing the location of a synthetic tree/shrub. The minimum distance between generated points was determined by the size of the synthetic vegetation models. Grass regions were enhanced by instantiating 3D models of grass and flowers. Fragments covered by water and snow were rendered using specific shaders. Terrain regions were detailed on-the-fly through displacement mapping shaders perturbing the original DTM according to Fractional Brownian Motion noise. Figures 13 and 1 show some resulting images (see accompanying video).

10.5. Detail synthesis validation

We conducted a final user study to evaluate the quality of our segmentation pipeline in the context of detail synthesis. We selected a set of 30 viewpoints on a large DEM (Figure 12, last column), and rendered the scene with procedurally-generated detail (vegetation, rocks, water) placed according to either our

Figure 12: Classifier results for our 11 datasets. The first eight datasets were segmented into 4 classes (tree, bush, grass, ground) while the last three were segmented into 8 classes (tree, bush, grass, ground, scree, rock, water, snow). We use different color maps to highlight this. From left to right, the datasets are: Andorra, Garraf-Quarry, Olot, Garraf, Montserrat, Peguera, Rocacorrb, Setcases, Besiberis, Nuria, Sant Maurici.

Figure 13: Example application: vegetation synthesis on terrain. Dataset Rocacorrb is shown with the result of the classifier (left) and the rendered images with vegetation on the terrain (right).

segmented image (OURS) and an official 5 m/pixel land cover map (LCM). The set of images used in the study can be found in the supplementary material.

Our study consisted of a *selection task*, in which participants were presented both images (OURS/LCM) and had to choose which one showed a better placement of the synthetic elements, and a *scoring task*, in which participants were shown one particular image at a time (either OURS or LCM) and had to indicate the plausibility of detail placement using a 4-point Likert scale. Both tasks started with a tutorial video and displayed instructions throughout the trials.

For the selection task, participants were shown 12 random image tuples (from the set of 30), where each tuple consisted of rendered images from the same viewpoint, using either our segmented image or the LCM. Users were requested (forced choice) to select the best image in terms of the placement of the added elements. A reference image showing just the DEM textured with the orthophoto was also shown. For all participants, the order of the tuples was randomly chosen, along with the order of the images within the tuple.

For the scoring task, we randomly selected 12 images as in the first task, but now each image was shown separately rather than in a tuple. One half of the images were detailed using our segmentation, the other half through LCM. Participants were asked to assign a score {1,4} based on how plausible they thought the detailed elements were placed, again according to a reference (no synthetic detail) image.

The study was deployed on a website, and participants (21, contacted through email) could complete the task remotely using the device of their choice. We applied Bayesian data analysis [33] using an experiment design in the same spirit of [34]. Reported results represent the posterior mean, and the confi-

dence interval (CI) represents the range including 95% of the posterior probability.

Concerning the selection task, we modeled the posterior probability of each method (OURS, LCM) being selected as the best as a Bernoulli random variable with a uniform Beta prior. As shown in Figure 14-left, our method was significantly more likely to be selected as the best in terms of detail placement, when comparing against LCM-based placement. Figure 15 shows also the posterior probability, but this time conditioned to the viewpoint type (aerial/ground); as expected, the advantage of OURS over LCM is higher for ground-level views where element misplacement is more apparent and the lower resolution of the LCM plays an important role. Nevertheless, our segmentation outperformed LCM also for aerial views, presumably because LCM involves manual user input and lacks the fine-grained contours of our fully-automatic per-pixel classification.

Regarding the scoring task, we computed how likely each segmentation was to get the highest plausibility score in the 4-Likert scale. Figure 14-right shows that our method was significantly more likely to get the highest score. Summarizing, these results show that our segmentation pipeline is suitable for plausible detail synthesis and that it outperforms an official (expert-assisted) land cover map.

Figure 14: *Left*: Posterior probability $p(\theta|D)$ of each method (OURS, LCM) of being chosen as the most plausible in a selection round. LCM: 26% (21%-31% HDI); OURS: 74% (69%-79% HDI). *Right*: Posterior probability of each method (OURS, LCM) of getting the highest score in the scoring task. LCM: 32% (25%-40% HDI); OURS: 81% (75%-87% HDI). Shaded rectangles indicate the 95% Highest Density Interval (HDI).

11. Fully Convolutional Neural Networks

Recently, Deep Learning has been successfully applied to image segmentation using Fully Convolutional Neural Net-

Figure 15: Posterior probability of winning a selection round, conditioned on the camera elevation: close-up views (1 m to 30 m, *left*), and aerial views (90 m to 180 m, *right*).

works (FCN). In [35], Long et al. convert image classification networks into per-pixel segmentation networks by turning the fully-connected layers into convolutions, thus being able to output classification maps from any input size. Since typical classification architectures apply several pooling layers that reduce the size of the original image, the output classification map has lower resolution. The FCN proposed by Long et al. performs upsampling as well as fusing information from previous layers in order to output a per-pixel segmentation. They are able to reduce the maximum upsampling required from $32\times$ to $8\times$, but explain that fusing further layers to reduce the upsampling only yields slight improvements at a larger cost. In order to evaluate the use of FCNs in our pipeline, we used their implementation and trained weights of the network FCN-8s-atonce using Caffe [36]. This network does an $8\times$ upsampling and reported their best performance in the PASCAL VOC segmentation dataset.

First, we modified the last layer of the net to match our classes, and retrained using our fully-segmented Dataset AndorraSplit as 75% training and 25% validation. After 10 training epochs (11 min 38 s), the obtained accuracy was 89.26%. Classifying a 1000×1000 image took 15.42 s in CPU, 0.84 s in GPU. Figure 16 shows the output of this network. Note that the output is smooth, as the network is in fact learning an $8\times$ upsampling of the per-pixel labeling in its last layers. Modifying the network to avoid this upsampling was out of the scope of our work.

Figure 16: Part of Dataset Andorra. Left: aerial image, center-left: ground truth, center-right: classification using FCN-8s-atonce [35] with fully-classified training set, right: classification using FCN-8s-atonce [35] with nearly-homogeneous regions training set.

In the first test above, we trained the FCN using a complete per-pixel segmented dataset. However, our goal is to allow the user to train the classifier using a few homogeneous training regions, as in our experiments in Section 10. If we train the net in this way – by letting the loss function ignore pixels outside training regions –, results are much worse as shown in Figure 16 right-most image, which shows the classification after

100 training epochs (4 h 40 min). This can be caused by the net not being allowed to learn the shapes of boundaries between classes. Even after a huge training time, results are still far from an acceptable segmentation, effectively rendering FCNs unusable for our S4S pipeline.

12. Conclusions and future work

In this paper we have presented a complete pipeline for segmenting aerial images into tree, shrub, grass and terrain classes. Segmented images can be used by external vegetation synthesis algorithms to generate plausible vegetation on top of publicly-available DTMs, enabling detailed close-up views of real scenarios in videogames and entertainment applications.

The pipeline we propose is practical in the sense that relies on RGB+I orthorectified images which are commonly available. All datasets used for the experiments were downloaded from the public WMS of the Cartographic and Geological Institute of Catalonia (ICGC)¹. Using hyperspectral images or LiDAR data would clearly facilitate the segmentation, but at the expense of severely restricting the applicability of our approach to selected places.

The main issues arising when segmenting aerial images for generating synthetic detail can be summarized as follows: the classes (tree, shrub, grass and terrain are likely to be just a subset of the required classes), the associated CPU/GPU rendering techniques, and the visual impact of misclassification errors, are all scenario-dependent. Considering the large amount of time and effort required to obtain massive training sets, we have restricted our attention to classification algorithms able to deal with relatively small training sets.

Our experiments show that Random Forests provide an excellent option considering accuracy and performance both at training and inference times. RF training times in the order of a few minutes allow artists to experiment with different sets of classes (e.g. adding water or sand) and to add training examples from new segmented regions as soon as they become available. Fast inference times enable fast segmentation and data amplification.

We have analyzed the contribution of standard color and texture features in the context of S4S. Adding features from down-sampled images only yielded very slight accuracy improvements. We did expect a higher impact, considering the fact that human perception of vegetation types (at least on 25 cm/pixel aerial images) seems to be affected by surrounding regions (during the user study we observed that many users had to zoom in and out multiple times to classify some regions). The analysis of feature contributions revealed the key role of NDVI, an excellent discriminator of non-dry vegetation.

Regarding the impact of training set selection from manually segmented images, we have shown that training examples from homogeneous regions (the fastest manual labeling approach) lead to suboptimal accuracies. These results should help to guide human labelers to create effective training sets.

¹http://geoserveis.icgc.cat/icc_mapesbase/wms/service?

In our experiments with different datasets, our pipeline achieved an average 90% accuracy, which we take as a very good result considering the low accuracy of individual users when asked to classify manually these images.

As future work, we plan to enhance our segmentation approach with regression to estimate the height of vegetation; estimated height values could replace the individual labels for tree, shrub and grass classes. We also plan to extract features from LiDAR data, mainly to get massive training sets automatically (rather than using it as input for the segmentation, due to less availability of LiDAR data compared to aerial images). Tools for facilitating the manual segmentation of images tailored for the chosen labels and adapted to S4S problems is also an interesting venue for future work.

Acknowledgements. This work has been partially funded by the Spanish Ministry of Economy and Competitiveness and FEDER under grants TIN2014-52211-C2-1-R and TIN2014-56919-C3-2-R; and the Spanish Ministry of Education, Culture and Sports PhD grants FPU13/01079 and FPU14/00725.

References

- [1] Ruiz LA, Fdez-Sarría A, Recio JA. Texture feature extraction for classification of remote sensing data using wavelet decomposition: a comparative study. In: International Archives of Photogrammetry and Remote Sensing; vol. 35. 2004, p. 1682–750.
- [2] dos Santos JA, Penatti OAB, da Silva Torres R. Evaluating the potential of texture and color descriptors for remote sensing image retrieval and classification. In: VISAPP (2). 2010, p. 203–8.
- [3] Tokarczyk P, Montoya J, Schindler K. An evaluation of feature learning methods for high resolution image classification. ISPRS Annals of Photogrammetry, Remote Sensing and Spatial Information Sciences 2012;I-3:389–94. doi:10.5194/isprsannals-I-3-389-2012.
- [4] Penatti OAB, Nogueira K, dos Santos JA. Do deep features generalize from everyday objects to remote sensing and aerial scenes domains? In: Computer Vision and Pattern Recognition Workshops (CVPRW), 2015 IEEE Conference on. 2015, p. 44–51.
- [5] Aksoy S. Spatial techniques for image classification. Image processing for remote sensing 2008;:225–48.
- [6] Cheriadat AM. Unsupervised feature learning for aerial scene classification. Geoscience and Remote Sensing, IEEE Transactions on 2014;52(1):439–51.
- [7] Castelluccio M, Poggi G, Sansone C, Verdoliva L. Land use classification in remote sensing images by convolutional neural networks. CoRR 2015;abs/1508.00092.
- [8] Fröhlich B, Rodner E, Denzler J. Semantic segmentation with millions of features: Integrating multiple cues in a combined random forest approach. In: Lee K, Matsushita Y, Rehag J, Hu Z, editors. Computer Vision – ACCV 2012; vol. 7724 of *Lecture Notes in Computer Science*. Springer Berlin Heidelberg. ISBN 978-3-642-37330-5; 2013, p. 218–31.
- [9] Fröhlich B, Bach E, Walde I, Hese S, Schmullius C, Denzler J. Land cover classification of satellite images using contextual information. ISPRS Annals of Photogrammetry, Remote Sensing and Spatial Information Sciences 2013;II-3/W1:1–6. doi:10.5194/isprsannals-II-3-W1-1-2013.
- [10] Tokarczyk P, Wegner J, Walk S, Schindler K. Features, color spaces, and boosting: New insights on semantic classification of remote sensing images. Geoscience and Remote Sensing, IEEE Transactions on 2015;53(1):280–95.
- [11] Schindler K. An overview and comparison of smooth labeling methods for land-cover classification. Geoscience and Remote Sensing, IEEE Transactions on 2012;50(11):4534–45.
- [12] Andújar C, Chica A, Vico M, Moya S, Brunet P. Inexpensive reconstruction and rendering of realistic roadside landscapes. Computer Graphics Forum 2014;33(6):101–17.

- [13] Shaw GA, Burke HhK. Spectral imaging for remote sensing. Lincoln Laboratory Journal 2003;14(1):3–28.
- [14] Dachsbaecher C. Interactive terrain rendering: towards realism with procedural models and graphics hardware. Ph.D. thesis; University of Erlangen-Nuremberg; 2006.
- [15] Zhou H, Sun J, Turk G, Rehag JM. Terrain synthesis from digital elevation models. Visualization and Computer Graphics, IEEE Transactions on 2007;13(4):834–48.
- [16] Gnevaux JD, Galin E, Peytavie A, Gurin E, Briquet C, Grosbellet F, et al. Terrain modelling from feature primitives. Computer Graphics Forum 2015;34(6):198–210.
- [17] Peytavie A, Galin E, Grosjean J, Merillou S. Arches: a framework for modeling complex terrains. Computer Graphics Forum 2009;28(2):457–67.
- [18] Gurin E, Digne J, Galin E, Peytavie A. Sparse representation of terrains for procedural modeling. Computer Graphics Forum (proceedings of Eurographics 2016) 2016;35(2):177–87. URL: <http://dx.doi.org/10.1111/cgf.12821>. doi:10.1111/cgf.12821.
- [19] Argudo O, Andujar C, Chica A, Gurin E, Digne J, Peytavie A, et al. Coherent multi-layer landscape synthesis. The Visual Computer 2017;33(6-8):1005–15.
- [20] Argudo O, Chica A, Andujar C. Single-picture reconstruction and rendering of trees for plausible vegetation synthesis. Computers & Graphics 2016;57:55 – 67.
- [21] Shah MA, Kontinnen J, Pattanaik S. Real-time rendering of realistic-looking grass. In: Proceedings of the 3rd international conference on Computer graphics and interactive techniques in Australasia and South East Asia. ACM; 2005, p. 77–82.
- [22] Boulanger K, Pattanaik SN, Bouatouch K. Rendering grass in real time with dynamic lighting. IEEE Computer Graphics and Applications 2009;29(1):32–41.
- [23] He H, Garcia EA. Learning from imbalanced data. IEEE Transactions on Knowledge and Data Engineering 2009;21(9):1263–84.
- [24] Stockman G, Shapiro LG. Computer Vision. 1st ed.; Upper Saddle River, NJ, USA: Prentice Hall PTR; 2001. ISBN 0130307963.
- [25] Pouli T, Cunningham DW, Reinhard E. A survey of image statistics relevant to computer graphics. Computer Graphics Forum 2011;30(6):1761–88.
- [26] Roettger S. N-dvi-based vegetation rendering. In: Proceedings of the Ninth IASTED International Conference on Computer Graphics and Imaging 2007. CGIM '07; 2007, p. 41–5.
- [27] Ojala T, Pietikinen M, Menp T. Multiresolution gray-scale and rotation invariant texture classification with local binary patterns. IEEE Trans Pattern Anal Mach Intell 2002;24(7):971–87.
- [28] hovin L, Bosni Z. Empirical evaluation of feature selection methods in classification. Intelligent data analysis 2010;14(3):265–81.
- [29] O'brien DB, Gupta MR, Gray RM. Cost-sensitive multi-class classification from probability estimates. In: Proceedings of the 25th international conference on Machine learning. ACM; 2008, p. 712–9.
- [30] Whitehill J, fan Wu T, Bergsma J, Movellan JR, Ruvolo PL. Whose vote should count more: Optimal integration of labels from labelers of unknown expertise. In: Bengio Y, Schuurmans D, Lafferty JD, Williams CKI, Culotta A, editors. Advances in Neural Information Processing Systems 22. Curran Associates, Inc.; 2009, p. 2035–43.
- [31] Mineiro P. Modeling mechanical turk. <http://www.machinedlearnings.com/2011/01/modeling-mechanical-turk.html>; 2011.
- [32] Berthold MR, Cebon N, Dill F, Gabriel TR, Ktter T, Meinl T, et al. KNIME: The Konstanz Information Miner. Berlin, Heidelberg: Springer Berlin Heidelberg. ISBN 978-3-540-78246-9; 2008, p. 319–26.
- [33] Kruschke J. Doing Bayesian Data Analysis. 2nd ed.; Academic Press; 2014. ISBN 9780124058880.
- [34] Gryka M, Terry M, Brostow GJ. Learning to remove soft shadows. ACM Transactions on Graphics 2015;34(5):153:1–153:15.
- [35] Long J, Shelhamer E, Darrell T. Fully convolutional networks for semantic segmentation. In: The IEEE Conference on Computer Vision and Pattern Recognition (CVPR). 2015;.
- [36] Jia Y, Shelhamer E, Donahue J, Karayev S, Long J, Girshick R, et al. Caffe: Convolutional architecture for fast feature embedding. arXiv:14085093 2014;.