COMPARISON OF DIFFERENT WASTEWATER TREATMENTS FOR COLOUR REMOVAL OF REACTIVE DYE BATHS

Journal:	<i>Desalination and Water Treatment</i>
Manuscript ID:	TDWT-2014-2004.R1
Manuscript Type:	Original Paper
Date Submitted by the Author:	n/a
Complete List of Authors:	Lopez-Grimau, Victor; Universitat Politecnica de Catalunya, Vilaseca, Merce; Universitat Politecnica de Catalunya, INTEXTER Gutierrez-Bouzan, Carmen; Universitat Politecnica de Catalunya, INTEXTER
Keywords:	Colour removal, Reactive dyes, Electrochemical treatment, Moringa oleifera, Natural coagulant, Enzymatic treatment, Laccase

SCHOLARONE™
Manuscripts

COMPARISON OF ~~DIFFERENT NEW~~ WASTEWATER TREATMENTS FOR
COLOUR REMOVAL OF REACTIVE DYE BATHS

Víctor López-Grimau^{a,b,*}, Mercè Vilaseca^a, Carmen Gutiérrez-Bouzán^a

^a INTEXTER, Institute of Textile Research. Universitat Politècnica de Catalunya, 08222 Terrassa, Spain, Tel. +34 93 7398008; emails: victor.lopez-grimau@upc.edu (V. López-Grimau), vilaseca@intexter.upc.edu (M. Vilaseca), gutierrez@intexter.upc.edu (C. Gutiérrez-Bouzán).

^b. Department of Projects Engineering, ETSEIAT. Universitat Politècnica de Catalunya, 08222 Terrassa, Spain, Tel. +34 93 7397316

* Corresponding author

ABSTRACT

The generation of high coloured wastewater is one of the main environmental problems of the textile industry. Reactive dyes are widely used in the dyeing of cellulosic fibres. However, they have low exhaustion degree (70%-90%). The degradation of residual dyes by ~~aerobic conventional~~ biological treatment is very poor, being necessary the application of specific treatments. In this work, three different methods for the removal of reactive dyes were compared: electrochemical treatment, coagulation with Moringa oleifera waste and enzymatic treatment with Laccase. Two azo bifunctional dyes with different reactive groups were selected: C.I. Reactive Black 5 (vinylsulfone) and C.I. Reactive Red 231 (chlorotriazine). The influence of pH (5 and 9) and dye hydrolysis on the decolourisation yield was studied. The electrochemical treatment was the most efficient, with 95-100% colour removal yield. The coagulation with Moringa oleifera waste also achieved high colour removal efficiency (91-94%). Both methods showed an independent behaviour with respect to pH or dye hydrolysis. The enzymatic treatment should be performed at pH 5. This method was suitable to remove the chlorotriazine dye (92-93% efficiency) whereas the vinylsulfone one showed a marked dependence on dye hydrolysis: moderately efficient for the hydrolysed dye and highly efficient without hydrolysis. The activity of Laccase was not modified by the ~~usual~~ salinity

of the reactive dyeing effluent (20 g/L NaCl). ~~Nevertheless, This factor the~~
effluent salinity enhanced the electrochemical and Moringa oleifera treatment
yield.

*Keywords: Colour removal; Reactive dyes; Electrochemical treatment; Moringa
oleifera; Natural coagulant; Enzymatic treatment; Laccase.*

1. INTRODUCTION

Worldwide, 280,000 tons of textile dyes are discharged in industrial effluents
every year, being azo dyes the most widely used with more than 60% of the
total dye production [1]. The aromatic amines generated from dyes reduction
can be harmful and some of them have been classified as carcinogenic and
genotoxic by the International Agency for Research on Cancer [2]. The
presence of toxic and carcinogenic products in textile dyeing effluents is a
problem added to the high coloration inherent to this type of effluents [3], mainly
taking into account the large volume of wastewater generated by textile
industry.

Among the different kind of textile dyes, reactive ones are widely used in the
dyeing of cotton and other cellulosic fibres since they offer high washing
fastness and brilliant colours. Reactive dyes represent the 25% of the total
world market [4]. In opposite, these dyes have a low degree of exhaustion and
fixation, from 70% to 90% [5]. Therefore, an important percentage of dye
remains in its hydrolysed and unfixed form in the exhausted dye bath or it is
removed in the washing liquors.

The degradation of residual dyes by aerobic conventional-biological treatment
by activated sludge is very poor, since they have low biodegradability and they
are also poorly adsorbed in the activated sludge [6]. As biological treatments
are not able to remove colour properly, the application of specific treatments is
required in order to accomplish current regulations. There are different
techniques to achieve colour removal, ~~and among them~~, the most used are:
activated carbon adsorption [7-86-7], membrane filtration [9-108-9], coagulation-
flocculation processes [11-1240-11] and treatment with ozone [13-1412-13].

These technologies have been applied at industrial scale, offering a good colour removal, but they have a high cost of operation and maintenance in the case of membrane technologies and ozonolysis or high cost of chemical products in the case of activated carbon and coagulation-flocculation reagents [5]. Different research groups are working, at laboratory and pilot plant scale, on diverse new methods: low cost adsorbents [15-16][4-15], natural coagulants [17-18][6-17], enzymatic action of specific microorganisms [19-20][8-19], anaerobic bioreactors [21][20] or advanced oxidation methods (Fenton and Photo-Fenton reactions [22-23][21, 22], heterogeneous photocatalysis [24-25][23, 24] or electrochemical oxidation [26-27][25, 26]).

~~In this work, three different methods for the removal of reactive dyes were compared: electrochemical degradation, coagulation with an agricultural by-product and enzymatic treatment.~~

The electrochemical oxidation is an advanced oxidation method (AOM) which provides great advantages in the treatment of high coloured textile wastewater: wastes are not generated and the addition of chemical compounds (organic or inorganic) is not required. In fact, the salt added during the dyeing process with reactive dyes acts as support electrolyte during the electrolysis. The only requirement is the power supply which can be minimized by optimizing operational conditions [27][26].

On the other hand, the use of agricultural by-products as coagulants is a low cost alternative to traditional chemical coagulants (aluminum and ferrum salts). This is the case of the residues generated after oil extraction of *Moringa oleifera* seeds. These residues have a high content of positive charged protein which acts as coagulant. *Moringa oleifera* has been widely applied to eliminate turbidity in drinking water [28][27] and more recently to eliminate colour of industrial wastewater [29][28].

Moreover, some bacteria and fungi are able to degrade recalcitrant compounds such as reactive dyes by enzymatic action [30][29]. This is the case of laccase from the ascomycete *Myceliophthora thermophila* [31][30]. Enzymes are highly selective and may be affected by changes in pH and salinity. Furthermore, in many cases the enzyme action requires the addition of an organic mediator,

such as ABTS (2,2'-azino-bis(3-ethylbenzothiazoline-6-sulfonic acid)) or HBT (1-hydroxybenzotriazole) [32].

In this work, these three methods (electrochemical, *Moringa oleifera* waste and laccase) ~~were~~ **are** applied to the removal of colour from reactive dyebaths. Two azo reactive dyes ~~were selected~~: C.I. Reactive Black 5 and C.I. Reactive Red 231. ~~This dyes have—with~~ different reactive groups (vinylsulfone and chlorotriazine ~~respectively~~) ~~were selected~~ in order to study their influence on the treatment efficiency. The effect of pH and dye hydrolysis on the decolourisation yield was also studied. In addition, the influence of high salt concentration was evaluated, due to the high salinity characteristic of reactive dye effluents.

2. EXPERIMENTAL

2.1 Dye solutions

Two azo reactive dyes widely used ~~in on~~ cotton dyeing industries were selected in this study: Colour Index (C.I.) Reactive Black 5 (referred as RB5) and C.I. Reactive Red 231 (RR231). Both are bifunctional: RB5 has two vinylsulfonic groups whereas RR231 has two monochlorotriazinic ones. The chemical structure of dyes is shown in Figure 1.

(a)

(b)

Figure 1. Chemical structure of the two selected dyes: (a) C.I. Reactive Black 5 (RB5), (b) C.I. Reactive Red 231 (RR231).

Simulated dye baths were prepared at a dye concentration of 0.1 g/L in decalcified water. Decolourisation tests were carried out at pH 5 and 9, adjusted with HCl 1M or NaOH 1M. To simulate a residual reactive dyeing baths, ~~up to~~ 20 g/L NaCl was added to all dye solutions.

The effect of dye hydrolysis on the efficiency of the three decolourisation methods was studied with the two dyes since they contain different reactive groups. The general reactions of hydrolysis for vinylsulfonic dyes (react. 1) and chlorotriazinic dyes (react. 2) are as follows:

The hydrolysis of chlorotriazinic dyes only implies the substitution of Cl⁻ by OH⁻, whereas the hydrolysis of vinyl sulfonic dyes suppose the loss of a sulfonic group which can affect to the dye removal efficiency. Dye hydrolysis was carried out by boiling for 2h the dye solutions at pH 12.

2.2 Electrochemical treatment

Electrochemical treatments were conducted in an electrolytic cell, which was undivided. The cathodes were constituted by titanium and the anodes were made of titanium, covered by platinum oxides (Ti/PtOx anodes). The total surface area of each electrode was 486 cm² and the distance between the electrodes was 2 mm. The volume of the vessel was 1 L.

The experimental plant was completed by a pump to feed the cell and a tank to store the treated wastewater. This plant operated continuously at a flow rate of 20 L/h [27]. The current was regulated by the source supply among 0 and 25 A (current density range: 0- 50 mA/cm²). The electrical consumption was

registered during the treatment [as Wh/L taking into account the time of treatment and the volume of the sample.](#)

.

2.3 Moringa oleifera coagulation

Dry Moringa oleifera seeds were supplied by the *Centre National de Semences Forestières* of Burkina Faso. Shells were removed manually and kernels were reduced to powder using a domestic grinder (Moulinex). 1g of M. oleifera powder fed to a Soxhlet extractor fitted with a 250 mL round-bottom flask and a condenser. The extraction was run for 2 hours with 100 mL of hexane (Sharlab). After the extraction, the solvent was distilled off under vacuum in a rotary evaporator. The oil extraction yield was 36.1%. Protein content of the Moringa oleifera seeds was determined by analysis of Nitrogen Kjeldahl (protein= N(%) x 6.25). The protein content of seeds before extraction was 25.0% and after extraction with ethanol was 34.4%. This increase in the protein content should favour the coagulant effect of Moringa oleifera solutions.

Oilseed residues were used to prepare a suspension at 5% (w/v) in distilled water by stirring at room temperature for 2 hours. [Later the suspension was filtered with 0.45 µm glass filter \(Millipore\).](#) Colour removal tests were carried out with [solutions of Moringa oleifera](#) at different concentrations ~~of Moringseed extraction waste~~, ranging from 250 to 1,250 mg/L. [Trials with 1 liter of dye solution samples were performed in a Jar Test.](#) The samples were first submitted to a fast stirring at 150 rpm for 10 minutes, subsequently they were stirred slowly at 20 rpm for 30 minutes [\[33\]](#) and finally they were allowed to stand 1 hour [in Imhoff cones](#) to promote natural decantation [\[34\]](#).

2.4 Enzymatic treatment

Laccase from the ascomycete *Myceliophthora thermophila* was selected for the enzymatic treatments. Laccase solutions were supplied by Novozymes (Davis, CA, USA). Commercial solutions were initially filtered with a cartridge Sep-Pack C18 (Waters Associates, Milford, USA). Lacasse activity was determined

spectrophotometrically by oxidation of ABTS (2, 2'-azino-di-[3-ethyl-benzothiazoline-(6)-sulfonic acid]) supplied by Sigma-Aldrich (Madrid, Spain). The reaction was monitored at room temperature by measuring the change in absorbance at 436 nm for 2 min. One activity unit was defined as the amount of enzyme that oxidized 1 μ mol of ABTS per minute and the activities were reported as U/mL. The Laccase enzyme solution showed 400 U/mL of activity. The pH of dye solutions was fixed at 5 by addition of 0.1M acetate/acid acetic buffer solution pH 5, [as it is a common procedure in previous literature focused on the removal of Reactive Black 5 solutions \[35-36\]](#). According to our previous studies no organic mediator was added to dye solutions and all the experiments were performed at 50 $^{\circ}$ C for 24-48h with the addition of 4 U/mL of enzyme concentration.

2.5 Colour removal measurements

Colour removal values were calculated from absorbance measurements at the maximum absorbance wavelength of each dye (599 for RB5 dye and 522 nm for RR231 dye). The absorbance measurements were carried out with a UV-visible spectrophotometer Shimadzu UV-2401 PC model (Japan). The linearity interval was previously established. All dye removal tests were carried out in triplicate.

3. RESULTS AND DISCUSION

3.1 Electrochemical treatment

The results of colour removal obtained in the electrochemical treatment are shown in Figure 2. Current density was initially fixed at 24 mA/cm² according to previous studies [\[27\]](#). As can be seen, the same experiments were performed with dyes not hydrolysed and with solutions of dyes previously hydrolysed.

Figure 2. Colour removal by electrochemical treatment (0.1 g/L dye, 20 g/L NaCl; Current density 24 mA/cm²).

Figure 2 evidences that colour removal results were almost independent on pH. Dye oxidation mainly occurs through the action of oxidant species generated in the anode (Cl_2 , $\text{Cl}\cdot$, $\text{Cl}_2\cdot$, $\text{ClOH}\cdot$) which are independent on the pH [27]. The electrochemical treatment reached 98-100% of colour removal for RR231 dye and 95-96% for RB5. On the other hand, the dye hydrolysis did not have any significant effect on the efficiency of the electrochemical treatment. Decolourisation is mainly caused by the breakage of the chromophore (azo bond) [37]. The hydrolysis of the reactive group, located in different points of the dye molecule is not a decisive factor in this reaction and does not have effect on the efficiency of the electrochemical treatment.

Consequently, solutions with hydrolysed dye at pH 9 were selected to optimise the current to be applied during the electrochemical treatment, as these conditions are similar to those of industrial residual dye baths. With this purpose, experiments at different current densities were carried out (Figure 3).

Figure 3. Optimisation of the electrochemical treatment (0.1 g/L hydrolysed dye, pH9, 20 g/L NaCl).

As is shown in Figure 3, colour removal results were better for RR231 than for RB5. In this sense, almost total decolourisation was obtained for RR231 at 12 mA/cm² and 94% colour removal was reached for RB5, which electrical consumption corresponded to 12.4 Wh/L. However, it can be underlined that in the case of RR231, 6 mA/cm² current density was sufficient to obtain more than 90% colour removal, which implied that the electrical consumption was drastically reduced to 6.7 Wh/L. Between the two dyes, the differences in colour removal can be attributed to their different molecule structure. Both dyes have two azo chromophore groups to be degraded, so the difference between their decolourisation yield is attributed to the rest of their molecular structure [38]. RB5 degradation can produce any intermediate capable of giving slight colour to the water.

3.2 Moringa oleifera coagulation

Results of coagulation with Moringa oleifera suspensions are shown in Figure 4. Initially, the concentration of Moringa oleifera was fixed at 1,000 mg/L, which is a common concentration of coagulant for this type of industrial wastewater [39].

Figure 4. Colour removal by *Moringa Oleifera* coagulation (0.1 g/L dye, 20 g/L NaCl; *Moringa oleifera* 1,000 mg/L).

As can be seen in Figure 4, *Moringa oleifera* waste had high coagulation action (90-94% of colour removal) for all experimental conditions, independently of the pH or the dye hydrolysis. Previous studies reported the interaction between the sulfonic groups of the dyes and the positive charged proteins of *Moringa oleifera* [29, 33]. This interaction is independent of the pH. *Moringa oleifera* provided good colour removal yield for RR231 whether or not the dye was hydrolysed. However, for RB5 the efficiency was slightly lower when the dye was hydrolysed. This fact could be attributed to the loss of two sulfonic groups due to the hydrolysis of vinyl sulfonic dyes.

As can be seen in Figure 4, *Moringa oleifera* waste had high coagulating action whether or not the dye is hydrolysed for both dyes. The dye molecule size or reactive group do not show any influence on the treatment yield (RB5: smaller molecule and two vinyl sulfone reactive groups; RR231: larger molecule and two monochlorotriazine reactive groups). In this sense, the loss of two sulfonic groups due to the hydrolysis of vinyl sulfonic dyes did not affect the efficiency of the *Moringa oleifera* treatment. Moreover, colour removal yield higher than 90% was achieved for both dyes, independently of the pH.

In order to optimise the addition of coagulant to the dye solutions, decolourisation tests were performed with solutions of hydrolysed dye at pH9 to simulate the industrial reactive dye baths. Several *Moringa oleifera* suspensions were prepared in a range 250 mg/L - 1250 mg/L. Dye removal results are shown in Figure 5.

Figure 5. Coagulation dose optimisation for *Moringa oleifera* waste suspensions (0.1 g/L hydrolysed dye, pH9, 20 g/L NaCl).

Figure 5 evidences slightly better performance of *Moringa oleifera* suspensions to remove RR231 than RB5. RR231 removal reached 90% with the 750 mg/L *Moringa* solution whereas RB5 required the addition of 1,000 mg/L *Moringa oleifera* to achieve the same level of colour removal. [The higher efficiency on the removal of RR231 respect to RB5 could be attributed to its higher number of negative sulfonic groups \(8 groups for RR231 respect to 4 groups for RB5\).](#)

3.3 Enzymatic treatment

Results of colour removal obtained by applying enzymatic treatment are shown in Figure 6. In any case, Laccase provided good colour removal yield for RR231 dye (88-93%). For RB5 the efficiency was highly dependent on dye hydrolysis (53-61 % vs. 88-91%). This can probably be attributed to the effect of

vinylsulfone reactive groups on the enzyme activity. Zille et al. [35] stated that Laccase reacts with dyes by electrostatic interaction between negative charged sulfonic groups of the dyes and amino acids of the enzymes. The hydrolysis of the two vinylsulfone groups of RB5 implied the loss of two sulfonic groups which did not occur in the case of hydrolysis of the RR231 triazine groups. In fact, RR231 dye maintain their 8 sulfonic groups after dye hydrolysis. On the other hand, 48h reaction time provided slightly better results than 24h. This results were in accordance with previous studies where an increase of decolourisation was reported when the incubation time was extended from 24h to 48h [36].

Figure 6. Dye removal by enzymatic treatment (0.1 g/L dye, 20 g/L NaCl, pH fixed at 5, enzyme concentration 4 U/mL).

Finally, it is important to underline that inhibitory phenomena were not observed in the enzymatic treatments although all the experiments were carried out in high saline medium. Furthermore, the addition of electron transfer mediator or co-substrate was not necessary; unlike other enzymes reported for decolourisation studies [20][49].

3.4. Comparison of the treatment methods

The three technologies studied in this work demonstrated to be effective for the removal of reactive dyes in simulated residual dyebaths. As can be seen in Table 1, despite the very different chemical constitution (molecular size and reactive groups) of the two selected dyes, for each type of treatment it was possible to find experimental conditions which enabled to remove at least 90% dye.

Table 1. Colour removal yield (%) of the different treatments.

Dye	Electrochemical				Moringa Oleifera				Enzymatic	
	Hydrolysed		Not hydrolysed		Hydrolysed		Not hydrolysed		Hydrolysed	Not hydrolysed
	pH 5	pH 9	pH 5	pH 9	pH 5	pH 9	pH 5	pH 9	pH 5	pH 5
RB5	95	96	96	96	90	90	93	94	61	90
RR231	98	100	99	100	93	92	93	94	92	93

The electrochemical treatment provided excellent results: colour removal in the range 95-100%, almost independent on dye hydrolysis and pH. The characteristic high salinity of the industrial reactive dye effluents is a factor that enhances the performance of the electrochemical treatment and reduces the electrical consumption and consequently, the cost of the treatment. An additional advantage of the electrochemical method is that it can be considered as a clean technology because the addition of chemical reagents is not required, no wastes are generated and dyes are degraded, which enables the reuse of the treated effluent.

The Moringa Oleifera waste applied to the coagulation of reactive dyes has also shown to be an interesting option. Both dyes exhibited removal yield results in the range 90-94 %. As in the previous case, the salinity of the effluent also demonstrated to be a positive factor for the treatment efficiency (see section 3.2). In addition, results are also almost independent of the other variables: pH and dye hydrolysis. For these reasons, to the use of Moringa Oleifera waste as reactive dye coagulant constitutes an interesting low-cost and natural alternative to substitute the conventional chemical coagulants-flocculants. On another hand, the addition of Moringa oleifera supposes a low increase of COD which can be easily eliminated in the subsequent biological treatment plant. The increase of COD is slight in comparison with the organic content of industrial textile waste waters. In this sense, the use of Moringa oleifera as well as the

[other two methods described in this work are thought as specific methods to remove non biodegradable dyes and they are proposed as a previous step to biological aerobic treatment. Once the dye is eliminated the water can be discharged to the biological plant to follow up with the degradation of the rest of organic matter.](#)

With respect to enzymatic treatment, results can be considered in general very positive because Laccase activity is not influenced by the salinity of the effluent, as it was shown in section 3.3, [in opposite to previous studies which reported inhibitory effects caused by the high salinity of the dye effluents \[40\]](#). However, the treatment is very sensitive to pH variations: the effluent should be buffered at pH 5. This implies an additional cost and an increase of wastewater salinity as reactive dye effluents which are typically alkaline. In addition, the dye hydrolysis constitutes also an important factor to take into account in the case of vinylsulfonic dyes.

4. CONCLUSIONS

The comparison of the three decolourisation methods studied in this work leads to the conclusion that the electrochemical treatment was the most efficient (95-100% colour removal yield).

The coagulation with *Moringa oleifera* also achieved high colour removal efficiency for both dyes (91-94%).

Enzymatic treatment provided good colour removal yield for RR231 (92-93%) whereas for RB5 the efficiency was highly dependent on dye hydrolysis (61-90%). ~~That is to say, in the case of the vinylsulfone dye, this treatment showed a marked dependence on dye hydrolysis, being moderately efficient for the hydrolysed dye and highly efficient without hydrolysis. This difference can probably be attributed to the effect of sulfonic groups on the enzyme activity when the vinylsulfone dye is not hydrolysed.~~

~~On the other hand, results of E~~electrochemical and *Moringa oleifera* treatments were almost independent on pH whereas in the case of the enzymatic treatment, the pH should be carefully controlled (pH buffered at 5).

~~In addition, both electrochemical and Moringa oleifera treatments promising to remove colour of industrial effluents containing reactive dyes, because they were very efficient independently on pH range and dye hydrolysis conditions and because their yield is enhanced by the effluent salinity.~~

Therefore, both electrochemical and Moringa Oleifera treatments have shown to be attractive as new alternative methods for colour removal, whereas Laccase can only be applied for the removal of reactive dyes under controlled conditions.

378

379 **ACKNOWLEDGEMENTS**

380 The authors thanks the Spanish Ministry of Economy (MINECO) for its financial
381 support (Project CTM2012-31461).

382

383 **REFERENCES**

- 384 1. M. Solis, A. Solis, H.I. Perez, N. Manjarrez and M. Flores, Microbial
385 decolouration of azo dyes: A review, *Process Biochemistry*, 47 (2012) 1723-
386 1748.
- 387 2. IARC. Overall evaluations of carcinogenicity to humans. In: IARC
388 monographs, International Agency for Research on Cancer, Lyon 2004, pp. 1-
389 82.
- 390 3. V. López-Grimau, M. Riera-Torres, M. Lopez-Mesas and C. Gutierrez-
391 Bouzan, Removal of aromatic amines and decolourisation of azo dye baths by
392 electrochemical treatment, *Color. Technol.*, 129 (2013) 267-273.
- 393 4. P.A. Carneiro, M.E. Osugi, C.S. Fugivara, N. Boralle, M. Furlan and M.V.
394 Zanoni, Evaluation of different electrochemical methods on the oxidation and
395 degradation of Reactive Blue 4 in aqueous solution, *Chemosphere*, 59 (2005)
396 431-439.
- 397 5. V. López-Grimau and C. Gutiérrez-Bouzán, Selection of decolorization
398 methods of reactive dye baths for reuse purposes. In *Dyeing: Processes,*
399 *techniques and applications.* Jie Fu; Nova Publishers Inc., New York 2013,
400 Chapter 10, pp. 205-216.

- 401 | [6. A. Pala and E. Tokat, Color removal from cotton textile wastewater in an](#)
402 | [activated sludge system with various additives. Water Res., 38 \(2002\) 2920-](#)
403 | [2925.](#)
- 404 | [76. A. Gurses, Ç. Dogar, S. Karaca, M. Açıkyidiz and R. Bayrak, Production of](#)
405 | [granular activated carbon from waste Rosa canina sp. Seeds and its adsorption](#)
406 | [characteristics for dye, J. Hazard. Mater., 131 \(2006\) 254-259.](#)
- 407 | [87. S. Wang and Z.H. Zhu, Effects of acidic treatment of activated carbons on](#)
408 | [dye adsorption, Dyes Pigm., 75 \(2007\) 306-314.](#)
- 409 | [98. J.J. Qin, M.H. Oo and K.A. Kekre,. Nanofiltration for recovering wastewater](#)
410 | [from a specific dyeing facility. Sep. Purif. Technol, 56, \(2007\) 199-203.](#)
- 411 | [109. I. Petrinic, N.P. Andersen, S. Sostar-Turk and A.M. Le Marechal, The](#)
412 | [removal of reactive dye printing compounds using nanofiltration, Dyes Pigm., 74](#)
413 | [\(2007\) 512-518.](#)
- 414 | [1140. V. Golob, A. Vinder and M. Simonc, Efficiency of the](#)
415 | [coagulation/flocculation method for the treatment of dyebath effluents, Dyes](#)
416 | [Pigm., 67 \(2005\) 93-97.](#)
- 417 | [1244. A.Y. Zahrim, C. Tizaoui and N. Hilal. Evaluation of several commercial](#)
418 | [synthetic polymers as flocculant aids for removal of highly concentrated C.I.](#)
419 | [Acid Black 210 dye. J Hazard Mater., 182 \(2010\) 624-630.](#)
- 420 | [1342. M. Constapel, M. Schellenträger, J. M. Marzinkowski and S. Gäb,](#)
421 | [Degradation of reactive dyes in wastewater from textile industry by ozone:](#)
422 | [analysis of the products by accurate masses, Water Res. 43 \(2009\) 733-743.](#)
- 423 | [1443. S. Song, H. Ying, Z. He and J.Chen, Mechanism of decolourization and](#)
424 | [degradation of CI Direct Red 23 by ozonation combined with sonolysis,](#)
425 | [Chemosphere, 66 \(2007\) 1782-1788.](#)
- 426 | [1544. V.K. Gupta, Suhas, Application of low-cost adsorbents for dye removal –](#)
427 | [A review. J. Environ. Manage. 90 \(2009\) 2313-2342.](#)
- 428 | [1645. E.A. Oliveira, S.F. Montanher and M.C. Rollemberg, Removal of textile](#)
429 | [dyes by sorption on low-cost sorbents. A case study: sorption of reactive dyes](#)
430 | [onto Luffa cylindrica, Desal. Wat. Treat., 25 \(2011\) 54-64.](#)

431 | [1746](#). Y. Chun-Yang, Emerging usage of plant-based coagulants for water and
432 | wastewater treatment. *Process Biochem.*, 45 (2010) 1437-1444.

433 | [1847](#). A.K. Verma, R.D. Dash and P. Bhunia, A review on chemical
434 | coagulation/flocculation technologies for removal of colour from textile
435 | wastewaters. *J. Environ. Manage.*, 93 (2012) 154-168

436 | [1948](#). P.D. Shah, S.R. Dave and M.S. Rao, Enzymatic degradation of textile
437 | dye Reactive Orange 13 by newly isolated bacterial strain *Alcaligenes faecalis*
438 | PMS-1. *Int. Biodeterior. Biodegrad.*, 69 (2012) 41-50.

439 | [2049](#). L. Mendoza, M. Jonstrup, R. Hatti-Kaul and B. Mattiasson, Azo dye
440 | decolorization by laccase/mediator system in a membrane reactor: Enzyme and
441 | mediator reusability. *Enzyme Microb. Technol.* 49 (2011) 478-484.

442 | [2120](#). F.P. Van der Zee and S. Villaverde. Combined anaerobic-aerobic
443 | treatment of azo dyes—A short review of bioreactor studies. *Water Res.*, 39
444 | (2005) 1425-1440.

445 | [2224](#). S.Papic, D. Vujevic, N. Koprivanac and D.Sinko, Decolourization and
446 | mineralization of commercial reactive dyes by using homogeneous and
447 | heterogeneous Fenton and UV/Fenton processes. *J. Hazard. Mater.*, 164
448 | (2009) 1137-1145.

449 | [2322](#). Y. Li, T. Zhou, X. Lu, J. Wang and F-S. Wong, Rapid decolorization and
450 | mineralization of simulated textile wastewater in a heterogeneous Fenton like
451 | system with/without external energy. *J. Hazard. Mater.* 165 (2009) 193-199.

452 | [2423](#). M. Muruganandham and M. Swaminathan, Photocatalytic decolourisation
453 | and degradation of Reative Orange 4 by TiO₂-UV process. *Dyes Pigm.*. 68
454 | (2006) 133-142.

455 | [2524](#). T. Visa, M. Sanchez, V. López-Grimau, R. Navarro and S. Reche,
456 | Gutiérrez-Bouzán, M.C. Photocatalysis with titanium dioxide to remove colour of
457 | exhausted reactive dyebaths without pH modification. *Desal. Water Treat.*. 45
458 | (2012) 91-99.

459 | [2625](#). M.S. Morsi, A.A. Al-Sarawy and W.A. Shehab El-Dein, Electrochemical
460 | degradation of some organic dyes by electrochemical oxidation on a Pb/PbO₂
461 | electrode. *Desal. Wat. Treat.*. 26 (2011) 301-308.

- 462 | [2726](#). V. Lopez-Grimau and M.C. Gutierrez, Decolourisation of simulated
463 | reactive dyebath effluents by electrochemical oxidation assisted by UV light.
464 | Chemosphere. 62 (2006) 106-112.
- 465 | [2827](#). A. Ndabigengesere and K.S. Narasiah, Quality of water treated by
466 | coagulation using Moringa oleifera seeds. Water. Res.. 32 (1998) 781-791.
- 467 | [2928](#). J. Beltran-Heredia and J. Sanchez-Martin, Azo dye removal by Moringa
468 | oleifera seed extract coagulant. Color. Technol.. 124 (2008) 310-317.
- 469 | [3029](#). P.D. Shah, S.R. Dave and M.S. Rao, Enzymatic degradation of textile
470 | dye Reactive Orange 13 by newly isolated bacterial strain *Alcaligenes faecalis*
471 | PMS-1. Int. Biodeterior. Biodegrad., 69 (2012) 41-50.
- 472 | [3130](#). A. Kunamneni, I. Ghazi, S. Camarero, A. Ballesteros, F.J. Plou and M.
473 | Alcalde, Decolorization of synthetic dyes by laccase immobilized on epoxy-
474 | activated carriers. Process Biochem., 43 (2008) 169-178.
- 475 | [32](#). S. Rodríguez Couto, M.A. Sanromán and G.M. Gübitz, Influence of redox
476 | mediators and metal ions on synthetic acid dye decolourization by crude
477 | laccase from *Trametes hirsute*. Chemosphere, 58 (2005) 417-422.
- 478 | [33](#). M. Vilaseca, V. López-Grimau and C. Gutiérrez-Bouzán. Valorization of
479 | Waste Obtained from Oil Extraction in Moringa Oleifera Seeds: Coagulation of
480 | Reactive Dyes in Textile Effluents. Materials 7 (2014), 6569-6584.
- 481 | [34](#). APHA-AWWA-WEF. Method 2540 (F). Settleable solids. Standard Methods
482 | for the Examination of Water and Wastewater. 20th ed. Washington, D.C.:
483 | American Public Health Association; 1998.
- 484 | [35](#). A. Zille, T. Tzankov, G. Gübitz and A. Cavaco-Paulo, Immobilized laccase
485 | for decolourization of Reactive Black 5 dyeing effluent. Biotechnol. Lett., 25
486 | (2003) 1473-1477.
- 487 | [36](#). K. Murugesan, A. Dhamija, I.H. Nam, Y.M. Kim and Y.S. Chang.
488 | Decolourization of reactive black 5 by laccase: Optimization by response
489 | surface methodology. Dyes Pigm. 75 (2007) 176-184.
- 490 | [37](#). M. Riera-Torres and C. Gutiérrez-Bouzán. Optimisation of the
491 | electrochemical and UV combined treatment to remove colour and organic

1
2
3 492 [halogenated compounds of textile effluents. Sep. Purif. Technol. 98 \(2012\),](#)
4 493 [375-382.](#)
5
6 494 [38. M. Sala, A.I. del Río, J. Molina, F. Cases and M.C. Gutiérrez-Bouzán.](#)
7 495 [Influence of Cell Design and Electrode Materials on the Decolouration of Dyeing](#)
8 496 [Effluents. Int. J. Electrochem. Sci. 7 \(2012\) 12470 – 12488.](#)
9
10 497 [39. A.K. Verma, R.D. Dash and P. Bhunia. A review on chemical](#)
11 498 [coagulation/flocculation technologies for removal of colour from textile](#)
12 499 [wastewaters. J. Environ. Manage. 93 \(2012\), 154-168.](#)
13
14 500 [40. E. Rosales, M. Pazos and M.A. Sanromán. Comparative efficiencies of the](#)
15 501 [decolourisation of leather dyes by enzymatic and electrochemical treatments.](#)
16 502 [Desalination 278 \(2011\) 312-317.](#)
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60