Potential of Spaceborne GNSS Reflectometry for Soil Moisture, Biomass and Freeze-Thaw Monitoring: Summary of an ESA-Funded Study

N. Pierdicca, D. Comite, A. Camps, H. Carreno-Luengo, L. Cenci, M. P. Clarizia, F. Costantini, L. Dente, L. Guerriero, A. Mollfulleda, S. Paloscia, H. Park, E. Santi, M. Zribi, and N. Floury

Abstract— This work presents an overview of the activity developed in the frame of a project funded by the European Space Agency. The research was focused on the study of the potential applications of Global Navigation Satellite System Reflectometry (GNSS-R) over land, with emphasis on soil moisture and biomass. A study about the sensitivity with respect to the freeze-thaw dynamics was considered as well. The work started with an analysis of the sensitivity of GNSS-R reflectivity collected by the TechDemoSAT-1 experimental satellite. Although to a limited extent, the CyGNSS (Cyclone Global Navigation Satellite System) constellation was considered as well. The encouraging sensitivity outcomes led to the development of retrieval algorithms, three different approaches for soil moisture and one for biomass based on neural networks.

A more theoretical investigation was carried out to better understand and predict the signal from a satellite platform, which required to update two different models. Topography effects and sensitivity to moisture and roughness of a rough soil were included, as well as the effect of vegetation cover.

The project was carried out by a large team involving different research groups in Europe. It has led to main conclusions and recommendations derived from a beneficial collaboration and fertilization of ideas. The main approaches and outcomes are summarized here also in comparison to the recent literature.

Index Terms— GNSS Reflectometry, Soil Moisture, Biomass, Freeze-Thaw.

Corresponding author: Davide Comite, e-mail: davide.comite@uniroma1.it. Nazzareno Pierdicca and Davide Comite are with “Sapienza” University, Rome Adriano Camps and Hyuk Park are with Universitat Politècnica de Catalunya H. Carreno-Luengo is with University of Michigan, Ann Arbor Luca Cenci is with Serco Italia S.p.A. Maria Paola Clarizia is with Deimos UK. Fabiano Costantini is with DEIMOS Engenharia S.A. Antonio Mollfulleda is with Starlab Ltd. Laura Dente and Leila Guerriero are with University of Rome Tor Vergata. Simonetta Paloscia and Emanuele Santi are with National Research Council, IFAC institute, Florence Mehrez Zribi is with Université Toulouse III Paul Sabatier. Nicolas Floury is with ESA/ESTEC, Noordwijk, The Netherlands. This study has been conducted in the framework of the ESA contract 4000120299/17/NL/AF/hh “Potential of Spaceborne GNSS-R for Land Applications”.

I. INTRODUCTION AND STATE-OF-ART ON GNSS REFLECTOMETRY

Global Navigation Satellite System (GNSS) Reflectometry (GNSS-R) is a technique that exploits the signals of opportunity provided by navigation satellites to implement a multi-static radar system for remotely sensing different bio-geophysical parameters [1], [2], [3]. This can be achieved by means of receivers looking downward, cross-correlating the reflected signal either with a replica of the transmitted one (i.e., conventional GNSS-R) or with the direct signal itself (i.e., interferometric GNSS-R). The received signal power is delivered as a function of the time delay (sampled according to the GNSS signal bandwidth) and Doppler frequency due to platform and Earth motion (sampled according to the coherent integration time); the resulting Delay Doppler map (DDM) represents the main observable. Recent experiments have been carried out with airborne platforms, but also from satellites (e.g., UK-DMC, TechDemoSat-1, and FSSCat). A NASA mission, i.e., the Cyclone Global Navigation Satellite System (CyGNSS) [4], collecting reflections from a constellation of 8 small platforms, is currently operating to monitor tropical cyclones, and to study ocean winds.

In the last decade, the European Space Agency (ESA) has stimulated the growth of this technology funding ground-based and airborne experiments and even designing spaceborne receivers to perform altimetry of the ocean surface (i.e., PARIS IoD, Geros-ISS) [5], [6], [7]; based on such heritage a research team has also proposed an ESA Earth Explorer based on this technique (G-TERN) [8]. Very recently the HydroGNSS scout mission has also been found [9].

Recently, ESA has funded a research project that was run by a large European team with consolidated experience in GNSS-R modeling and data processing for land applications [10], [11], [6] [12], [13], [14], [15], [16], [17], [18], [19]. The project aimed at demonstrating *i*) to what extent the current knowledge from models and past ground/airborne experiments on GNSS-R applications for soil moisture and vegetation biomass retrieval is still applicable from space (with a preliminary analysis also on the monitoring of the freeze-thaw state), *ii*) which additional phenomena should be modeled and/or explained, *iii*) which final bio-geophysical products are possible to deliver and how (with recommendations for future systems). We should mention that, even if the project, and therefore this manuscript, only focuses on the retrieval of soil moisture, biomass, and freeze-thaw state, other very important land parameters can be monitored and characterized by means

of the GNSS-R reflectometry. These are floods [20], [21], [22], [23], the wetland state and dynamic [24], and land/ice altimetry [25], [16], [26]. We just note that soil moisture retrieval is quite mature and largely investigated, whereas as for biomass and freeze/thaw the project was more explorative in view of future missions. All these variables play an important role to study and understand the carbon and energy cycle of the Earth and the monitoring of the environment.

The project has stimulated very beneficial discussions and a cross-fertilization of ideas. Many papers have been already published by individual research groups taking part in the project, but the relevant tasks and the main achievements will be outlined throughout this paper. This can contribute to provide a comprehensive summary of the final responses to the addressed science questions. Besides the details that can be found in the referenced literature, this paper offers a comparative summary of the results achieved by the different teams and synthesizes the project conclusions about potential and drawbacks of GNSS-R applications over land. This is done also in comparison to the recent literature.

A review of the state of the art was carried out at the beginning of the project, followed by the collection, quality control, and detailed analysis of experimental GNSS-R data over land, with a strong focus on the spaceborne datasets provided by the TechDemoSat-1 (TDS-1) mission [27] and, although to a limited extent, by the CyGNSS mission [4]. As a by-product, the TDS-1 L1b data collected during the full mission lifetime were organized and pre-processed to create a manageable set of files (one for each year on a global scale, and one for each test site along the full mission lifetime).

The main scope was the investigation of the sensitivity of the data to the target land parameters and the effects of additional bio-geophysical parameters on the GNSS-R observations. Some data collected by the airborne GLORI sensor [12], [17] in France and the CORTO sensor [18] in Spain were also analyzed and compared to the spaceborne case to understand at what extent the platform height can affect both sensitivity and retrieval capability. Another promising application of GNSS-R over land was also investigated, that is the monitoring of freeze-thaw soil conditions in subarctic areas [28], which has attracted scientific interest from different groups [29], [30], [31], [32].

Different approaches to retrieve soil moisture (SM), above ground forest biomass (AGB), and tree height or vegetation optical depth (VOD) from TDS-1 and CyGNSS data were developed and tested [33], [34], [35], [36], [37]. Vegetation parameters were even retrieved from ground by placing the receiver under vegetation [38], [39].

Changes in TDS-1 received power were consistently associated to change in SM in [38], with a dynamic in the order of 7 dB, even though soil roughness and vegetation were recognized having an impact. Changes in CyGNSS reflected power were also found to be linearly correlated to changes of Soil Moisture Active Passive (SMAP) products in [35]. In the presence of low vegetation, the sensitivity of TDS-1 Signal-to-Noise Ratio (SNR) to SM measured by the Soil Moisture and Ocean Salinity (SMOS) satellite was found globally in the order of 38 dB/(m³/m³) in [34].

In [41] it is demonstrated that the CyGNSS constellation is able to make denser the SM product from the Soil Moisture Active Passive mission posted on a 36 km grid. The combined

near-operational SM product is noisier than SMAP but achieves a highly appreciable temporal sampling of 6 hours.

Algorithms to retrieve SM from CyGNSS data only (i.e., independently of SMAP or SMOS products) have been proposed using Artificial Neural Network (ANN) [42] [43]. They can include as input other quantities affecting the GNSS-R signal (e.g., NDVI), introduce additional observables (e.g., derived from the full DDM) and take into account the non-linearity of the relationships among inputs and the SM output. In [43] the ANN regressor was trained and tested using in-situ SM from the International Soil Moisture Network (ISMN) and sub-daily retrievals over a 9 km x 9 km cell achieved a root mean square error (RMSE) of 0.054 m³/m³. Similarly, in [42] an improvement of the retrieval performances was also found when increasing the integration time; a comparable accuracy of CyGNSS and SMAP products when both compared to ISMN data was observed as well.

A simple forward model was instead proposed in [44], leveraging on the microwave radiometry heritage. Although it is recognised the GNSS-R signal is a mixture of coherent and incoherent scattering, an equivalent reflectivity is considered as main observable. The model accounts for the influence of surface reflection, the vegetation attenuation, and volume scattering and few model parameters were tuned using a match-up of CyGNSS and SMAP data. The model was conceived as first step for future model-based inversion.

A different approach was proposed in [45], based on the assumption that on a short time scale SM can produce change in the CyGNSS bistatic normalized scattering coefficients, whereas soil roughness and vegetation do not change much. Note that in [45] only incoherent scattering was selected, contrarily to other papers where a coherent reflection from the land surface was assumed. The change detection approach is able to estimate only changes in SM, so that prior statistics from SMAP were needed to deliver absolute values. The SM maps on a 0.2° x 0.2° grid and a 1 or 3-day temporal sampling were compared to SMAP and the RMSE was found in the order of 0.03-0.04 m³/m³.

The progress about vegetation parameters and freeze-thaw from spaceborne GNSS-R sensors is less mature. The GNSS-R signature of different land cover types (including forest, ice, etc.) was analysed empirically using GNSS reflections collected by the SMAP radar receiver, taking advantage from the dual linearly polarized antenna and its high gain [46]. Specifically, the sensitivity of the soil reflection to the attenuation of vegetation in near specular geometry was previously addressed, with a theoretical approach, in [14]. This was empirically verified using reflectivity and zero-Doppler waveform trailing edge derived from the CyGNSS DDMs. As for the freeze-thaw state, the expected change in reflectivity modelled according to the SMAP F/T was actually observed in the GNSS-R scenario captured by the SMAP radar receiver [32].

In this project, three different approaches were tested for SM, i.e., a physically based algorithm applied to a single satellite passage, an empirical multilinear regression approach, and a change detection approach based on a multitemporal data stack. The physical approach was tested on airborne and satellite TDS-1 data, paying attention to understand how to collect the needed ancillary information, which revealed to be a major

problem. The multilinear regression and the change detection have been applied to data resampled on a regular grid and averaged over time (e.g., retrieval of daily means). The former was applied on a global scale as well as at local scale, the availability of ancillary data being different for the two cases. The latter can retrieve a saturation index, to be successively converted into volumetric soil moisture. Retrieval approaches based on Artificial Neural Networks (ANN) were also attempted for different target parameters (biomass, tree height, vegetation optical depth, SM), whose reference values (the training and test sets) were provided by different sources. In detail, the ANN algorithms were employed to retrieve the forest biomass and the tree height at global scale from CyGNSS data, and to provide daily estimates of SM and VOD [47].

An additional work carried out in the project framework dealt with the modelling of the reflected GNSS signal over land observed from space, merging the experiences of two research groups. The two software tools developed in the past by two different teams have been updated to improve the modelling accuracy and including specific satellite related effects. The GEROS-ISS end-to-end simulator [48] has been updated for predicting the land signal introducing a simple first-order solution for vegetation attenuation/scattering (see [49]). The SAVERS simulator [50] has been updated (see [51]) and used to understand the contribution of near specular and diffuse incoherent signal at spaceborne height, implementing the model described in [52]. Both tools account for surface topography and target inhomogeneity, whose effects on the satellite signal have been recognized and discussed. The simulators were used to derive the theoretical sensitivity of the signal to the surface parameters, to be compared with that observed on the data [51].

The paper is a summary of the project final report [53], attempting to set the work in the state of art of the GNSS-R technique. The following sections summarize the datasets used and the pre-processing tasks (Section II), the results of the sensitivity analysis (Section III and V), the retrieval approaches (section IV and VI). Section VII reports the results on sensitivity to the freeze-thaw state. The simulation tool upgrades are summarized in Section VIII, whereas Section IX draws the final conclusions from the project.

II. DATASET DESCRIPTION AND CALIBRATION

The work was carried out by exploiting the data from two spaceborne platforms, i.e., TDS-1 and CyGNSS. TDS-1 L1b products in NetCDF format were collected from the MERRBYS portal [54]. Original data are split into 6-hour segments. In order to facilitate the scientific exploitation of the data, they have been arranged in a single file over a period of time, i.e., one year for the global database, and the whole mission lifetime for specific test sites. Processed data contain the most significant set of variables for the analysis and investigation of biomass and soil moisture sensitivity. CyGNSS Level 1 data [55], version 2.0 (the one available at the time of the work), were collected from the PODAAC ftp server [56].

The main observable extracted from both products is the DDM power, which must be converted into a calibrated observable using ancillary information included within the

files. Namely, the peak Signal-to-Noise Ratio (SNR) and the reflectivity were computed. The latter has been derived assuming the signal is dominated by the coherent component of the surface scattering in the near-specular direction, so that the power received by the down-looking antenna (i.e., P_{rp}^S), starting from the well-known radar equation for deterministic targets (see, e.g., [57]) can be written as follows

$$P_{rp}^S = \Gamma_{pq}(\theta) \frac{\lambda^2 G^t G^r P_t}{(4\pi)^2 (R_r + R_t)^2} \quad (1)$$

where R_r is the distance from the receiver to the specular point (SP), R_t from the transmitter to SP, λ is the wavelength, G^t and G^r are the gain of the transmitting and receiving (i.e., down-looking) antennas. Γ_{pq} is the surface (equivalent) reflectivity, which is a function of the incidence angle θ at the SP, for transmitted q polarization (Right Hand Circular Polarization for GPS systems) and received p polarization (LHCP as for TDS-1 and CyGNSS). To retrieve the unknown transmitter Equivalent Isotropic Radiate Power, i.e., $EIRP = G^t P_t$, the amplitude of the direct signal collected by the TDS-1 uplooking antenna was exploited as described in [58]. As for CyGNSS the EIRP was retrieved from the L1 product itself. Both approaches have serious drawbacks: from one side the uplooking antenna pattern is not accurately known, whereas the nominal values of the EIRP can be inaccurate. Additionally, the power of the noise must be estimated from the DDM using the first delay lines preceding the peak, which is then subtracted from the received power to retrieve the signal power.

The equivalent reflectivity embeds the effects of the surface moisture content, of small-scale roughness, and of the attenuation introduced by the vegetation cover. Such observable is denoted as *equivalent reflectivity* as it also includes the contribution of the incoherent component of the scattered field introduced by vegetation and soil roughness at different scale. In this respect it should be mentioned that, during the development of the project, different research groups have deeply investigated the phenomenology of GNSS-R land scattering, considering both theoretical and experimental approaches (see [16], [59], [60], [26] and refs. therein). In this frame, the need of modelling the presence of an intermediate scale of roughness and accounting for the incoherent nature of the scattering for most of the observed land surfaces (excluding water bodies, iced surfaces, and almost planar surfaces characterized by large values of the correlation length) have been discussed. The relative weight of coherent and incoherent signal in the GNSS-R data is probably still a main research question, as well as the way one can distinguish among the two.

In the analysis presented in the sequel, a quality-filtering of the TDS-1 data was applied to remove cases with spacecraft *in eclipse* or with the direct signal potentially entering into the DDM. In most cases small incidence angles (e.g., less than 45°) were only considered, as signals at larger angles are collected far from the boresight of the down-looking antenna, which can introduce calibration problems due to poor knowledge of the attitude. Data collected over complex topography were also removed from the analysis, as well as CyGNSS data with poor quality flags and over continental surfaces with altitude greater than 500 m, since the small receiving windows was initially set

Fig. 1. Screened and compensated TDS-1 GNSS-R observables versus SMOS soil moisture data. The color scale represents VOD. Pictures from [19].

Fig. 2. Calibrated TDS-1 GNSS-R reflectivity (dB) at LRCP polarization versus SMOS soil moisture data for different ranges of incidence angle: a) from 0° to 30°, b) from 30° to 60°, and c) from 60° to 90°. Pictures from [19].

to collect data from the ocean and, likely, it cannot accommodate data coming from high mountains. It should be mentioned that, after December 2017, reflections coming from altitudes greater than 500 m can be successfully collected by CyGNSS.

The research on the retrieval of soil and forest parameters needs reference global information, such as soil moisture, biomass, and tree height or vegetation optical depth (VOD) for carrying out correlation analysis and validating the relevant retrieval algorithms.

They were obtained from microwave radiometer products, i.e., the SMAP L3 daily products, version 5, projected onto the Equal-Area Scalable Earth (EASE) Grid, and the SMOS Level 3 product. It must be pointed out that VOD is not a vegetation parameter that can be measured on the ground, but it is rather an electromagnetic parameter that is correlated with the vegetation biomass and height [30]. MODIS/Terra Normalized Difference Vegetation Indices (NDVIs) generated every 16 days were also collected. As for forest, the ICE-GLAS LiDAR acquisitions processed as in [61] were considered to provide tree height maps (available from <http://lidarradar.jpl.nasa.gov/>), as well as the improved pan-tropical Above Ground Biomass (AGB) [62], limited to $\pm 40^\circ$ of latitude (available from www.wageningenur.nl/grsbiomass).

The time interval used for collocating different products were rather short for the estimates of soil moisture (2-3 hours), but were more relaxed for biomass estimates, as the reference data can be considered mainly ‘static’ maps that do not provide any evolution in time.

The sensitivity analysis and the retrieval were carried out both on a global scale and on a local scale (i.e., over specific test

areas). The latter were selected with different criteria, with the aim of covering different soil and forest conditions and getting a suitable amount of ancillary data. Specifically, for soil moisture the following were considered: Florida, Texas, SMOSMANIA (France), Merguellil (Tunisia), REMEDHUS (Spain), and CEMADEN (Brasil). As for biomass, the selected areas were Alaska, Florida, Manaus, Argentina, Zambia, and Finland. Additional areas to test the effect of topography are Chad and Alps.

The study related to the GNSS-R potentiality for Freeze/Thaw (FT) monitoring was carried out in the Northern Hemisphere. An analysis aimed at comparing SMAP FT and GNSS-R spatial-temporal dynamics was carried out in Siberia. Comparisons between GNSS-R data and in situ temperature records were performed by taking advantage of stations located in Canada, Finland, Siberia, and Alaska.

III. SENSITIVITY TO SOIL MOISTURE

A. Analysis of TechDemoSat-1 Data

The sensitivity of TDS-1 observables to surface soil moisture was investigated using the 2014-2017 global dataset. The sensitivity of different GNSS-R observables to surface SM and its dependence on the incidence angle was analyzed. A global scale statistical analysis using SMOS L3 products (SMOS nominal resolution, re-gridded at 25 km) was first carried out. Then, an investigation at regional scale using SMOS L4 products (1 km resolution) as well as in situ sensors was performed. The potential dependence on subsurface soil moisture was also analyzed in the Brazilian *semi-arid* region

(a)

(b)

(c)

(d)

Fig. 3. GNSS-R observables at 0°-20° incident angles as a function of soil moisture: (a) Γ_{RL} for LAI<1; (b) Γ_{RL} for LAI>1; (c) SNR for LAI<1; (d) SNR for LAI>1. Data are relevant to the GLORI campaign, more information can be found in [17].

using Lisflood [63] and Musa models (<http://musa.cptec.inpe.br>).

The TDS-1 reflectivity was first corrected to compensate for the vegetation effects using the SMOS derived VOD. A simple model is assumed considering the vegetation 2-way attenuation and the small-scale surface roughness HR parameter used in the SMAP retrieval algorithm, as given in the following

$$\Gamma(\theta_i, SM, VOD) = \Gamma(\theta_i, SM) \cdot e^{-HR} \cdot e^{-2 \cdot VOD / \cos(\theta_i)} \quad (2)$$

It must be pointed out that the mixed pixel effects were not accounted for and that the resolution of SMOS products (35 to 50 km) is significantly different from that of GNSS-R products, as the latter can be approximately determined by the size of the first Fresnel zone in case of coherent scattering [52], [66], [67] [68], [59], or about 25 km as a maximum for incoherent scattering. The model derives from the application of a simple τ - ω approach to the reflectivity measurements. The low performances of the results shown in Fig. 1 and 2 may be attributed to the different resolution of the measurements that was not considered (about 1 to 10 km for TDS) when incorporating the SMOS and SMAP data (i.e., VOD and HR) into (2).

Figure 1 shows the scatter plots of SNR, DDM peak and reflectivity (compensated for vegetation and the distance factor and limited to incidence angles up to 30°) versus the collocated SMOS L3 SM product. The color scale shows the VOD in Np. Note that the pixels with the highest VOD are well above the fitting line, which suggests that the vegetation optical depth effects must be considered, but that the correction in (2) is overcompensating these effects.

As it can be appreciated, the SNR exhibits the largest uncertainty (standard deviation $\sigma = 7.1$ dB), but also the largest sensitivity to soil moisture, i.e., 22.75 dB/(m³/m³). The peak of the DDM exhibits a very weak sensitivity to SM, as the signal is masked by the speckle noise. Reflectivity scatter plot exhibits a sensitivity to SM of 9.11 dB/(m³/m³) and a much smaller uncertainty of $\sigma = 3.17$ dB. From now on, only the reflectivity will be analyzed [19].

Figure 2 shows the scatter plots of the (calibrated) reflectivity for incidence angles a) from 0° to 30°, b) from 30° to 60°, and c) from 60° to 90°, versus the collocated SMOS SM. It can be appreciated that as the incidence angle increases the sensitivity to SM decreases: 8.7 dB/(m³/m³) from 0° to 30°, 5.7 dB/(m³/m³) from 30° to 60°, and 2.8 dB/(m³/m³) from 60° to 90°, while the pixels more affected by dense vegetation (large VOD) depart more from the linear fit.

While the obtained sensitivities are lower than those obtained in previous studies mentioned in the introduction (see [34], [38]), they are still significant. Note that any speculation about the presence of speckle noise sends back to the question about relative weight of coherent and incoherent scattering, which is object of recent literature as discussed before [16], [45].

A similar analysis was also performed over 3 different regions where 1 km resolution L4 downsampled SMOS surface SM was produced and in situ data were available. L4 SM maps were obtained from the L3 SM maps by applying a downscaling algorithm to disaggregate the original SM pixels to 1 km resolution [69], [70].

The considered regions were the CEMADEN area located in a Brazilian semiarid region, the REMEDHUS site in Spain and the OzNet site in Yanco, Australia. These regions belong to soil moisture networks. For the Brazilian site hydrological models were run to estimate the 50 cm and 100 cm soil moisture.

The TDS-1 reflectivity was compared with SMOS L3 and L4 products, as well as in situ data from the ground network. In principle, collocated data should be available for inter-comparison. In practice, TDS-1 ground tracks are so far away

Fig. 4 GNSS-R observables at 20°-40° incident angles as a function of LAI at dry conditions ($SM < 0.1 \text{ m}^3/\text{m}^3$): (a) Γ_{RL} ; (b) SNR. Pictures from [17].

Fig. 5. Comparison between retrieved reflectivity and ground measurements a) considering the test set and b) the validation set. Pictures from [17]. The RMS for the retrieved soil moisture is equal to $0.06 \text{ m}^3/\text{m}^3$.

from the network stations that few matchups were available, and only when the distance threshold is increased up to 30 km results become statistically significant. Unfortunately, this distance is similar to the SMOS L3 resolution, so that no conclusive results can be derived about the comparison at higher resolution.

The sensitivities obtained using the SMOS L3 SM values can be considered quite high: $18.64 \text{ dB}/100(\text{m}^3/\text{m}^3)$ in Yanco/NSW/Australia, $9.37 \text{ dB}/(\text{m}^3/\text{m}^3)$ in Cemadem/Brazil, and $12.15 \text{ dB}/(\text{m}^3/\text{m}^3)$ over the Iberian Peninsula. However, the sensitivity derived when comparing to the SMOS L4 SM values decreased notably to $11.18 \text{ dB}/(\text{m}^3/\text{m}^3)$ in Yanco/NSW/Australia, $6.62 \text{ dB}/(\text{m}^3/\text{m}^3)$ in Cemadem/Brazil, and $-1.1 \text{ dB}/(\text{m}^3/\text{m}^3)$ in the Iberian Peninsula (probably less significant because of the limited amount of data and limited range of SM values). As the topography effects and/or vegetation effects increase, this sensitivity decrease, despite pixels affected by topography were flagged and discarded, and vegetation effects were, in principle, compensated for. In any case, all these sensitivities are smaller than those obtained in [34] and [38], which are about $38 \text{ dB}/(\text{m}^3/\text{m}^3)$. The non-linearity of reflectivity versus SM values mainly explains this discrepancy. Likely, certain experiments show higher sensitivity since they explore low values of SM with respect to the present analysis that regarded almost the full range of SM values. An investigation about this issue was done in the radar context in [71].

When trying to correlate the TDS-1 GNSS-R reflectivity with in-situ soil moisture values, very few matchups were found. It was difficult to perform a robust fit over the Remedhus (Spain)

and Yanco (NSW, Australia) sites. Only over Brazil, setting a radius of 30 km, satisfactorily matchups have been found to obtain representative results. Sensitivities are equal to $7.39 \text{ dB}/100\%$, $1.36 \text{ dB}/100\%$, and $-9.10 \text{ dB}/100\%$ for incidence angles from 0° to 30° , from 30° to 60° , and from 60° to 90° , respectively. For incidence angles from 0° to 30° , the value obtained is between $6.62 \text{ dB}/100\%$ and $9.37 \text{ dB}/100\%$ evaluated with respect to L4 and L3 SMOS SM data, respectively.

Thanks to the availability of the outputs of hydrological models (Lisflood and MUSA) in the Brazilian semiarid site, a comparison of reflectivity with soil moisture in the root zone was attempted [19]. Results were not conclusive, also because of the small number of matchups. However, a sensitivity of the reflectivity to the SM at 50 cm depth was observed using the Lisflood model (at 10 km resolution), whereas no apparent sensitivity to the 1 m depth SM from the MUSA model was observed, the latter running at worse resolution (i.e., 25 km).

The problems encountered when analyzing the sensitivity at high resolution sent back to another research question, which is the spatial resolution of the GNSS-R observations [72], which is related again to the issue of coherence of the collected signal [16], [45]. Moreover, it must be pointed out that the observations are not repeated systematically over a pre-defined spatial grid and thus the match-up with in situ data can be problematic.

Fig. 6. Dependence of sensitivity on incidence angle, when the RR flag for SMAP data is applied.

B. Supporting Dataset: The Airborne GLORI Campaign

Data from the GLORI polarimetric receiver [12], [17] were used to understand at what extent the satellite height can affect the GNSS-R performances. Two classes of crops are considered according to their leaf area index (LAI) in the sensitivity analysis of GNSS-R observables to soil moisture. The objective of this choice is to limit the influence of the heterogeneity of vegetation cover densities between agricultural reference fields. The first class is defined by $LAI < 1$, corresponding to bare or poorly vegetated soils. The second class is defined for $LAI > 1$, corresponding to medium and high vegetation densities. Figure 3 illustrates Γ_{RL} and the reflected SNR as a function of soil moisture, for the two LAI classes within the 0° - 20° interval of incident angle. For each plotted point, the GNSS-R observables are averaged over an agricultural field at a given date. It can be seen that increasing LAI generally reduces the sensitivity of GNSS-R observables to soil moisture.

The Γ_{RL} sensitivity to soil moisture decreases from $45.7 \text{ dB}/[\text{m}^3/\text{m}^3]$ for the weak LAI values ($LAI < 1$) to $28.38 \text{ dB}/[\text{m}^3/\text{m}^3]$ for the highest LAI values ($LAI > 1$). This result clearly illustrates the nuisance effect of the vegetation on GNSS-R observables. For the case of the Polarimetric Ratio (PR), defined as Γ_{RL}/Γ_{RR} , a low correlation with soil moisture was observed ($R^2 < 0.2$, even for low LAI values). For the case of low LAI class, a sensitivity slightly higher of both reflectivity and SNR for low incident angles was observed.

The GNSS-R observables were studied also as a function of the LAI of the plant cover. As in the case of soil moisture, two incident angle intervals and three observables (Γ_{RL} , LHCP SNR, and PR) were considered. Effect of soil moisture is

reduced by considering data acquired in dry conditions, with soil moisture lower than $0.1 \text{ m}^3/\text{m}^3$. There is a clear decrease in the GNSS-R observables with increasing vegetation LAI, due to the signal scattering and absorption (both increasing the optical thickness), as shown in Fig. 4 [17]. The observed higher sensitivity to LAI at high incident angles (equal to $-0.91 \text{ dB}/[\text{m}^2/\text{m}^2]$) can probably be attributed to a decrease in the influence of the soil component (roughness and moisture) due to an increment of the vegetation optical depth.

A similar behaviour is observed for the signal SNR. The PR observable was found to be correlated with vegetation LAI, with a high sensitivity to vegetation LAI equal to $-1.1 \text{ dB}/[\text{m}^2/\text{m}^2]$ for high angles and $-1.18 \text{ dB}/[\text{m}^2/\text{m}^2]$ for low incident angles. This better performance of PR in comparison to its sensitivity to soil moisture could be explained by the highest effect of vegetation on the depolarization of the GNSS signal.

Based on the model in (2), assuming approximated linear dependence of the Fresnel reflectivity from SM and of VOD from LAI, the equivalent reflectivity of a vegetated and rough soil in dB units can be written as follows

$$\Gamma_{LR}(\theta)_{\text{dB}} = \alpha \cdot \text{SM} + \frac{\beta \cdot \text{LAI}}{\cos(\theta)} + \delta \quad (3)$$

where α is the sensitivity of Fresnel reflectivity to soil moisture, β the sensitivity of canopy opacity to the vegetation LAI, and δ a constant related to the roughness effect. α , β and δ are empirical parameters to be retrieved from the experimental data. The retrieved equation for the received left polarization is given in the following, where a linear relationship between VOD and LAI is also applied:

$$\Gamma_{LR}(\theta)_{dB} = 40.73 \cdot SM - \frac{7.01 \cdot VOD}{\cos(\theta)} - 19.04 \quad (4)$$

Figure 5 presents a comparison between measured and simulated reflectivity over the training set (to retrieve the coefficients) and an independent validation set. As for the test set the determination coefficient R^2 is 0.69, with a RMSE equal to 2.9 dB. Corn agricultural fields with the highest vegetation height are illustrated by the points showing highest discrepancy and a saturation behavior for low values of reflectivity. The choice of LAI as a proxy of optical thickness instead of other properties such as the vegetation water content could induce certain limitations.

Moreover, the sensitivity of the Fresnel coefficient to SM could be parametrized to the incidence angle, especially in the higher range of angles. Nonetheless the simple model exhibits fairly good capability to reproduce the data and can be adopted within a physically based retrieval approach. Of course, its validity for spaceborne data has to be verified.

C. Sensitivity of CyGNSS Data

As done for TDS-1, the sensitivity of CyGNSS data to SM was assessed with respect to SMAP SM. Note that reasonable results were obtained only retaining SM data with the SMAP flag “retrieval recommended” (RR) set on. The sensitivity and its dependence on incidence angle are shown in Fig. 6. For small angles the sensitivity appears relevant, even without compensating the effect of vegetation and roughness, and the data behaviour appears similar to that of TDS-1 data. Finally, the dependence of the CyGNSS reflectivity on vegetation has been analysed in more details using the Vegetation Water Content (VWC) parameter, derived from NDVI climatology and included in SMAP data (not shown here for sake of conciseness). To provide an overall estimate of sensitivity to SM and VOD a multivariate regression analysis was carried out, as shown in Table 1. The results show a good sensitivity to soil moisture and VOD (the latter being negative, as expected). The sensitivity to SM is also quite independent of the incidence angle, as the multivariate regression probably better compensate empirically for VOD effect with respect to the physical model in (2). The sensitivity to VOD is higher at larger angles, confirming previous outcomes.

IV. SOIL MOISTURE RETRIEVAL APPROACHES

A. Single-Pass Retrieval

The feasibility to perform single-pass SM retrievals using GNSS-R observations and a physically based approach was investigated [64], [73]. The aim was exploiting data from a single receiver overpass, in contrast with next sections where the retrieval of space and temporal means is carried out based on empirical approaches. A single-pass approach does not need to resample and collocate observations over time, it thus enables better temporal and spatial resolution. Another important advantage is the possibility of considering accurate forward models, describing the non-linear relationship between

reflectivity and SM, which exhibits a saturation effect for wet soils (see previous discussion about the dependence of sensitivity on the SM dynamic range). The drawbacks are the need of an accurate absolute calibration and the collection of ancillary data to correct roughness and vegetation effects on each data sample.

The proposed physical SM retrieval algorithm exploits the model in (2) and inverts it to retrieve the Fresnel reflectivity using independent ancillary information on VOD and roughness. The Fresnel reflection formula is used to derive the soil permittivity and finally a permittivity model is exploited to retrieve the soil moisture (among other variables, such as the clay fraction and physical temperature) through a minimization process.

The approach was first attempted on data acquired during an airborne experiment that took place on October the 22nd, 2018, in an agricultural region around Balaguer, Catalunya. The plane was a CESSNA Caravan, flying at 1200 m of height. The AISA instrument (a pushbroom hyperspectral sensor collecting 126 bands in the VNIR) flew together with the ARIEL L-band radiometer and the CORTO (COmpact Reflectometer for Terrain Observations) reflectometer at L1/L2 GPS bands [18].

The VOD used to compensate for the vegetation effects was derived following the SMAP approach [74] applied to the high resolution NDVI available from AISA. A field campaign was carried out to collect data on surface roughness by a laser profiler and in situ soil moisture measurements performed the same day as the airborne campaign. Ground samples were collected from 5 different areas corresponding to different agricultural fields. Surface roughness measurements revealed to be quite critical, as usual, and the sampling was not dense enough. The ARIEL L-band radiometer [75] was used to provide a complete SM map with a final resolution of 0.8 m. The retrieved SM maps have then been validated using the in-situ soil moisture samples.

Due to the limited estimation of the soil surface roughness from in situ data, results show a disparity between SM retrieved by the Ariel radiometer and the CORTO GNSS-R instruments. For a single track of reflections over a relatively flat area, the retrieved SM values are highly variable with the incidence angle and are quite different with respect to the SM derived from the L-band radiometer. These results testify that the surface roughness correction was not appropriate, either in the value of the h parameter, and/or the power of the cosine

REGRESSION COEFFICIENTS for CYGNSS	SM	VEGETATION OPACITY	ROUGHNESS
All θ	26.00	-16.02	-15.22
$0^\circ \leq \theta < 30^\circ$	27.09	-13.30	-16.41
$30^\circ \leq \theta < 60^\circ$	25.51	-16.50	-13.50
$\theta \geq 60^\circ$	25.66	-21.77	-13.45

Table 1. Regression coefficients as a function of incidence angle ranges computed using the dataset when the RR flag for SMAP data is applied.

function appearing in (2). Then, the surface roughness correction term was tuned to match as close as possible the CORTO SM retrieval and the SM from ARIEL data. The best value for the power of the cosine function was found to be $n = 0$ ($n = 2$ is the theoretical value).

The *ad hoc* roughness parameter revealed to be quite spread, notably more for the highest values. There is no evident correlation neither with the different fields, nor with the soil moisture values to explain the variability of the *ad hoc* roughness. Of course, the anomalous values of the *ad hoc* roughness can be related to a wrong compensation of the vegetation effect based on NDVI and/or to the estimation of the noise in the DDM needed to compute the reflectivity. This led to the conclusion that soil surface roughness is a key parameter to correctly estimate the SM, but in situ measurements of surface roughness are not suitable to predict the value to be used; the use of a constant value for a large region is not suitable either. The approach of forcing a tunable roughness correction per pixel is not feasible in an operational system. An alternative approach can consist in deriving empirically the best roughness parameter as a function of the incidence angle from a suitable training set. The “ad hoc” roughness derived in this way provided reasonable results and could be further exploited in the future.

The approach tested on the Balaguer data has been also applied to TDS-1 reflectivity collected over the Remedhus experimental site where in-situ SM measurements and other data are routinely collected. Similar conclusions can be outlined through the Balaguer experiment. An *ad hoc* roughness parameter is needed to force a correct soil moisture retrieval. It can be adjusted locally or regionally, but it does not seem feasible (or at least it is very difficult, in general, and not known at present) from an operational viewpoint. For this reason, it was concluded that, at least at this stage, retrievals of spatially or temporally averaged values, possibly exploiting a temporal sequence of GNSS-R data can be more effective.

However, recent results using airborne data acquired by the MIR (Microwave Interferometric Radiometer) over Yanco, New South Wales, Australia [76], have shown that the origin of the fluctuations of the reflectivity, mainly linked to thermal noise, speckle, and surface roughness, can be used to correct surface roughness effects. This is a new promising result that can be applied to single-pass retrievals, also from space, as in [77].

B. Retrieval by Change Detection

An alternative inversion algorithm was proposed to retrieve surface soil moisture from CyGNSS data using a change detection approach. It was tested on the Merguellil site (Tunisia), the Dallo Basso site (Niger) and the Ouémé site (Benin) around respective ground moisture stations. As for ancillary data, 10-day NDVI products were collected and atmospherically corrected, derived from Proba-V data at spatial resolution of 1 km. Soil moisture data (i.e., relative saturation index, ranging between 0% and 100%) retrieved from the backscattering coefficient measured by the ASCAT radar carried aboard the METOP satellite [78] were also included. CyGNSS data were filtered according to SNR > 3 dB and incidence angles lower than 35°. Only data with NDVI between

site	RMSE (%.vol)	R ²
Merguellil	6.7	0.36
Dallo Basso	1.8	0.68
Ouémé	5.1	0.7

Table 2. Statistical parameters of the comparison between satellite products and ground measurements

0.2 and 0.8 were considered to avoid both water bodies and dense forests; data over surfaces with altitude greater than 600 m were also discarded. After selection of CyGNSS data, an empirical normalization of the reflectivity as a function of the incidence angle was applied considering data aggregated on a $0.1 \times 0.1^\circ$ grid. Finally, data were aggregated on a $0.5^\circ \times 0.5^\circ$ grid. The large dimension of this grid (e.g., with respect to the $0.25^\circ \times 0.25^\circ$ ASCAT grid) is aimed at getting enough data within each pixel as specular reflections generally come from different elements of the surface and lead to high variability in time in case of inhomogeneous surfaces. A minimum number of 5 GNSS-R measurements in the same pixel were considered to derive the mean daily value.

A problem that was apparent looking at the data in the test area, characterized by an arid climate, is the high variation of GNSS-R reflectivity in dry conditions, with a standard deviation of about 3 dB, without any expected local effect due to soil moisture. This could be due to a larger uncertainty in the retrieval of reflectivity for low SNR values, but it can be also linked to the heterogeneity of the surface both vertically (considering the high penetration depth) and horizontally, as explained before.

The change detection algorithm was applied to the data with grid resolution equal to $0.5^\circ \times 0.5^\circ$ collected along a period of 21 months. In a context of a database spanning a long-time interval, the highest SM (i.e., larger I) likely corresponds to soil saturation and the lowest SM (i.e., smaller I) to the driest possible condition. An index between 0% and 100% is then estimated according to the formula below, referred to as “saturation degree”, similarly to what is done for the ASCAT moisture products [78]:

$$Ind = \frac{I - I_{min}}{I_{max} - I_{min}} \times 100 \quad (5)$$

Since vegetation could influence the dynamic of the reflectivity, the change detection algorithm was applied within two vegetation classes, i.e., NDVI < 0.4 and NDVI > 0.4. The number of classes could increase with the increasing of the length of the time series.

In order to compare CyGNSS saturation degree with ground measurements, CyGNSS products were converted to physical units of $m^3 m^{-3}$ by normalizing them to the mean and standard deviation of the theta probe ground data in each station.

Fig. 7 provides a comparison between Merguellil ground measurements at 5 cm depth and GNSS-R products. During dry season, as already observed, CyGNSS retrievals exhibit high variability in spite of the absence of temporal and spatial

Fig. 7. Comparison between soil moisture products from CyGNSS data and ground measurements in the Merguellil site with the in situ probes.

variation of SM. The quality of the statistical outcome of our comparison between ground-truth measurements and satellite products is moderate. Table 2 summarizes the statistical parameters, i.e., RMS errors and correlation coefficients. When dry period is not considered in the proposed comparison, better results with highest accuracy in soil moisture estimation were observed.

A comparison between ASCAT and CyGNSS products estimated in the period between March 2017 and end of December 2018 was also performed. A moderate agreement between the two saturation degree products were observed (correlation of 0.62), although it must be considered the limited number of matchups and the fact that the ASCAT change detection algorithm is based on more than 20 years of radar data.

In conclusion, the use of CyGNSS data within a change detection algorithm has shown a reasonable potential for monitoring soil moisture content. The GNSS-R technique is still very young, and decades of experience acquired in the monostatic radar and passive microwaves make a great difference. Nonetheless, the accuracy was not far from that achieved by scatterometers or passive microwave radiometers. However, there are still many aspects to clarify in order to improve the accuracy of the estimates, such as a better correction of topographic effects and vegetation cover, a better understanding of the limitations of low reflectivity values over dry conditions, the need to increase the density of acquisitions as the specular points do not pertain to the same surface from one day to the other. The latter factor generates a variation as a function of time over the same resolution cell of the grid that is an issue to further consider in the future.

C. Retrieval by Multivariate Regression

Two approaches have also been tested to estimate the soil moisture (SM) using CyGNSS data based on an empirical multivariate regression. The results of the proposed algorithms were investigated both on a global scale, and specifically over three study areas: Florida, Texas and New South Wales [79].

Fig. 8. Density scatter plot in logscale of true (SMAP) and retrieved (CYGNSS) soil moisture using R-V-R algorithm on a pixel base (from [79]).

Besides 5 months of CyGNSS acquisitions, spanning from April 2017 to August 2017 (Level 1 products, version 2.0), the investigation considered as ancillary data the SMAP Level 3 products to gather reference soil moisture, as well as information about vegetation opacity (VOD) and roughness coefficient.

It is worth noting that the roughness coefficient is a parameter essentially derived from information about land classification, and as such is not much representative of the small-scale roughness. The soil moisture extracted by the SMOS Level 2 product was also used, version 6.50, and limited to the Florida, Texas and New South Wales areas. The in-situ daily SM measurements were analysed over Florida and Texas, and were taken from the Soil Climate Analysis Network (SCAN) climate monitoring stations,

The algorithm is based on a multivariate linear regression that estimate the soil moisture as:

$$SM = a \cdot \Gamma'_{dB} + b \cdot VOD' + c \cdot H' + d \quad (6)$$

With respect to (2) the VOD, the measured reflectivity, and the roughness parameters were standardized (for this reason are indicated with an apex in eq. 6) imposing the dynamic range of the variables to be [0 1], and the dependence on the incidence angle was not considered. Standardization aims at comparing directly the weights that the retrieval algorithm gives to each variable. The regression coefficients were estimated from a combined training set of CyGNSS reflectivities and SMAP SM and then tested on an independent set. The test set was extracted randomly from 2.5 months of data, while the algorithm performances were evaluated from the remaining 2.5 months of data. The data were quality controlled to check that the CyGNSS reflectivity were positive, VOD and roughness coefficients had valid numbers and the acquisition altitudes was lower than 500 m. The reflectivity was then gridded for each day, and over the SMAP EASE-grid at 36 km x 36 km resolution.

The so-called Relevance Vector Regression (R-V-R) retrieval algorithm determines a unique set of regression coefficients on the global database of GYGNSS and SMAP data implementing a trilinear regression to estimate soil moisture. The consideration of the incidence angle in the regression model was proved not to be effective in terms of retrieval performance and was then not included. The algorithm applied to global data tends to give similar weights to both the reflectivity and the vegetation opacity. Moreover, it tends to underestimate high SM and overestimate low SM. This is a typical behaviour of linear regression approaches that do not account for non-linear effects and are biased by an inhomogeneous distribution of the value of the target parameter in the training set. For this reason, a further bias correction was applied to the retrieval using a Look-Up-Table (LUT) as detailed in [79].

Figure 10 shows a density scatter plot in log-scale of the SMAP reference SM and CyGNSS SM. The density plot highlights overall good agreement between CyGNSS and SMAP, even though there is a large amount of scatter in the data. The RMS error calculated over the test set is $0.08 \text{ cm}^3/\text{cm}^3$ with a negligible bias. Both the bias and the RMS difference increase for increasing soil moisture.

The R-V-R algorithm can also be applied on a regional scale and the three case studies of Florida, Texas and New South Wales were considered. The coefficients, as well as the correction LUT, were derived from the training data pertaining to each specific region. In this case the coefficients give more weight to the CyGNSS reflectivity in some cases, and less weight in some others. The test results were in line with the global case, exhibiting comparable results for Florida (RMS error $0.08 \text{ cm}^3/\text{cm}^3$) and much better results in Texas (RMS error $0.06 \text{ cm}^3/\text{cm}^3$) and New South Wales (RMS error $0.06 \text{ cm}^3/\text{cm}^3$). It must be considered that Florida was found a quite problematic area for soil moisture retrieval even for the SMAP mission, because of the large number of lakes and swamps (i.e., water bodies).

The retrievals from CyGNSS were also compared with L2 SMOS data for Florida, Texas and New South Wales, also gridded daily over the EASE-Grid, at a resolution of $36 \text{ km} \times 36 \text{ km}$, to facilitate the comparison. The results (not shown here, more details can be found in [79]) were slightly worse than the tests using SMAP, but this was expected being the regression trained on SMAP data, so that, overall, the SMOS comparison showed quite a good consistency with the previous one.

The second approach for retrieving SM from CyGNSS consisted in estimating the regression fit between the CyGNSS reflectivity and the SMAP soil moisture for each pixel of the considered grid. In this case, a simple linear regression only using the CyGNSS reflectivity was performed, as vegetation opacity and roughness coefficient gathered from the SMAP products do not exhibit a temporal dynamic in a single pixel but are almost “static” parameters. This is quite understandable for roughness, but the same situation was also observed for VOD as in the considered SMAP product VOD was an auxiliary data, not retrieved from the radiometer observations. This does not happen on a global scale as the spatial variability of those parameters is meaningful. In the pixel-by-pixel approach the difference in the surface conditions, other than SM, are implicitly accounted for by the different regression coefficients. Here, the pixel is chosen to be $1^\circ \times 1^\circ$ of lat/lon, since this was

Fig. 9. a) TDS-1 and CyGNSS reflectivity versus AGB from pantropical map for the Manaus, Argentina and Uruguay test areas, b) ALOS backscatter and TDS-1 reflectivity as a function of AGB for biomass values higher than 150 t/ha.

a good compromise between accuracy of the retrievals and the need to have a large enough number of samples in each pixel, to form the two separate subsets of training data and test data, as for the R-V-R algorithm. The coefficient of the linear regression for each pixel was derived from a training set, e.g. a random half of the data falling into that pixel, and the algorithm performance was estimated using the test data, e.g. the other half. In principle, this algorithm can be applied considering even smaller pixels, if more data will be available, and the accuracy is expected to improve. This methodology is mathematically equivalent to the approach presented in [35]. A difference between the two approaches is the use in our case of the reflectivity as observed quantity instead of the SNR.

The test of the retrieval on a global scale assuming as ground truth the SMAP SM is presented in Fig. 8. The density plot highlights a good agreement between CyGNSS and SMAP, and the agreement is slightly improved compared to the R-V-R results, exhibiting on a global scale an RMS error of $0.06 \text{ cm}^3/\text{cm}^3$, which is close to typical RMS differences also obtained by other satellites. On a local scale the performance in

Florida was worst (RMS error $0.09 \text{ cm}^3/\text{cm}^3$), and slightly better in Texas (RMS error $0.05 \text{ cm}^3/\text{cm}^3$). The comparison with SMOS confirmed the previous considerations.

Finally, the results from CyGNSS were compared with the SM measured by in-situ stations of SCAN, over Florida and Texas, and in the Merguellil catchment in Central Tunisia. The estimates provided from SMAP were also considered for comparison. Both retrievals were mean daily quantities that were extracted in the pixels closest to the in-situ probe location. Unfortunately, this analysis did not provide reliable conclusions. In some cases, the number of matchups were quite small, or the dynamic range of observed SM was very small; compared to SMAP, CyGNSS exhibited retrievals sometime better and sometime worse. In general, the performances were not good and SMAP outperformed CyGNSS in case of higher SM dynamic range.

V. SENSITIVITY TO VEGETATION BIOMASS

The sensitivity of TDS-1 to the forest parameters related to biomass was evaluated on five test areas, chosen as representative of the most important forest types on the Earth: Brazil (Manaus), Uruguay (Algora), Alaska (Fairbanks), Finland, Argentina (Asuncion). ALOS radar images have been also considered for comparison and the sites were chosen with an extension of approximately $350 \text{ km} \times 350 \text{ km}$, corresponding to the size of ALOS Scansar images, except the Uruguay one having an extension of $70 \text{ km} \times 70 \text{ km}$. In addition to ALOS backscatter images, additional data providing forest characteristics were selected and specifically the VOD available from the SMAP L3 products, the improved pan-tropical biomass map providing the AGB as illustrated in [62] and the tree height derived from the ICE-GLAS LiDAR acquisitions at 1 km resolution on a global scale as described in [61]. It is pointed out here as AGB and tree height were “static” data, related to a specific epoch, whereas the VOD has some temporal dynamic.

The TDS-1 and CyGNSS sensitivities to AGB, as well as ALOS backscatter, were first evaluated by comparing the reflectivity to the improved pan-tropical AGB map. The comparison on a local scale was carried out on the common dataset, i.e., the month of April plus the period from July to November 2017, for the Argentina, Manaus and Uruguay test areas. Since the AGB map is limited to $\pm 40^\circ$ of latitude the boreal forests were excluded in this analysis. AGB and ALOS backscatter were resampled on a fixed grid at $5 \text{ km} \times 5 \text{ km}$, by averaging all the values in the same grid cell. The result shown in Fig. 9 can be considered encouraging and confirm that the main mechanism making GNSS-R data sensible to the biomass is the attenuation of the near specular reflected signal from the soil due to the vegetation (more discussions and results can be found in [36]).

Although there is a bias between the two reflectivity values (to be further investigated), it should be noted that both sensors show almost the same sensitivity to AGB ($0.047 \text{ dB}(\text{t/ha})^{-1}$ for CyGNSS and $0.045 \text{ dB}(\text{t/ha})^{-1}$ for TDS-1). The same happens for the correlation coefficient that is $R \approx 0.4$ in both cases. It is also noticeable as the scatterplot of the HV normalized radar cross section of ALOS as a function of AGB in the range $150 -$

a)

b)

Fig. 10. Reflectivity as a function of tree height estimated by the ICE-GLAS mission. a) TDS-1 over the test areas, b) Density plot of CyGNSS on a global scale.

400 t/ha confirms the saturation of the L-band backscatter signal above 150 t/ha biomass observed in many papers, whilst Γ is decreasing almost linearly down to the maximum AGB available in the dataset.

As far as tree height and VOD, in Fig. 10 the reflectivity as a function of the tree height is reported, with TDS-1 data over the test areas and CyGNSS on a global scale. The expected linear decrease of the reflectivity when the height of trees, and arguably the biomass, increases is confirmed, with $R \approx -0.4$ and a sensitivity of about -0.66 dB/m as for the test areas. Although with higher dispersion, the result is confirmed on a global scale using CyGNSS; in this case $R \approx -0.36$ and the sensitivity is -0.23 dB/m . The presence of many different species in the analysis on a global scale may partially contribute to increase the dispersion. The comparison with VOD confirmed this behaviour (i.e., the negative correlation) with sometimes even better results.

Although the three parameters are not exactly providing the vegetation biomass, they are partially correlated, so that the work provided an experimental confirmation of the biomass retrieval potential for spaceborne data. Despite the correlation keep high for large biomass values without showing apparent saturation, the SNR can become critical when the forest becomes very dense. Therefore, GNSS-R may be particularly

Fig. 11. Density plot of the AGB and H retrieval validation on the test areas using TDS-1 data. Density plot of estimated versus target AGB (a) and estimated versus target tree height (b).

Fig. 12. Density plot of the AGB and H retrieval validation on a global scale using CyGNSS data. a) AGB estimated by ANN as a function of the reference from the pantropical map, b) tree height estimated by ANN as a function of the reference H from the ICE-GLAS data.

effective for higher latitude forests, where less dense woodlands are expected, preventing very low SNR.

To summarize, on a local scale, the observed sensitivities were 16 dB/VOD unit, $0.05 \text{ dB}(\text{t/ha})^{-1}$ and 0.7 dBm^{-1} , for VOD, AGB and H , respectively. The corresponding sensitivities at global scale were 7 dB/VOD, $0.01 \text{ dB}(\text{t/ha})^{-1}$ and 0.23 dBm^{-1} . It should be noted that the sensitivity reported from two different airborne experiments were $0.015 \text{ dB}(\text{t/ha})^{-1}$ and $0.05 \text{ dB}(\text{t/ha})^{-1}$, and thus the present results confirm this range of values [80], [15]. The correlation coefficient is not very high, but the impact on the reflectivity of many other factors (e.g., moisture, roughness) should be considered, as well as the poor temporal matching among the data (despite the expected temporal stability of the forest conditions). It is noticeable that the higher correlation was observed with VOD at a local scale, implying a good time matching between SMAP and TDS-1 data, in contrast with that considering static maps of AGB and tree heights.

VI. FOREST BIOMASS RETRIEVAL

An investigation of the GNSS-R capabilities in estimating the forest biomass was carried out. To cope with the high scattering of the experimental points, prototype retrieval algorithms based on Artificial Neural Networks (ANN) were developed [36], with the aim of estimating AGB and forest height from I^-

derived from TDS-1 and CyGNSS alone and in synergy with ALOS data. Furthermore, an attempt to jointly estimate VOD and SM was carried out by using the SMAP datasets as targets for training and validating the algorithms [47]. When possible, ancillary data have been introduced in the retrieval algorithm to mitigate the ill-posedness of the inverse problem. In particular, the incidence angle has been added to the reflectivity as input to the net; the pixel geographical location also proved a positive impact, although quite small. A synergic retrieval using both GNSS-R and ALOS radar data was also attempted.

Algorithms were applied to local retrievals on the selected test areas and also globally. The feed-forward multi-layer perceptron neural networks (MLP-ANNs) available in the Matlab® Neural Networks toolbox was applied. The training was based on the back propagation (BP) learning rule. From each of the available datasets illustrated in the previous section VI, a subset of data was considered for training the algorithm and the remaining data for its validation. The percentage of data used for training and testing depends on the given implementation: a 50% and 50% separation of the dataset in training and test sets was adopted for applications at local scale, due to the small amount of data available, while for global scale it was possible to decrease the training set down to 1% of the total dataset, keeping the 99% of data for the algorithm test. The network structure (i.e., the number of neurons and hidden layers and the transfer function) was defined by applying the iterative

Fig. 13. The validation of SM and VOD retrievals: a) VOD estimated by CyGNSS as a function of the reference data from SMAP, b) SM estimated by CyGNSS as a function of the reference data from SMAP.

Fig. 14 a) global biomass map at 5 Km resolution obtained from CyGNSS data by using the ANN algorithm, b) absolute difference between the map and the improved pan-tropical Above Ground Biomass (AGB) [62], considered as reference.

architecture definition described in [47], [81], while the *early stopping* technique was used to prevent overfitting. In detail, this technique further subsamples the training set in 60%, 20%

and 20% subsets: at each training iteration the first subset is used to adjust the ANN parameters using BP, and the actual parametrization is applied to the other two and third subsets for

having independent tests; training stops as soon as the errors on the three subsets begin to diverge. In general, the “optimal” ANN, depending on the given problem, was composed of two hidden layers with a number of neurons between 7 and 14, respectively, and a transfer function of type logistic sigmoid (logsig) or hyperbolic tangent (tansig).

In Fig. 11 the results of two exercises conducted on a local scale using TDS-1 data to retrieve both AGB and trees height are presented. In both cases, 50% of the dataset was considered for training the ANN, and the remaining for validating the algorithm. It should be reminded, again, that the “static” maps (AGB or H) are not the optimal reference for comparing time series of satellite acquisitions. Nonetheless, the obtained results are encouraging, as pointed out by $R \approx 0.8$ obtained in both cases, and RMSE of 38 t/ha for AGB retrieval (in the range 100 to 400 t/ha) and 3.1 m for H retrieval (in the range 10-40 m), respectively.

On a global scale the results are likewise interesting and are shown in Fig. 12, where the AGB and H estimated by the ANN by using CyGNSS data are represented as a function of the corresponding target parameter. The correlation coefficients of AGB and H retrievals are good, $R \approx 0.82$ and $R \approx 0.80$, respectively, and the RMSE slightly worse than on the local scale, i.e., 76 t/ha for AGB retrieval (in the range 100 to 500 t/ha) and 6.5 m for H (in the range 0-40 m).

The VOD and SM retrievals are shown in Figs. 13 a) and b). The statistics were: for VOD retrievals $R \approx 0.92$, RMSE=0.1 and bias negligible, for SM retrievals $R \approx 0.85$, RMSE=0.07 (m³/m³) and bias negligible. These results have been computed on a dataset of about 2.6 million samples, corresponding to about 6 months of SMAP daily acquisitions at global scale (from April to September 2017).

After validation, the ANN algorithms have been applied to generate global maps of forest AGB and tree height. The AGB map generated by the ANN using CyGNSS data is shown in Fig. 14 a), whilst Fig. 14 b) shows the absolute difference between the map and the corresponding target data from the improved pan-tropical AGB map [62], considered as reference for implementing and validating the ANN algorithm. The agreement between the two maps is evident from the absolute error values, and the corresponding statistics are in line with the results shown in Fig. 12 b). However, some local patterns with high biomass are slightly underestimated by the algorithm, as it can be deduced from the increase of the absolute error in some areas of equatorial forests in Africa and South America. The underestimation of the AGB values higher than 400 t/ha can be also observed in the scatterplot of Fig. 12 b), and it could be attributed either to the GNSS-R signal saturation for higher AGB values or to some training limit, being the higher biomass values less represented in the training set due to the limited number of samples.

In summary, the ANN estimates compared with the reference data of the test set resulted in a correlation coefficient $0.8 \leq R \leq 0.9$ between retrieved and reference quantities in the various experiments, and $37 \text{ t/ha} \leq \text{RMSE} \leq 76 \text{ t/ha}$ for local and global AGB retrievals (AGB in the range 0 – 400 t/ha), and $3.1 \text{ m} \leq \text{RMSE} \leq 6.5 \text{ m}$ for tree height retrieval (H in the range 0 – 45 m). Indeed, GNSS-R may have a role for monitoring forest biomass at average resolution. Waiting for the BIOMASS P-band SAR mission, a high-resolution product based only on

Fig. 15. Time series analysis of the SMAP FT fraction (solid red curve, right axis) and percentage of frozen pixels (dotted red curve, right axis) versus the TDS-1 calibrated reflectivity (left axis). The relevant macro-area land-cover classes are reported in the subfigure title. θ_0^T indicates the upper bound of the considered incidence angles. Pictures from [28].

satellite data with high temporal frequency is unavailable, so that GNSS-R could offer the possibility of effectively covering a gap in the monitoring of forest biomass. Also, the synergy between GNSS-R and monostatic radar SAR is promising, as GNSS-R sensitivity is kept for biomass values larger than the typical saturation threshold in L-band backscatter (~ 150 ton/ha), provided the SNR is adequate.

VII. INVESTIGATION ON THE FREEZE-THAW SENSITIVITY

TDS-1 data have shown that GNSS-R can have good sensitivity for Freeze-Thaw (F/T) sensing in the active zone of permafrost [28]. Time series of monthly averaged TDS-1 reflectivity over a grid of 36 km x 36 km cells were compared

with the co-located monthly Freeze/Thaw Fraction (FTF) product provided by SMAP, grouped in land cover (LC) types.

The results showed a strong agreement between the trends of the two time-series for almost all the LC classes, with TDS-1 reflectivity exhibiting a dynamic range of 10 dB (see Fig. 15, more details can be found in [28]). Lower reflectivity values were obtained in winter months, when the SMAP FTF product indicated a higher fraction of frozen pixels, and vice versa. Two exceptions (i.e., noisy temporal trends of reflectivity), were found for two LC classes: grassland and forest evergreen. The first case can be explained by the less marked discrimination of F/T conditions in areas located at lower latitudes. The second case can be explained by the attenuating effect of the vegetation on the GNSS-R signal.

Throughout the project, additional analyses were carried out to compare: *i*) spatial patterns of GNSS-R and SMAP FTF gridded data (36 x 36 km); *ii*) GNSS-R and in situ temperature data. In both cases it was highlighted the GNSS-R sensitivity to frozen soil conditions. In particular, the comparison with in-situ data collected by stations located in Canada, Finland, Siberia, and Alaska showed that the anomalies (i.e., deviation from the temporal average value) in TDS-1 reflectivity data were correlated with in-situ soil temperature. Negative anomalies can be associated to frozen soil conditions, whereas positive anomalies align with thawed soil conditions. Transitional seasons (in which the average temperature ranges between -2 and 2 °C), and months characterized by higher NDVI values produced results with higher degree of uncertainty (lower correlation between GNSS-R reflectivity and temperature). More details about this analysis can be found in [28].

VIII. SIMULATORS UPGRADE AND VALIDATION

A. GEROS

In this project the GARCA/GEROS-SIM4LAND software packages has been implemented starting from the GARCA/GEROS-SIM OCEAN version which simulates the spaceborne GNSS-R observables (DDM and waveforms) over ocean [48]. Many parts were directly reused without modifications, for example, the DDM generation module. However, some parts were modified according to the mechanisms of GNSS-R signal reflection and scattering over land. The simulator operates according to two simulation modes: 1) parameter sweep mode, and 2) orbital propagation mode with inhomogeneous FOV. More details can be found in [49].

The static mode simulates the DDM varying a single input parameter, holding the other parameters as constant. This mode is efficient to study the impact of a single parameter on the DDM. In the static mode, the specular reflection point is set as user input (lat, lon). Other user inputs for this mode are the receiver orbital height, the incident angle, the azimuths of the transmitter and receiver.

The orbit progressing mode for inhomogeneous FOV simulates the DDM according to the actual orbit progress on each epoch. To simulate an actual spaceborne GNSS-R instrument like TDS-1, the transmitter and receiver states (positions and velocities) are inputs of the simulation. The geophysical data describing the Earth surface are also read from

a database that was produced during the SAIRPS RTM development [34]. This mode is useful to compare to TDS-1 data, as well as any future spaceborne GNSS-R mission. Note that the DDM output is furnished in unit of received power of the down-looking antenna, assuming nominal EIRP of the GNSS transmitters. A few examples of the simulator outputs and validation with respect to real GNSS-R data are presented in the following.

An example of the simulation results of the static mode is shown in Fig. 16. According to the input parameters concerning observation geometry, specular point location, and geophysical value characterizing the surface target, the simulator computes the internal variables and provide the output DDM. Fig. 17 shows the result of one snapshot in the case of the orbit progress mode. According to the transmitter and receiver positions and velocities read from TDS-1 files, the observation geometry is computed, and the reflection/scattering scene is modelled using the geophysical database from SAIRPS RTM. Finally, the DDM is computed and delivered as an output.

The static mode of the simulator is more suitable to study the geophysical parameter impacts on the DDM with a simple sweep of the geophysical quantity. As an example, Fig. 17 shows the values of DDM peak as a function of the soil moisture. The peak value increases with the increase of soil moisture. The slope of the curve complies with two regimes: 1) 43 dB in the SM range [0 – 0.15], 2) 8.6 dB in the range of [0.15–0.45]. The slope in [0 – 0.45] is 17 dB. These values are in agreement with the experimental results published in [34], i.e., 38 dB/100% for bare dry soils, and [19] ~9 dB/100% at global scale, and show that the higher sensitivity to SM is achieved for dry soils.

The results for inhomogeneous FOV of the orbit progress mode were produced for different parts of the world and compared with TDS-1 data. We only show one case over Tunisia, in a dry and flat region with high desert fraction. Figure 18 shows the DDM peak values, which is quite weak due to the rough and dry soil. The highest value of the DDM on this area is comparable to the lowest DDM peak on more wet areas with complex topography, i.e., -169 dBw. Both the simulation and real DDM peaks have very similar shapes, being somehow different in the middle part. There is also a peak value on the final part of the DDM peak plot, which corresponds to a flat ground. A comparison between the simulated and measured power is reported in Fig. 19.

In summary, the simulator has been verified and validated using the TDS-1 data for four different cases. The simulated DDM follows quite well the TDS-1 DDM, in term of shape in the delay-Doppler plane and peak values. The specific conditions of the FOV are also reflected in the simulated DDM, e.g., dry and wet, desert and forest, inland water, and coast. The GARCA/GEROS-SIM4LAND simulator is available online at: <http://147.83.91.189/>.

B. SAVERS

SAVERS (Soil And VEgetation Reflection Simulator) was conceived as a simulator of GNSS-R instrument response able to incorporate the most accurate electromagnetic models of bare and vegetated land surfaces [50]. The first version of the SAVERS simulator was developed during the Leimon project

Rx, Tx, SP positions

FOV altitude, Delay and Doppler

Fig. 16. Results of static mode GARCA simulations. Note the K-shape of the noise-free DDM resulting from the sum of the coherent and incoherent components (bottom left panel). This shape is not that clear in the noisy DDM (bottom right panel), and the incoherent term is mostly buried under the noise. (From [49]).

funded by ESA, and validated using the ground based experimental campaign at Montespertoli, Italy [13]. It takes as input system and observation parameters, as well as geophysical parameters of soil and growing sunflower plants. During a second ESA project (i.e., GRASS), SAVERS has been refined to include forest attenuation and scattering properties, as well as mixed pixel effects. It has been applied and validated in the conditions of the airborne campaign at Forcoli [15], Italy.

In this project, SAVERS has been modified to fit a satellite-borne GNSS-R configuration, specifically the observational setup of TechDemoSat-1, leading to the SAVERS-TDS release [51]. In particular, the main improvements consist in the introduction of the effect of topography, of a very large footprint and the actual TDS-1 antenna pattern. Some additional upgrades regarding the electromagnetic modelling of the

Fig.17. Input data and results of orbit progress / inhomogeneous mode GARCA simulation (From [49]).

coherent near-specular component was also included as detailed in [52].

The SAVERS simulator operates similarly to the orbit progress mode illustrated with reference to the GARCA/GEROS-SIM4LAND simulator. It provides many plots describing the geometrical and electromagnetic parameters of the scene under study, as detailed in [50]. The

final outputs are the full DDMs, calibrated in terms of surface equivalent reflectivity, and their peak values can be compared directly to the TDS-1 or CyGNSS observations.

In this paper we do not provide details about the mathematical formulations implemented in SAVERS-TDS; they can be found in [50] and [51]. We rather provide samples of the simulator outputs, of the investigation about sensitivity of GNSS-R

Fig. 18. Simulated DDM peak values with GARCA as a function of soil moisture. Simulation over the entire SM dynamic range (left panel, from [49]) and corresponding mean sensitivity are compared to the sensitivity estimates for small (upper-right) and large (bottom-right) values of SM.

Fig. 19. DDM peak values of Case 1 Tunisia: (top) GARCA simulated power and TDS-1 digital count, (bottom) normalized values. From [49].

reflectivity to the relevant geophysical parameters enabled by SAVERS-TDS, and of the validation effort based on the comparison with TDS-1 data. The sensitivity analysis consisted in varying one parameter at a time in a selected range, keeping fixed all the others.

In Fig. 20 we report the LR reflectivity versus the soil moisture as predicted by SAVERS. Here we show as the SM sensitivity changes according to the surface topography. Considering a real DEM of a volcanic area in Chad, we have

Fig. 20. SAVERS simulated reflectivity at LR polarization versus SM , for a height roughness standard deviation $\sigma_z=1.5$ cm and incidence angle $\theta_i=25^\circ$. Left panel: different colours represent different topographic elevation of the SP. The real topographical relief was provided by the SRTM DEM reported on the right panel. Circle and Cross correspond to the positions of the specular point of simulations at different elevations.

Fig. 21. SAVERS simulated reflectivity at LR polarization versus forest biomass, for a height roughness standard deviation $\sigma_z=1.5$ cm. Left panel: SAVERS simulated reflectivity versus biomass for a real topographical relief and an incidence angle $\theta_i=25^\circ$ (different colors represent different height of the SP). The SRTM DEM is reported on the right panel. Circle and cross correspond to the positions of the specular point corresponding to different elevations.

selected 2 specular points at different elevation along a TDS-1 track and plotted the reflectivity as a function of the SM . The corresponding reflectivity over a flat terrain (the top blue line) is reported as a reference and the small-scale roughness was set to 1.5 cm with no vegetation on top.

It is possible to observe that the sensitivity to SM is quite independent of the surface elevation, though the LR reflectivity gets lower as the elevation gets higher.

In Fig. 21 the sensitivity to forest biomass is compared for SPs at different heights along a TDS-1 track over the same mountainous terrain. For ease of reference, the same geographical locations as in Fig. 20 has been selected, though it is not actually a forested site. The biomass variation was set in the range $[25\div 400]$ t/ha, which is linked to a variation of the

mean diameter at breast height (dbh) within the range $[7\div 21]$ cm, and of density within $[350\div 100]$ trees/ha through the allometric equations in [64]. The reflectivity corresponding to a flat terrain is reported as a reference (the top blue curve). It can be observed that the sensitivity to biomass decreases over areas with an important topography. Since the elevation decreases the reflectivity value, the coherent scattering may eventually become weaker than incoherent scattering from vegetation volume and underlying soil. In this case, the saturation threshold is reached, as it happens in the monostatic case, and the sensitivity to biomass may be lost. It is worthwhile remarking that SAVERS is able to model not only attenuation contributions connected to VOD, but also volume scattering from the vegetation canopy [38].

Fig. 22. a), c): TDS-1 DDM. b), d): SAVERS DDM with 100 m DEM resolution. a), b): specular point at 20.22° latitude (at an elevation of about 1500m). c), d): specular point at 21.89° latitude (at an elevation of about 900m).

The reliability of SAVERS was evaluated over bare areas with a complex topography and over forested areas, by comparing the simulator output with TDS-1 data. The resolution of the DEM was demonstrated having an impact on the simulation accuracy. As a trade-off between accuracy and computational time a 300 DEM is the best choice [51].

In Fig. 22 the measured DDMs are shown on the left and the ones simulated by SAVERS are shown on the right (using a 100 m resolution DEM) for two acquisitions along a track overpassing the Chad volcanic area, as in the previous examples. The data collected over complex topography are characterized by a noisy DDM, where a clear pattern is less recognizable, and several peaks are spread in the DDM. Note that the shift of the DDM peak in the Doppler domain was found both from the data and the simulations being opposite for the cases of the receiver approaching (positive Doppler shift as in the upper panels) the mountains or leaving them (negative Doppler shift as in the lower panels).

A quantitative comparison of the peak reflectivity measured by TDS-1 and simulated by SAVERS along the same orbit is shown in Fig. 23, where the profile of surface height is also reported. It is interesting to note the large difference in reflectivity associated to the topography, with much smaller values over the higher terrain where many DEM facets with different orientations can contribute to the signal, none of them producing a strong specular reflection as in the case of an infinite plane surface. Note that the small-scale roughness was

not known in the area, so that its value was selected in the order of 3.5 cm. The value of the roughness height standard deviation shifts the reflectivity profile up or down, but the dynamic range of the reflectivity due to the topography along the track is notably reproduced by SAVERS.

A similar comparison was carried out over forested areas. Fig. 24 compares the measured and simulated peak reflectivity along a track overpassing a forested area near the border between Congo and Zambia. The tree height as provided by Lidar data [61] is included in the plot as an indicator of vegetation biomass along the track. The simulated reflectivity corresponds to a mean biomass of 100 t/ha, and its trend is smoother than the observed one, as it underestimates the higher reflectivity and overestimates the lower reflectivity values, with a R^2 of 0.23 and a RMSE of 3.15 dB. However, the LIDAR tree height shows an inhomogeneity of the vegetation along the track. In particular, the area between -10.2° latitude and -9.6° latitude is characterized by taller trees and consequently a higher biomass than the rest of the track. On the contrary, the peak at -11.4° latitude corresponds to a minimum of tree height, so that it is very likely due not only to a topography effect but also to a very low biomass or bare surface. Therefore, it is realistic to assume that the biomass is variable along the track. The error bars overlapping the simulated peak reflectivity in Fig. 24 indicate the reflectivity variations if the biomass ranges from 80 t/ha to 120 t/ha.

Fig. 23. TDS-1 peak reflectivity compared to reflectivity simulated with SAVERS for a bare soil. The error bars indicate the reflectivity variations for surface small-scale roughness ranging from 3.2 cm to 3.8 cm. The surface elevation is extracted from SRTM DEM.

The low values of reflectivity measured by TDS-1 would have not been reproduced without the consideration of the forest attenuation that was predicted by SAVERS by suitable allometric relations associating a value of the biomass to the height measured by the Lidar. A careful analysis of this data set shows that some features of reflectivity profile were reproduced by introducing a DEM in the simulation, whereas other features were associated to the change in the vegetation, leading to an

Fig. 24. SAVERS simulated and observed peak reflectivity versus latitude. The error bars indicate the reflectivity variations for biomass ranging from 80 to 120 t/ha. The tree height is estimated from LIDAR data [61].

overall good agreement between simulation and measurements, at least for most of the track.

IX. DISCUSSION AND CONCLUSION

The work carried out in the frame of an ESA-funded project, focused on the study of the potential application of GNSS reflectometry over land, was described and summarized. The research confirmed previous findings about the sensitivity of the reflection to land bio-geophysical parameters, i.e., soil moisture and forest biomass. It confirmed, coherently with other works from the literature, that the sensitivity to the target parameters can be considered well established and quite promising also in case of satellite observations. It is noticeable that the «average» behavior of the signal (i.e., its trend as a function of the target parameters once any other effect is properly smoothed out) is also quite well reproduced by models. The increase of reflectivity with soil moisture, which is due to the increase of permittivity, and its decrease as a function of the forest biomass due to attenuation of the coherent soil reflection, are reproduced by models if the coherent and incoherent contributions to the signal and the effect of topography are properly considered.

Table 3 and 4 summarize the sensitivities derived from the different experiments and model predictions carried out during the project. Results are quite consistent, with the airborne data exhibiting a higher sensitivity, but referring to drier conditions.

The impact of topography is clearly highlighted by the work, both experimentally and from models. There was a consensus in the need to upgrade the simulation models introducing the topography effect when predicting the signal from satellite.

The spatial resolution can be also good (order of kilometers) for very flat surfaces if the signal is mainly coherent, otherwise it goes down to about 25 km. However, measurements are sparse (they are not arranged as in one image) and they are not characterized by exact and fixed repetition cycle. Then, some

	Empirical $\theta_i=0-30^\circ$	Theoretical
TDS-1 (VOD theoretically corrected)	7 dB/ $1\text{m}^3\text{m}^{-3}$ 3 dB/ $0.4\text{m}^3\text{m}^{-3}$	6÷6.8 dB/ $0.4\text{m}^3\text{m}^{-3}$
CyGNSS	15 dB/ $1\text{m}^3\text{m}^{-3}$ 6 dB/ $0.4\text{m}^3\text{m}^{-3}$	
CyGNSS binned	~18 dB/ $1\text{m}^3\text{m}^{-3}$ (θ_i ~independent) ~7 dB/ $0.4\text{m}^3\text{m}^{-3}$	
CyGNSS VOD and σ empirically corrected	26 dB/ $1\text{m}^3\text{m}^{-3}$ (θ_i ~independent) ~10 dB/ $0.4\text{m}^3\text{m}^{-3}$	
GLORI	~18÷11 dB/ $0.4\text{m}^3\text{m}^{-3}$ (relatively dry case)	

Table 3. Summary of sensitivity to SM from the different experiments. It is indicated in dB per unit of volumetric soil moisture (in m^3/m^3) and as dynamic range over the typical range of SM (between 0 and $0.4 \text{ m}^3/\text{m}^3$)

Sensitivity to	local	global	theoretical
VOD (Np)	-16 dB/1VOD	-7 dB/1VOD	< -11 dB/1VOD
AGB (t/ha)	-0.05 dB/ha ⁻¹ 18 dB/[50-400 t/ha]	-0.01 dB/ha ⁻¹	26 dB/[50-400 t/ha]
Tree height (m)	-0.7 dB/m	-0.23 dB/m	

Table 4. Summary of sensitivity of spaceborne reflectivity to different forest parameters derived from local and global scale analysis.

aggregation in space and time must be carried out to come with a product having a raster (i.e., gridded) format. The GNSS-R technique is also affected by a poor coverage and temporal resolution. As a matter of fact, a specular point for repeating passes is located in different positions, so that for inhomogeneous targets this can generate a variable signal as a function of time. For these reasons, a constellation of small satellites must be considered to overcome the problem [83], [84].

The work has also addressed the need of ancillary data for retrieving the target parameters to compensate for the effects of other features affecting the signal, including the small-scale surface roughness and the topography (this is however a common situation in remote sensing). Dual polarized GNSS-R observations have been proved quite useful from low platforms, but not yet tested from satellite, except for the experiment exploiting the SMAP radar as a GNSS receiver.

In addition to the influence of many parameters on the signal and the fact that observations are not regularly repeated on the same point in inhomogeneous areas, large fluctuations (sort of speckle) were observed even in case the signal was expected to be prevalently *coherent*, as in the case of flat surfaces [16].

In conclusion, many sources of signal fluctuation were observed due to non-systematic sampling over time of an inhomogeneous earth surface, to the influence of nuisance parameters (such as topography), as well as to a speckle effects not mitigated by the incoherent integration. Other sources of uncertainty are likely related to calibration issues (e.g., unknown changes in the transmitted power, antenna gain characterization, etc.), not completely solved in the current missions. Those fluctuations must be mitigated to achieve reasonable retrieval performances of the target quantities. Then a proper strategy for calibration, noise mitigation and spatial and temporal aggregation has to be carried out, leading to final resolutions of the products still to be optimized. This topic is strictly related to the issue of spatial resolution. Although a specular coherent reflection originates mainly from the first Fresnel zone, in practice over inhomogeneous areas a suitable spatial aggregation must be implemented.

The retrieval exercises carried out during the project indicate contradictory retrieval results, depending on the space-time

averaging. In particular, the comparison of single shot retrievals (i.e., not averaged in time) with reference data was always very poor and the removal of unwanted physical quantities affecting the signal was not effective (e.g., mitigation of the vegetation and roughness effects to retrieve the soil moisture). It was found very difficult to combine single shot GNSS reflectivity with the right ancillary parameters (e.g., roughness, vegetation optical depth) to derive soil moisture even if the former were accurately measured. The highly fluctuating behavior of the signal can explain this outcome.

Rather, in case of averaged quantities, such as biomass maps derived over a long-time frame or daily soil moisture maps, the retrieval performances were promising. Simple empirical linear regressions suffered from the non-linear dependence of reflectivity from surface parameters, whereas change detection techniques, although capable to cope with local effects (assuming they can be considered stationary), do not provide absolute quantities (but only temporal change of the target parameter). Machine learning techniques can overcome those problems, although the consideration of the physical mechanisms affecting the signal should be carefully taken into account, especially to mitigate the risk of overfitting with a blind use of input data. As for soil moisture retrieval, an issue was identified in case of very dry soil, likely associated to the deeper penetration into a stratified terrain.

The selection of required ancillary information in the retrieval algorithms should be further improved, as well as the combination with other satellite data (e.g., monostatic radar or microwave radiometers).

Based on the previous considerations, three objectives are considered a priority for further research in this field. First, the capability to predict the signal over land by the simulators should be confirmed considering data from the CyGNSS constellation and of the future HydroGNSS mission, also to compare the absolute calibration and model validation based on TDS-1 data. Second, the fluctuating behavior of the signal should be better understood. Finally, the use of more sophisticated retrieval techniques based on neural networks should be further expanded to appreciate the real performances of GNSS-R with respect to well established and consolidated products from other earth observation techniques (e.g., microwave radiometers). Future dataset and future missions with enhanced features will help improve the potential and the quality of the retrieval of the bio-geophysical parameters, especially the biomass variable and the freeze-thaw state, which are relatively more immature and demand for more accurate investigations.

ACKNOWLEDGMENTS

This work has been carried out in the frame of the ESA project N. 4000120299/17/NL/AF/hh. TehchDemoSat-1 data have been freely collected from the MERRByS portal at merrbys.co.uk. CyGNSS and SMAP data have been downloaded from NASA Earthdata portal at podaac.jpl.nasa.gov and nsidc.org/data/smap, respectively. SMOS data are made available from ESA through the smos-diss.esa.int website.

This work has also been partially supported by the project of the Ministerio de Ciencia, Innovación y Universidades and EU ERDF ref. RTI2018-099008-B-C21/AEI/10.13089/E01100011083 “Sensing with pioneering opportunistic techniques”, and grant MDM-2016-0600 to CommSensLab-UPC “María de Maeztu” Excellent Research Unit.

REFERENCES

- [1] M. Martin-Neira, “A passive reflectometry and interferometry system (PARIS): Application to ocean altimetry,” *ESA journal* vol. 17, no. 4, pp. 331-355, 1993.
- [2] J. L. Garrison, and S. J. Katzberg, “The application of reflected GPS signals to ocean remote sensing,” *Remote Sensing of the Environment*, vol. 73, p. 175-187, 2000.
- [3] V. U. Zavorotny, S. Gleason, E. Cardellach, and A. Camps, “Tutorial on remote sensing using GNSS bistatic radar of opportunity,” *IEEE Geosci. Remote Sens. Mag.*, vol. 2, no. 4, pp. 8-45, 2014.
- [4] C. S. Ruf, C. Chew, T. Lang, M. G. Morris, K. Nave, A. Ridley, and R. A. Balasubramaniam, “A new paradigm in earth environmental monitoring with the CyGNSS small satellite constellation,” *Sci. Rep.* vol. 8 no. 11, p. 8782, Jun. 2018.
- [5] M. Martin-Neira, S. D’Addio, C. Buck, N. Floury, and R. Prieto-Cerdeira, “The PARIS ocean altimeter in-orbit demonstrator,” *IEEE Trans. Geosci. Remote Sens.*, vol. 49, no. 6, pp. 2209-2237, June 2011.
- [6] A. Camps et al., “Optimization and performance analysis of interferometric GNSS-R altimeters: Application to the PARIS IoD mission,” *IEEE J. Selected Topics Appl. Earth Obs. Remote Sens.*, vol. 7, no. 5, pp. 1436-1451, May 2014.
- [7] J. Wickert et al., “GEROS-ISS: GNSS reflectometry, radio occultation, and scatterometry onboard the international space station,” *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 9, no. 10, pp. 4552-4581, Oct. 2016.
- [8] E. Cardellach et al., “GNSS transpolar Earth reflectometry exploring system (G-TERN): Mission concept,” *IEEE Access*, vol. 6, pp. 13980-14018, 2018.
- [9] M. Unwin, et al., “An Introduction to the HydroGNSS GNSS reflectometry remote sensing mission,” *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, vol. 1, pp. 6987-6999, 2021.
- [10] H. Carreno-Luengo, G. Luzi, and M. Crosetto, “Sensitivity of CyGNSS bistatic reflectivity and SMAP microwave radiometry brightness temperature to geophysical parameters over land surfaces,” *IEEE J. Selected Topics Appl. Earth Obs. Remote Sens.*, vol. 12, no. 1, pp. 107-122, 2019.
- [11] A. Camps, Alonso-Arroyo, A.; Park, H.; Onrubia, R.; Pascual, D.; Querol, J. L-Band, “Vegetation Optical Depth Estimation Using Transmitted GNSS Signals: Application to GNSS-Reflectometry and Positioning,” *Remote Sens.*, vol. 12, p. 2352, 2020.
- [12] E. Motte, M. Zribi, P. Fanise, A. Egido, J. Darrozes, A. Al-Yaari, and P. L. Frison, “GLORI: A GNSS-R dual polarization airborne instrument for land surface monitoring,” *Sensors*, vol. 16, no. 5, p. 732, 2016.
- [13] A. Egido, M. Caparrini, G. Ruffini, S. Paloscia, E. Santi, L. Guerriero, N. Pierdicca, N. Floury, “Global navigation satellite systems reflectometry as a remote sensing tool for agriculture”, *Remote Sensing*, vol. 4, pp. 2356-2372, 2012.
- [14] P. Ferrazzoli, L. Guerriero, N. Pierdicca, and R. Rahmoune, “Forest biomass monitoring with GNSS-R: Theoretical simulations,” *Adv. SpacRes.*, vol. 47, no. 10, pp. 1823–1832, 2011.
- [15] A. Egido, S. Paloscia, E. Motte, L. Guerriero, N. Pierdicca, M. Caparrini, E. Santi, G. Fontanelli, N. Floury, “Airborne GNSS-R polarimetric measurements for soil moisture and above-ground biomass estimation. *IEEE J. Sel. Top. Appl. Earth Obs. Remote Sens.*, vol. 7, pp. 1522–1532. doi:10.1109/JSTARS.2014.2322854, 2014.
- [16] D. Comite and N. Pierdicca. “Decorrelation of the near-specular land scattering in bistatic radar systems,” *IEEE Trans. Geosci. Rem. Sens.*, 2020, in press, DOI: 10.1109/TGRS.2021.3072864.
- [17] M. Zribi, E. Motte, N. Baghdadi, F. Baup, S. Dayau, P. Fanise, D. Guyon, M. Huc, J. Wigneron, “Potential applications of GNSS-R observations over agricultural areas: Results from the GLORI airborne campaign,” *Remote Sens.* 10, no. 8, p. 124, 2018.
- [18] R. Onrubia, D. Pascual, J. Querol, J. Castellvi-Esturi, J. Corbera, H. Park, and A. Camps, “Preliminary altimetry results of the MALYGNSS instrument in the HUMIT project,” *Proc. IEEE Int. Geosci. Remote Sensing Symp.*, pp. 3331-3334, 2018.
- [19] A. Camps, M. Vall-Ilosera, H. Park, G. Portal, and L. Rossato, “Sensitivity of TDS-1 GNSS-R Reflectivity to Soil Moisture: Global and Regional Differences and Impact of Different Spatial Scales,” *Remote Sens.*, vol. 10, no. 11, p. 1856, Nov. 2018.
- [20] N. Rodriguez-Alvarez, E. Podest, K. Jensen, and K. C. McDonald, “Classifying inundation in a tropical wetlands complex with GNSS-R,” *Remote Sensing*, vol. 11, no. 9, p. 1053, 2019.
- [21] K. Jensen, K. McDonald, E. Podest, N. Rodriguez-Alvarez, V. Horna, V., and N. Steiner, “Assessing L-band GNSS-reflectometry and imaging radar for detecting sub-canopy inundation dynamics in a tropical wetlands complex,” *Remote Sensing*, vol. 10, no. 9, p. 1431, 2018.
- [22] C. Chew, J. T. Reager, and E. Small, “CYGNSS data map flood inundation during the 2017 Atlantic hurricane season,” *Scientific Reports* vol. 8, no. 1, pp. 1-8, 2018.
- [23] T. Beltramonte, M. di Bisceglie, C. Galdi, and I. M. Russo, “Remote sensing of inland waters with signals of opportunity from global navigation satellite systems,” *IEEE International forum on Research and Technology for Society and Industry (RTSI)*, pp. pp. 115-119, 2019.
- [24] S. V. Nghiem, et al., “Wetland monitoring with global navigation satellite system reflectometry,” *Earth and Space Science*, vol. 4, no. 1. pp. 16-39, 2017.
- [25] Li, E. Cardellach, F. Fabra, S. Ribó, and A. Rius, “Measuring Greenland ice sheet melt using spaceborne GNSS reflectometry from TechDemoSat-1,” *Geophysical Research Letters*, vol. 47, no. 2, 2020.
- [26] Y. Wang and Y. Jade Morton, “Coherent GNSS Reflection signal processing for high-precision and high-resolution spaceborne applications,” *IEEE Trans. Geosci. Remote Sens.*, vol. 59, no. 1, pp. 831-842, 2020.
- [27] M. Unwin, P. Jales, J. Tye, C. Gommenginger, G. Foti, and J. Rosello, “Spaceborne GNSS-reflectometry on TechDemoSat-1: Early mission operations and exploitation,” *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 9, no. 10, pp. 4525-4539, Sep. 2016.
- [28] D. Comite, L. Cenci, A. Colliander, and N. Pierdicca, “Monitoring freeze-thaw state by means of GNSS reflectometry: An analysis of TechDemoSat-1 Data,” *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 14, pp. 1218-1233, May. 2020.
- [29] X. Wu and J. Shuanggen, “Can we monitor the bare soil freeze-thaw process using GNSS-R?: a simulation study,” *Earth observing missions and sensors: Development, implementation, and characterization III*. vol. 9264. International Society for Optics and Photonics, 2014.
- [30] X. Wu, Z. Dong, S. Jin, Y. He, Y. Song, W. Ma, and L. Yang, “First measurement of soil freeze/thaw cycles in the Tibetan plateau using CYGNSS GNSS-R data,” *Remote Sensing*, vol. 12, no. 15, p. 2361, 2020.
- [31] N. Rodriguez-Alvarez and E. Podest, “Characterization of the land surface freeze/thaw state with SMAP-reflectometry (SMAP-R),” *Proc. IEEE Int. Geosci. Remote Sens. Symp.*, pp. 4024-4027, 2019.
- [32] C. Chew, S. Lowe, N. Parazoo, S. Esterhuizen, S. Oveisgharan, E. Podest, and A. Freedman, “SMAP radar receiver measures land surface freeze/thaw state through capture of forward-scattered L-band signals,” *Remote Sens. Environment*, vol. 198, pp. 333-344, 2017.
- [33] Q. Yan, W. Huang, S. Jin, and Y. Jia, “Pan-tropical soil moisture mapping based on a three-layer model from CYGNSS GNSS-R data,” *Remote Sensing of Environment*, vol. 247, p. 111944, 2020.
- [34] A. Camps, H. Park, M. Pablos, G. Foti, C. P. Gommenginger, Pang-Wei Liu, J. Judge, “Sensitivity of GNSS-R Spaceborne Observations to Soil Moisture and Vegetation,” in *IEEE J. Sel. Topics Applied Earth Obs. Remote Sens.*, vol. 9, no. 10, pp. 4730-4742, Oct. 2016.
- [35] C. Chew, and E. Small, “Soil moisture sensing using spaceborne GNSS reflections: Comparison of CyGNSS reflectivity to SMAP soil moisture”, *Geophysical Research Letters*, April 2018, <https://doi.org/10.1029/2018GL077905>.
- [36] E. Santi, et al., “Remote sensing of forest biomass using GNSS reflectometry,” *IEEE J. Sel. Top. Appl. Earth Observ. Remote Sens.*, vol. 14, p. 107-122, May 2020.
- [37] Carreno-Luengo, H.; Luzi, G.; Crosetto, M. Above-Ground Biomass Retrieval over Tropical Forests: A Novel GNSS-R Approach with

- CyGNSS. Remote Sens. 2020, 12, 1368. <https://doi.org/10.3390/rs12091368>
- [38] L. Guerriero, F. Martin, A. Mollfulleda, S. Paloscia, N. Pierdicca, E. Santi, N. Floury, "Ground-based remote sensing of forests exploiting GNSS signals", *IEEE Trans. Geosci. Rem. Sens.*, vol. 58, n. 10, pp. 6844-6860, 2020.
- [39] A. Camps, A. Alonso-Arroyo, H. Park, R. Onrubia, D. Pascual, and J. Querol, "L-Band vegetation optical depth estimation using transmitted GNSS signals: Application to GNSS-Reflectometry and positioning," *Remote Sensing*, vol. 12, no. 15, 2352, 2020.
- [40] C. Chew, R. Shah, C. Zuffada, G. Hajj, D. Masters, A. J. Mannucci, "Demonstrating soil moisture remote sensing with observations from the UK TechDemoSat-1 satellite mission," *Geophys. Res. Lett.* doi:10.1002/2016GL068189, 2016.
- [41] C. Chew and E. Small, "Description of the UCAR/CU soil moisture product," *Remote Sensing*, vol. 12, no. 10, p. 1558, 2020.
- [42] Senyurek, V., Lei, F., Boyd, D., Gurbuz, A. C., Kurum, M., & Moorhead, R. (2020). Evaluations of a Machine Learning-Based CYGNSS Soil Moisture Estimates against SMAP Observations. *Remote Sensing*, 12(21), 3503.
- [43] Eroglu, O.; Kurum, M.; Boyd, D.; Gurbuz, A.C. High Spatio-Temporal Resolution CYGNSS Soil Moisture Estimates Using Artificial Neural Networks. *Remote Sens.* 2019, 11, 2272.
- [44] S. H. Yueh, et al., "A semiempirical modeling of soil moisture, vegetation, and surface roughness impact on CYGNSS reflectometry data," *IEEE Trans. Geosci. Remote Sens.*, 2021, doi: 10.1109/TGRS.2020.3035989.
- [45] Al-Khaldi M. M., J. T. Johnson, A. J. O'Brien, A. Balenzano and F. Mattia, "Time-Series Retrieval of Soil Moisture Using CYGNSS," in *IEEE Transactions on Geoscience and Remote Sensing*, vol. 57, no. 7, pp. 4322-4331, July 2019, doi: 10.1109/TGRS.2018.2890646.
- [46] Carreno-Luengo, H.; Lowe, S.; Zuffada, C.; Esterhuizen, S.; Oveisgharan, S. Spaceborne GNSS-R from the SMAP Mission: First Assessment of Polarimetric Scatterometry over Land and Cryosphere. *Remote Sens.* 2017, 9, 362. <https://doi.org/10.3390/rs9040362>.
- [47] E. Santi, et al., "Soil moisture and forest biomass retrieval on a global scale by using CyGNSS data and artificial neural networks," *Proc. IEEE Int. Geosci. Rem. Sens. Symp.*, pp. 5905-5908, 2020.
- [48] H. Park, A. Camps, D. Pascual, Y. Kang, R. Onrubia, J. Querol, and A. Alonso-Arroyo, "A generic level 1 simulator for spaceborne GNSS-R missions and application to GEROSS-ISS ocean reflectometry," *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 10, no. 10, pp. 4645-4659, 2017.
- [49] H. Park, A. Camps, J. Castellvi, and J. Muro, "Generic performance simulator of spaceborne GNSS-reflectometer for land applications," *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 13, pp. 3179-3191, 2020.
- [50] N. Pierdicca, L. Guerriero, R. Giusto, M. Brogioni, and A. Egido, "SAVERS: A simulator of GNSS reflections from bare and vegetated soils," *IEEE Trans. Geosci. Remote Sens.*, vol. 52, no. 10, pp. 6542-6554, 2014.
- [51] L. Dente, L. Guerriero, D. Comite, and N. Pierdicca, "Space-borne GNSS-R signal over a complex topography: modelling and validation," *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol.13, pp. 1218-1233, Mar. 2020.
- [52] D. Comite, F. Ticconi, L. Dente, L. Guerriero, and N. Pierdicca, "Bistatic coherent scattering from rough soils with application to GNSS reflectometry," *IEEE Trans. Geosci. Remote Sens.*, vol. 58, no. 1, pp. 612-625, 2019.
- [53] Camps, A., L. Cenci, M. P. Clarizia, D. Comite, F. Costantini, L. Dente, L. Guerriero, A. Mollfulleda, S. Paloscia, H. Park, N. Pierdicca, J. Reynolds, E. Santi, M. Zibri, "Potential of Spaceborne GNSS-R for Land Applications - Final Report", ESA/ESTEC CONTRACT n. 4000120299/17/NL/AF/hh, GLA-FR/1.2019, 30 September 2019.
- [54] Measurement of Earth Reflected Radio-navigation signals By Satellite, <http://merbys.org>
- [55] C. Ruf, P. Chang, M. P. Clarizia, S. Gleason, Z. Jelenak, J. Murray, M. Morris, S. Musko, D. Posselt, D. Provost, D. Starkenburg, V. Zavorotny, *CYGNSS Handbook*, Ann Arbor, MI, Michigan Pub., ISBN 978-1-60785-380-0, 154 pp, 1 Apr 2016
- [56] Physical Oceanography Distributed Active Archive Center, <ftp://podaac-ftp.jpl.nasa.gov>.
- [57] F. Ulaby and D. Long, *Microwave radar and radiometric remote sensing*, Artech House, 2015.
- [58] N. Pierdicca et al., "Spaceborne GNSS reflectometry data for land applications: an analysis of Techdemosat data," *Proc. IEEE Int. Geosci. Remote Sensing Symp.*, pp. 3351-3354, 2018. DOI: 10.1109/IGARSS.2018.8517987.
- [59] A. M. Balakhder, M. M. Al-Khaldi, and J. T. Johnson, "On the coherency of ocean and land surface specular scattering for GNSS-R and signals of opportunity systems," *IEEE Trans. Geosci. Remote Sens.*, vol. 57, no. 12, pp. 10426-36, Sep. 2019.
- [60] H. Xu, J. Zhu, L. Tsang, and S. B. Kim, "A fine scale partially coherent patch model including topographical effects for GNSS-R DDM simulations," *Progress In Electromagnetics Research*, vol. 170, pp. 97-128, 2021.
- [61] M. Simard, N. Pinto, J. B. Fisher, and A. Baccini, "Mapping forest canopy height globally with spaceborne lidar", *J. Geophysical Res.*, vol. 116, G04021, 2011.
- [62] V. Avitabile, et al., "An integrated pan-tropical biomass maps using multiple reference datasets," *Global Change Biology*, vol. 22, pp. 1406-1420. doi:10.1111/gcb.13139.
- [63] P. Burek, J. M. Van Der Knijff, and A. De Roo, "LISFLOOD - distributed water balance and flood simulation model - Revised User Manual. Doi: <http://dx.doi.org/10.2788/24719>, 2013.
- [64] A. Camps, H. Park, J. Castellvi, J. Corbera, and E. Ascaso, "Single-pass soil moisture retrievals using GNSS-R: Lessons learned," *Remote Sensing*, vol. 12, no. 12, p. 2064, 2020.
- [65] J. C. Jenkins, D. C. Chojnacky, L. S. Heath, and R. A. Birdsey, "National scale biomass estimators for United States tree species", *Forest Science*, vol. 49, pp. 12-35, 2003.
- [66] A. Camps and J. F. Munoz-Martin, "Analytical computation of the spatial resolution in GNSS-R and experimental validation at L1 and L5," *Remote Sens.*, vol. 12, p. 3910, 2020.
- [67] H. Carreno-Luengo, C. Ruf, A. Warnock, and K. Brunner, "Investigating the impact of coherent and incoherent scattering terms in GNSS-R delay doppler maps," *Proc. IEEE Int. Geosci. Remote Sens. Symp.*, Hawaii, USA, July 2020., in press.
- [68] A. Camps, "Spatial resolution in GNSS-R under coherent scattering," *IEEE Geosci. Remote Sensing Lett.*, vol. 17, no. 1, pp. 32-36, 2020.
- [69] G. Portal, M. Vall-llossera, M. Piles, A. Camps, D. Chaparro, M. Pablos, and L. Rossato, "A spatially consistent downscaling approach for SMOS using an adaptive moving window," *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 11, no 6, pp. 1883-1894, 2018.
- [70] M. Piles et al., "A downscaling approach for SMOS land observations: Evaluation of high-resolution soil moisture maps over the Iberian peninsula," *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 7, no. 9, pp. 3845-3857, Sept. 2014
- [71] M. Zribi, M. Foucras, N. Baghdadi, J. Demarty and S. Muddu, "A new reflectivity index for the retrieval of surface soil moisture from radar data," *IEEE J. Sel. Topics Appl. Earth Obs. Remote Sens.*, vol. 14, pp. 818-826, 2021.
- [72] A. Camps and Joan Francesc Munoz-Martin, "Analytical computation of the spatial resolution in GNSS-R and experimental validation at L1 and L5," *Remote Sensing*, vol. 12, no. 23, Pp. 3910, 2020.
- [73] M. Zribi, M. Huc, T. Pellarin, N. Baghdadi, N. Pierdicca, "Soil Moisture Retrieval Using Gns-R Data," *Proc. IEEE Mediterranean and Middle-East Geoscience and Remote Sensing Symp.*, pp. 172-175, 2020.
- [74] O'Neill P., R. Bindlish, S. Chan, E. Njoku, T. Jackson, Soil Moisture Active Passive (SMAP) Algorithm Theoretical Basis Document Level 2 & 3 Soil Moisture (Passive) Data Products, Revision D, June 6, 2018, ref. JPL D-66480.
- [75] R. Acevo-Herrera, A. Aguasca, X. Bosch-Lluis, A. Camps, J. Martínez-Fernández, N. Sánchez-Martín, C. Pérez-Gutiérrez, "Design and first results of an UAV-borne L-band radiometer for multiple monitoring purposes," *Rem. Sens.*, vol. 2 no. 7, pp. 1662-1679, 2010.
- [76] J. F. Munoz-Martin, et al., "Single-pass soil moisture retrieval using GNSS-R at L1 and L5 bands: Results from airborne experiment," *Remote Sensing*, vol. 13, no. 4, p. 797, 2021.
- [77] J. F. Munoz-Martin, et al., "Soil moisture estimation synergy using GNSS-R and L-Band microwave radiometry data from FSSCat/FMPL-2," *Remote Sensing*, vol. 13, no. 5, pp. 994, 2021.

- [78] W. Wagner, G. Lemoine, and H. Rott, "A method for estimating soil moisture from ERS scatterometer and soil data," *Remote Sens. Environ.*, vol. 70, no. 2, pp. 191–207, Nov. 1999.
- [79] M. P. Clarizia, N. Pierdicca, F. Costantini, and N. Floury, "Analysis of CyGNSS Data for Soil Moisture Retrieval," *IEEE J. Sel. Top. Appl. Earth Obs. Remote Sens.* pp. 1-9. 10.1109/JSTARS.2019.2895510, 2019.
- [80] M. Zribi, D. Guyon, E. Motte, S. Dayau, J. P. Wigneron, N. Baghdadi, and N. Pierdicca, "Performance of GNSS-R GLORI data for biomass estimation over the Landes Forest", *Int. J. Appl. Earth Obs. Geoinformation*, 74, 150–158, 2019.
- [81] E. Santi, S. Paloscia, S. Pettinato, G. Fontanelli, "Application of artificial neural networks for the soil moisture retrieval from active and passive microwave spaceborne sensors," *Int. J. Appl. Earth Observ. Geoinf.*, vol. 48, pp. 61–73, 2016.
- [82] D. Comite, L. Dente, L. Guerriero, and N. Pierdicca, "Modeling the coherence of scattered signals of opportunity, *IEEE Int. Geosci. Remote Sensing Symp.*, pp. 4819-4822, 2019.
- [83] J. F. Munoz-Martin, et al., "In-orbit validation of the FMPL-2 instrument—The GNSS-R and L-Band microwave radiometer payload of the FSSCat mission," *Remote Sensing*, vol. 13, no. 1, p. 121, 2021.
- [84] A. Perez-Portero, et al., "Airborne GNSS-R: A key enabling technology for environmental monitoring," *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, in press, DOI: 10.1109/JSTARS.2021.3076003. 2021.