Image data compression with Hierarchical Pixel Averaging and FAPEC

Riccardo Iudica^{a,b}, Gabriel Artigues^a, Jordi Portell^{a,c}, Enrique García-Berro^{a,b}

^aInstitute for Space Studies of Catalonia, c/Gran Capità 2-4, Edifici Nexus 201, 08034 Barcelona, Spain

^bDepartament de Física Aplicada, Universitat Politècnica de Catalunya, c/Esteve Terrades 5, 08860 Castelldefels, Spain

^cDepartament d'Astronomia i Meteorologia, Institut de Ciències del Cosmos, Universitat de Barcelona (IEEC-UB), c/Martí Franquès 1, 08028 Barcelona, Spain

Abstract. FAPEC is an entropy coder which typically offers better results than the adaptive Rice compressor. It uses basic pre-processing stages such as delta pre-processing, but it can also be combined with a DWT. Here we describe a new algorithm called Hierarchical Pixel Averaging (HPA). It divides an image in blocks of 16×16 pixels which are subsequently divided into smaller blocks, up to the basic level where one block corresponds to one pixel. Average pixel values are determined for each level, from which differential coefficients are extracted. HPA allows the introduction of controlled losses with several quality levels, also allowing to progressively decompress a given image from lower to higher quality. It achieves better resolution in sharp image edges when compared to other lossy algorithms. HPA is based on simple arithmetic operations, allowing a very simple (thus quick) implementation. It does not use any floating-point operation, which is an interesting feature for satellite or embedded data compression. We present a first implementation of HPA and the results obtained on a variety of images, both for the lossless and lossy cases with different quality levels. Our results indicate that HPA+FAPEC offers a performance comparable to that of CCSDS 122.0.

Keywords: Image data compression, FAPEC, HPA, DWT, lossless, lossy

Address all correspondence to: Jordi Portell, Institute for Space Studies of Catalonia, c/Gran Capità 2-4, Edifici Nexus 201, 08034 Barcelona, Spain; E-mail: portell@ieec.cat

10.951 INTRODUCTION

Given the large amount of data generated onboard the new generations of satellites for space exploration and Earth observation, a very efficient compression algorithm is needed to drastically reduce the size of the data to be transferred to the ground segment. Each space mission has strict requirements in terms of available bandwidth for the data downlink, available time for such transfer, and available computing resources on-board. Each of these resources is very expensive, so the cost of each mission can be strongly affected by the compression algorithm chosen. Other limitations come from the architecture of the on-board processor or the hardware implementation of the selected compressor. In some cases they cannot perform floating-point operations, but in general it is advisable to avoid so — especially in case of lossless compression. All this means that the algorithm must be kept as simple as possible. In particular, lossy compression algorithms based on wavelets or DCT (Discrete Cosine Transforms) are sometimes too complex for the available processing power onboard and, thus, are frequently avoided in the most restrictive applications [1, 2].

In this paper we introduce a new image compression algorithm, the so-called Hierarchical Pixel Averaging (HPA). It is a pre-processing stage envisaged for FAPEC [3], an entropy coder which can offer better results than the current standard — that is, the CCSDS 121.0 algorithm

Fig. 1. One HPA block, formed by 16×16 pixels.

— for lossless data compression in space [4]. The latter is based on the Rice-Golomb coding method, which is conceived for noiseless data following geometric distributions. Its performance rapidly degrades in the presence of outliers. FAPEC, on the contrary, is much more resilient in front of unexpected data, providing good compression efficiency under almost any situation. The goal of the HPA approach is twofold. On one hand, we intend to achieve better compression ratios by taking advantage of the inter-pixel correlations typically present in an image. Its design has been kept simple: it only uses simple arithmetic calculations, which makes it suitable to be embedded on-board satellite payloads. On the other hand, its design allows progressively introducing controlled losses in the compression, further increasing the compression ratios at the expense of a reasonable quality loss in the reconstructed image.

10.952 THE HPA CONCEPT

10.952.1 Image blocks and levels

The basic image block of the HPA algorithm consists of just 16×16 pixels. Let us call the entire block a *Level-4 block*. It can be divided into four smaller areas or quadrants, each one with an 8-pixels side, which we call *Level-3 blocks*. In the same way, we can define *Level-2 blocks* (with 4-pixel sides) and *Level-1 blocks* (with 2-pixel sides). Finally, *Level-0* consists of the 256 individual pixels. Summarizing, for each 256 pixels block, we define 256 level-0 pixels, 64 level-1 blocks (each made of 2×2 pixels), 16 level-2 blocks (each made of 4×4 pixels), 4 level-3 blocks (each made of 8×8 pixels), and finally 1 level-4 block (made of 16×16 pixels). A representation of this scheme can be seen in Fig. 1, where, for the sake of clarity, only a fraction of the blocks is highlighted and numbered.

A consequence of such a hierarchy is that each block of level $n + 1$ is composed of 4 blocks of level n , and that the average value of the $n + 1$ level block is equal to the mean of the average values of the 4 sub-blocks of level n . Equation (1) describes this relation as follows:

$$\overline{H_{n+1}(A)} = \frac{\overline{H_n(B)} + \overline{H_n(C)} + \overline{H_n(D)} + \overline{H_n(E)}}{4} + \rho_{n+1}(A) \quad (1)$$

where $\overline{H_{n+1}(A)}$ is the average of block A from level $n + 1$, $\rho_{n+1}(A)$ is the remainder of its integer division by 4, $\overline{H_n(B)}$ is the average of the block B from level n , and so on. Inverting Eq. (1), one can calculate one of the lower-level coefficients knowing that of the upper level and the other three of the present level as follows:

$$\overline{H_n(E)} = 4 \times \overline{H_{n+1}(A)} - \rho_{n+1}(A) - \overline{H_n(B)} - \overline{H_n(C)} - \overline{H_n(D)} \quad (2)$$

The basic concept behind the HPA algorithm is to extract differential coefficients using the average values and to compress them, instead of compressing the values of the original pixels. The relation between the differential coefficient and its original value is given by Eq. (3):

$$\Delta H_n(i) = \overline{H_n(i)} - \overline{H_{n+1}(A)} \quad (3)$$

Combining Eq. (2) and Eq. (3), the entire block of 16×16 pixels can be represented in 192 ΔH_0 coefficients, 48 ΔH_1 , 12 ΔH_2 , 3 ΔH_3 and 1 $\overline{H_4}$. Note that ΔH_i refers to the differential coefficients for level i , whereas $\overline{H_4}$ refers to the average value for level 4.

The total number of coefficients to be coded is 256, thus remaining identical to the number of original pixels in the block. Nevertheless, there is some overhead due to the remainders. Specifically, 64 ρ_1 remainders for level 1 are needed, which can be coded in just 2 bits each, leading to 16 bytes in total. Also, 16 ρ_2 remainders for level 2 are needed as well (this amounts to 4 bytes) 4 ρ_3 remainders for level 3 (1 byte). Finally, 1 ρ_4 remainder is required for level 4, that is, 2 bits. The total overhead of the HPA algorithm is given by those reminders, which sum 21 bytes plus 2 bits. This represents an overhead of 0.66 bits per pixel, which is compensated by the smaller entropy levels that result when the differential H coefficients are coded.

A consequence of the hierarchical approach of the HPA algorithm is that the first part of the coefficients ($\overline{H_2}$) contains most of the information contained in the image (that is the average value of the correspondent block of 16×16 pixels). Thus, they could be used to reconstruct a thumbnail of the original image, with a size much smaller than that of the original image. This is similar to the approach adopted in the multi-level Haar Wavelet Transform or in DCT algorithms. In these compressors the first part of the coefficients also contains most of the information of the image, whereas the rest consists of some sort of differential coefficients.

10.952.2 HPI variant

A variant of the HPA algorithm is the Hierarchical Pixel Interpolation algorithm, or HPI. The difference of this algorithm with respect to the previously explained one is how the differential coefficients are computed. As previously shown in Eq. (3), HPA calculates the differential coefficients by subtracting the lower-level average value from the higher-level average values. Instead, when the HPI algorithm is employed, in a first instance the average values of level 1 are interpolated to predict the pixel values. Subsequently, the differential coefficients are calculated by subtracting lower-level average values from the interpolated pixels just computed. Therefore, Eq. (3) must be modified, resulting in the following expression:

$$\Delta H_n(i) = P_n(i) - P_n(i)' \quad (4)$$

where $P_n(i)'$ is the interpolated pixel. Since the interpolated pixel is more similar to the original pixel than the average coefficient of the upper level, the differential coefficients of the HPI implementation have lower entropy and, hence, are more compressible. From now on when we refer to HPA+FAPEC we only consider the HPI variant. Hence, the lossy compressor described below has been implemented using the HPI variant.

10.953 LOSSY HPA

One of the advantages of the HPA algorithm is that it is easy to introduce controlled losses. The evolution to the lossy version of the algorithm consists of removing some of the least significant bits (LSB) from the ΔH coefficients or the ρ remainders. Note that HPA allows to do this very easily because we keep working in the image domain, whereas other approaches such as DWT have to handle this more carefully to avoid strange and uncontrolled effects when removing such bits from the transformed domain coefficients. Instead, when our approach is adopted, the values of the pixels are reconstructed with progressively less accuracy, thus reducing the overall quality of the image.

Fig. 2. Qualitative entropy comparison of the HPA coefficients for the lossless (top panel) and lossy (bottom panel) versions of the algorithm.

In the current implementation of lossy HPA we have opted to allow different configurations depending on the quality level required. That is, we have taken a fixed-quality approach instead of fixed-rate. In particular, in our strategy the number of bits removed from the ΔH coefficients varies from 0 to 8, and the number of bits removed from the ρ remainders varies from 0 to 2. Following this strategy, we define the Quality Levels (hereafter QL) of lossy HPA as follows. QL 0 is the lossless compression (no LSB removal). In QL 1 we remove 1 bit from ΔH_0 and 1 bit from ρ_1 , which in practice is equivalent to removing 1 bit per pixel. In QL 2, 2 bits from ΔH_0 and 2 bits from ρ_1 are removed, meaning that we remove ρ_1 completely. In QL 3, we discard 3 bits from ΔH_0 , 1 bit from ΔH_1 , 2 bits from ρ_1 and 1 bit from ρ_2 . In QL 4 we discard 4 bits from ΔH_0 , 2 bits from ΔH_1 , 2 bits from ρ_1 and 2 bits from ρ_2 . This otherwise intuitive and progressive approach is continued until QL 8, where we drop 8 bits from ΔH_0 (that is, these coefficients are completely removed), 6 bits from ΔH_1 , 4 bits from ΔH_2 , 2 bits from ΔH_3 , and all ρ remainders. In such QL 8 we lose all the high-resolution information of the image, effectively downsampling it to a quarter of its original resolution (that is, half its original width and height). We have also defined a “QL 0.5”, where we just remove one LSB from ρ_1 . The LSBs are removed by right shifting the adequate amount of bits. The consequence of this procedure is that the histogram of the differential coefficients becomes steeper and more centred around 0. The example shown in Fig. 2 compares the histograms of the ΔH_0 coefficients for the lossless version and the QL 2 lossy version.

10.954 FAPEC AND DWTEAPEC

The Fully Adaptive Prediction Error Coder (FAPEC) is a highly-optimized entropy coding algorithm for data compression which offers outstanding resiliency in front of outliers in the data [3]. The typical application of FAPEC is as the coding stage of a data compression system, after a first stage performing some kind of pre-processing on the data to be compressed, leading to prediction errors — hereby the name of FAPEC. Such prediction errors, in the form of signed integer values, are expected to be much smaller than the original data, and from that FAPEC will generate short binary codes leading to an output smaller than the original data. Additionally, FAPEC has been designed to be extremely efficient regarding the processing requirements. An

Fig. 3. Subset of images from the CCSDS 122.0 corpus that has been used in the tests. From top to bottom and from left to right: `pleiades_pan` (5504×1400 12-bit), `b8` (2048×2048 8-bit), `europa3` (557×600 8-bit), `marstest` (512×512 8-bit), `wfpc` (800×800 12-bit) and `p160_b_f` (2048×2048 16-bit).

FPGA prototype is also available for FAPEC [5], thus demonstrating its feasibility and suitability for space missions.

In addition to FAPEC, an image compressor based on it was developed. It is called DWTFAPEC [2]. The DWTFAPEC image compressor is a fast, simple and robust entropy coder that makes use of the DWT (Discrete Wavelet Transform) as pre-processing stage for FAPEC. Within this scheme, the compressor yields excellent compression ratios in almost any situation with very small requirements of processing resources. Additionally, DWTFAPEC demonstrated the feasibility of combining complex pre-processing stages with FAPEC.

10.955 TESTS AND RESULTS

A first prototype of the algorithm has been implemented in C and tested on an Intel i686-64bit platform running GNU/Linux. The GNU Compiler Collection (GCC) has been used to compile the code. We have run several tests of the HPA algorithm (using the HPI variant) on the CCSDS 122.0 image corpus. The main goal of these tests is to compare the HPA+FAPEC combination against different compressors — namely, FAPEC, DWTFAPEC and the CCSDS 122.0 recommendation, nowadays used in space applications. All of them have been run on the same platform in order to provide comparable performance results. Two test campaigns have been executed to compare the performance of these compressors. First, using the lossless configuration, considering compression ratios and execution times. Then, using the lossy versions (excluding FAPEC, which only supports lossless operation) with different quality levels, considering also the Peak Signal to Noise Ratio (PSNR). Note that for comparison purposes two CCSDS 122.0 implementations were used for the lossy tests. One is the standard implementation, whereas the other uses the same lossy compression approach as DWTFAPEC [2], where only the AC coefficients containing the most important information are coded.

10.955.1 Image compression corpus

The complete CCSDS 122.0 test image package has been used as image compression corpus for all the following tests. Nevertheless, for the sake of conciseness we only show here the results for a selected set of 6 of these images. Fig. 3 illustrates these images.

Table 1. Comparison of lossless compression ratios and execution times for HPA+FAPEC, FAPEC, DWTFAPC and CCSDS 122.0 on some representative images from the CCSDS 122.0 image corpus.

	FAPEC		HPA + FAPEC		DWTFAPC		CCSDS 122.0	
	C_R	Time	C_R	Time	C_R	Time	C_R	Time
b8	2.01	252 ms	1.95	672 ms	2.17	1116 ms	2.18	1236 ms
europa3	1.05	24 ms	1.07	52 ms	1.16	92 ms	1.21	132 ms
marstest	1.45	16 ms	1.34	40 ms	1.57	64 ms	1.67	88 ms
p160_b.f	1.25	860 ms	1.25	1852 ms	1.29	1548 ms	1.30	2344 ms
pleiades_pan	1.49	1452 ms	1.46	3056 ms	1.62	2628 ms	1.67	3424 ms
wfpc	3.07	100 ms	3.07	224 ms	3.21	200 ms	3.13	184 ms

Table 2. Minimum, average and maximum lossless compression ratios achieved by HPA+FAPEC, FAPEC, DWTFAPC and CCSDS 122.0 on the image corpus grouped by pixel bit depths.

	FAPEC			HPA + FAPEC			DWTFAPC			CCSDS 122.0		
	min	avg	max	min	avg	max	min	avg	max	min	avg	max
8	1.05	2.02	3.48	1.03	1.89	2.37	0.96	2.17	3.20	1.01	2.20	3.40
10	1.29	1.91	2.44	1.27	1.84	2.24	1.42	2.15	2.82	1.47	2.27	2.94
12	1.35	1.60	3.35	1.36	1.59	3.28	1.48	1.75	3.52	1.52	1.79	3.50
16	1.25	1.28	2.45	1.06	1.27	1.51	0.99	1.31	1.58	1.06	1.32	1.61

10.955.2 Lossless compression performance

We first compare our prototype of HPA+FAPEC against the original FAPEC, the standard CCSDS 122.0 (in lossless mode) and DWTFAPC (also in lossless mode). Table 1 compares the performance in terms of compression ratio (C_R) and execution time. We note here that the performance of the HPA algorithm for lossless compression is not optimal, when compared with that of FAPEC or of the CCSDS 122 standard. The reader should keep in mind that, as previously explained, the HPA algorithm has been designed to allow FAPEC to compress lossy. Thus, the results for lossless compression can only be considered as indicative. The average compression ratio for each compressor is shown in Table 2. Finally, to compare the complexity of the lossless algorithms, Table 3 shows the average number of instructions per sample or pixel.

The results show that, in terms of compression ratios, HPA+FAPEC performs more or less similar to FAPEC alone. The execution time is understandably larger than that of FAPEC due to the HPA pre-processing stage. Comparing HPA with CCSDS 122.0 and DWTFAPC it can be seen that, in general, the two last algorithms compress the images more than HPA. Nevertheless, the results are acceptable in general, considering that the main application of the HPA algorithm is to be implemented in a framework for lossy image compression. It should also be kept in mind that HPA is still a prototype, so here we mainly intend to demonstrate its feasibility and proof of concept. It is worth noting that the HPA ratios get closer to the DWT-based ones (that is, DWTFAPC and CCSDS 122.0) for the 12-bit and 16-bit images. This is otherwise expected, because FAPEC has proven to be more competitive for sample sizes larger than 8 bits [3]. Finally, despite of being in such a prototyping phase, HPA runs on average 28.5% faster than CCSDS 122.0 in its “Nebraska” C implementation available from the CCSDS website.

10.955.3 Lossless compression performance on noisy data

One of the strengths of FAPEC is its resilience in front of outliers, and therefore the HPA+FAPEC combination should also reveal that. In order to prove the robustness of our solution on that regard, we have added some noise to the images and compared the decrease in C_R against that of CCSDS 122.0 and DWTFAPC. Specifically, we have introduced 1% noise, that is, one noisy

Table 3. Average number of instructions per sample for lossless compression for HPA+FAPEC, FAPEC, DWTFAPC and CCSDS 122.0 on some representative images from the CCSDS 122.0 image corpus.

Image	FAPEC	HPA + FAPEC	DWTFAPC	CCSDS 122.0
b8	151	449	920	1487
europa3	168	471	979	1927
marstest	156	452	961	1736
p160_b_f	186	491	1171	2444
pleiades_pan	174	481	1153	2255
wfpc	158	464	1155	1682

Table 4. Percentage of degradation of C_R for HPA+FAPEC, DWTFAPC and CCSDS 122.0 when noise is present. The images have been modified by introducing outliers in 1% of their pixels. See text for details.

	HPA + FAPEC		DWTFAPC		CCSDS 122.0	
	C_R	C_R loss	C_R	C_R loss	C_R	C_R loss
b8	1.77	9.23 %	1.68	22.58 %	1.67	23.39 %
europa3	1.06	0.93 %	1.14	1.72 %	1.17	3.31 %
marstest	1.31	2.24 %	1.38	12.10 %	1.42	14.97 %
p160_b_f	1.21	3.20 %	1.19	7.75 %	1.20	7.69 %
pleiades_pan	1.22	16.44 %	1.41	12.96 %	1.47	11.98 %
wfpc	1.83	40.39 %	2.14	33.33 %	2.23	28.75 %

pixel every 100 pixels — which is quite sensible in space instrumentation [6]. The noise has been simulated by adding a random value uniformly distributed within $\pm 25\%$ of the dynamic range (e.g. within ± 64 in images of 8-bit color depth). These pixels can be regarded as outliers caused by, for instance, prompt particle events in space detectors. Table 4 shows the results of this test. This table reveals that the percentage of degradation in the compression ratio for CCSDS 122.0 standard is typically five or more times larger than that obtained using HPA. The worse results achieved by the HPA in the last two images are due to the low entropy of these images. Specifically, adding noise to one pixel every 100 means that for each block of 16×16 pixels there are at least two noisy pixels. This increases the entropy of the image and the effect is more evident for low entropy images. This explains why the largest percentage of degradation is often associated with larger values of C_R . In summary, except for a few cases, the HPA algorithm is typically more resilient to noise and outliers than the CCSDS 122.0 standard.

10.955.4 Lossy compression performance

We have considered the HPA quality levels from QL 1 to QL 8 for the comparison of the compression ratio, execution time and quality of the reconstructed images (quantified as the PSNR). Fig. 4 shows the comparison of the PSNR versus compression ratios achieved by HPA, DWTFAPC and CCSDS 122.0. We also include the “modified” CCSDS 122.0 algorithm in the comparison, that is, an implementation that follows the same lossy approach as DWTFAPC [2], where only the AC coefficients containing the most important information are coded. In general, HPA seems to be quite competitive for low levels of losses, yielding better results than DWTFAPC and the modified CCSDS 122.0 algorithm, and similar results for higher levels of losses. It is worth emphasizing that HPA appears to provide a smoother evolution from lossless to lossy, that is, we can achieve higher PSNR levels than with the DWT-based algorithms. Therefore, it is an interesting solution for near-lossless image compression. To better show this we computed, for each block of 16×16 pixels, the value of the maximum difference between the original and the reconstructed pixels in our simulation, $\epsilon_{\max}$, and compared it with the

Fig. 4. Comparison of C_R as a function of the PSNR for Lossy HPA+FAPEC, DWTFAPEC and the CCSDS 122.0 standard. From left to right and from top to bottom: b8, europa3, marstest, p160_b.f, pleiades_pan, wfpc.

theoretical maximum number of pixels which may differ from the original ones for each QL, δn . Table 5 shows these results for the b8 image (8 bit). The maximum number of different pixels is 256 because at least 1 LSB is removed from ΔH_0 . We also note that the maximum error depends on the number of LSBs removed from each type of coefficient.

On the other hand, the CCSDS 122.0 recommendation demonstrates its good design by typically providing the best PSNR results for a given compression ratio. An exception is the *wfpc* image (the wide-field planetary camera image from the Hubble space telescope), where HPA provides significantly better results than any other compressor for low to medium levels of quality loss. This result must come from this peculiar image, where most of the pixels are dark with just a few of them containing images from stars and galaxies.

Regarding execution times, Fig. 5 shows that HPA runs significantly faster than its competitors for the lower levels of losses, specially for the 8-bit images. This result is consistent with

Table 5. Comparison of the bits removed and the maximum difference found for the image b8 for each quality level.

	ΔH_0	ρ_1	ΔH_1	ρ_2	ΔH_2	ρ_3	ΔH_3	ρ_4	$\epsilon_{\max}$	Δn
QL 1	1	1	0	0	0	0	0	0	3	256
QL 2	2	2	0	0	0	0	0	0	9	256
QL 3	3	2	1	1	0	0	0	0	22	256
QL 4	4	2	2	2	0	0	0	0	37	256
QL 5	5	2	3	2	1	1	0	0	64	256
QL 6	6	2	4	2	2	2	0	0	117	256
QL 7	7	2	5	2	3	2	1	1	119	256
QL 8	8	2	6	2	4	2	2	2	156	256

Table 6. Average number of instructions per sample for lossless compression for HPA+FAPEC, FAPEC, DWTFAPC and CCSDS 122.0 on some representative images from the CCSDS 122.0 image corpus.

Image	HPA + FAPEC	DWTFAPC	CCSDS 122.0
b8	396	469	802
europa3	433	505	826
marstest	412	506	856
p160_b-f	455	557	808
pleiades_pan	446	551	830
wfpc	411	562	841

those found for the lossless compression, previously shown in Table 1. Actually, the execution time of HPA seems to be quite constant for all levels, whereas the other options progressively reduce their execution time as we increase the level of losses. This result comes from the fact that fewer coefficients (in DWTFAPC and in the modified CCSDS 122.0 algorithm) or bitplanes (in the original CCSDS 122.0 standard) have to be coded when we introduce more losses, whereas HPA keeps coding all of the coefficients — except in QL8 where we remove the higher-resolution ones. The slight reduction in its execution time comes from the FAPEC core, which runs faster for more compressible data. Again, it is important to point out that this is the first prototype of the HPA algorithm and that further optimizations are still possible to make it even more efficient. For the sake of completeness, in Table 6 we compare the complexity of the lossy algorithms, in terms of the average number of instructions per sample or pixel for all the quality levels.

Finally, Fig. 6 provides a qualitative comparison of the lossy results that can be achieved with the different algorithms. We have used QL 7 for HPA, QL 3 for DWTFAPC and a fixed rate of 0.5 bits for the CCSDS 122.0 standard, all of them providing a PSNR around 10 dB — that is, quite a bad-quality case. The top panels show a detail of the original *europa3* image and its lossy recovered images, whereas the bottom panels show the errors of the recovered images after lossy compression. The latter are actually “error maps”, where each pixel shows the error in the reconstruction of that pixel with respect to the original image. White pixels mean a perfect reconstruction, while dark or black pixels mean a larger error. It can be seen that the reconstruction errors for the case of HPA are quite randomly distributed over the image, although they become significantly more evident around the sharp edges. In the case of DWTFAPC the errors are also evident in such edges, which lead to artifacts in the reconstructed image. Finally, in the case of the CCSDS 122.0 recommendation the errors are more uniformly distributed over the entire image. Overall, it seems that HPA and especially the CCSDS 122.0 recommendation provide more details in the sharp image edges. On the other hand, DWTFAPC significantly smoothens such edges in the reconstructed image.

Fig. 5. Comparison of the execution time between Lossy HPA+FAPEC, DWTFAPC and CCSDS 122.0 algorithm. From left to right and from top to bottom: b8, europa3, marstest, p160_b.f, pleiades_pan, wfpc.

For completeness, we also provide the qualitative comparison of the lossy results for the case of lower levels of losses — that is, higher image qualities. Specifically, we have tested the algorithms for a PSNR of about 17 dB. The results are shown in Fig. 7. As otherwise expected, despite of zooming into a detail of the image it is hard to identify any problems in the reconstructed images, which are obviously an excellent result for all of the algorithms. Only when looking at the error maps it can be seen that the HPA algorithm (both with QL 3 and QL4) has some remarkable differences in the reconstructed images around the sharp edges. DWTFAPC also reveals such effects, whereas the CCSDS 122.0 recommendation shows almost no difference at all in the entire image. It is worth noting the significant increase in the HPA compression ratio (from 1.81 to 2.33) when moving from QL 3 to QL 4 despite of leading to very similar images after reconstruction. DWTFAPC seems to offer the worst compression ratios in this case.

Fig. 6. Detail of the original and reconstructed europa3 image after low-quality lossy compression. The top panels show, from left to right: original, HPA+FAPEC, DWTFAPC and CCSDS 122.0 standard. Bottom panels: HPA error map, DWTFAPC error map and CCSDS 122.0 standard error map. The compression ratios are 8.4 for HPA, 5.0 for DWTFAPC and 15.9 for the CCSDS 122.0 standard. The PSNR obtained in all cases is around 10 dB.

Fig. 7. Top panels: detail of the reconstructed europa3 image after high-quality lossy compression. Bottom panels: error maps obtained from the different compressors. From left to right: HPA+FAPEC with QL 3 (ratio 1.81 and PSNR 18.1 dB), HPA+FAPEC with QL 4 (ratio 2.33 and PSNR 15.5 dB), DWTFAPC with QL 1 (ratio 1.43 and PSNR 17.0 dB) and CCSDS 122.0 recommendation with a rate 3 bpp (ratio 2.65 and PSNR 17.2 dB).

10.956 FUTURE IMPROVEMENTS

The HPA algorithm and its HPI variant, despite of still being prototypes, have shown future potential and a clear applicability and usefulness. Nevertheless, there is clearly much room for improvements. For example, so far the algorithm is only able to handle greyscale images. A different implementation of the algorithm allowing to compress color or even hyperspectral images is currently under study. Besides, the algorithm needs to be further optimized, reducing in this way the execution time needed to compress a given image. We also envisage improvements in the FAPEC core to enable a parallelization of the compression process — an interesting feature when dealing with large data volumes. Since HPA works independently on the different 16×16 pixels blocks, it can be easily parallelized, and this will result in a reduction of the execution time. The HPA algorithm will also be revised in order to improve the lossless and high-quality lossy ratios. Finally, regarding the lossy compression, one feature that would improve the algorithm usability is a logic which, given a desired compression ratio (or bits per pixel), the adequate QL is adaptively selected. This means to add a control that allows the HPA to compress not only with fixed quality, but also with fixed rate.

10.957 CONCLUSIONS

In this paper we have introduced a new image compression algorithm called Hierarchical Pixel Averaging (HPA). It has been designed as a new pre-processing stage for FAPEC, specific for images. The goal was to obtain an efficient image compression algorithm allowing to progressively move from lossless compression to near-lossless and lossy compression with different quality levels. The HPA implementation has been kept as simple as possible, avoiding floating-point operations in order to make it more suitable to be implemented in hardware and embedded on satellite payloads. It must be also noted that we have adopted this approach (instead of the typical wavelet-based or transformation-based approaches) in order to minimize the artifacts that can be seen in the restored images when they are lossy compressed with very low quality levels.

The results, when compared to the CCSDS 122.0 standard, show that the HPA+FAPEC combination can compress an image significantly faster (28.5% on average) in the lossless scheme. The compression ratio is similar to that obtained when compressing using FAPEC alone (which uses a delta pre-processing), but still lower than with the lossless CCSDS 122.0 recommendation or DWTFAPC. We expect to improve such lossless results with future improvements in the algorithm. In presence of noise, the HPA+FAPEC combination has shown better results than its competitors, resulting in a smaller degradation of C_R . In the lossy scheme, HPA can achieve higher compression ratios and PSNR values for the lower levels of losses. One interesting result is the capability of HPA to achieve higher quality levels than DWTFAPC or the CCSDS 122.0 recommendation, thus offering a near-lossless image compression.

The quality of the recovered images are very good for low to moderate levels of losses. One of the interesting results is that the compressed images obtained using lossy HPA can keep most of the details around sharp image edges, whereas the modified lossy CCSDS 122.0 recommendation and DWTFAPC typically present a significant smoothing or artefacts in such edges.

Summarizing, this new image compression approach appears as a promising, feasible and efficient alternative to the current image data compression standard for satellite payloads.

10.958 Acknowledgments

The images shown in this paper were obtained from the CCSDS website. This work was partially supported by the MINECO (Spanish Ministry of Economy) – FEDER grants AYA2011-23102, AYA2012-39551-C02-01 and ESP2013-48318-C2-1-R.

10.95References

- [1] Consultative Committee for Space Data Systems, “Image Data Compression, Blue Book,” Tech. Rep. CCSDS 122.0-B-1, CCSDS (2005).
- [2] B. Artigues, J. Portell, A. Villafranca, H. Ahmadloo, and E. García-Berro, “DWTFAPEC: image data compression based on CCSDS 122.0 and fully adaptive prediction error coder,” *J. of Appl. Remote Sensing* **7** (1), 074592 (2013).
- [3] J. Portell, A. Villafranca, and E. García-Berro, “Quick outlier-resilient entropy coder for space missions,” *J. of Appl. Remote Sensing* **4**, 339–363 (2010).
- [4] Consultative Committee for Space Data Systems, “Lossless Data Compression, Blue Book,” Tech. Rep. CCSDS 121.0-B-1, CCSDS (1993).
- [5] A. Villafranca, S. Mignot, J. Portell, and E. García-Berro, “FAPEC in an FPGA: a simple low-power solution for data compression in space,” in *Satellite Data Compression, Communication, and Processing VI, Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series* **8157**, 81570I–81570I–9 (2011).
- [6] M. A. Nieto-Santisteban, D. J. Fixsen, J. D. Offenberger, R. J. Hanisch, and H. S. Stockman, “Data Compression for NGST,” in *Astronomical Data Analysis Software and Systems VIII*, D. M. Mehringer, R. L. Plante, & D. A. Roberts, Ed., *Astronomical Society of the Pacific Conference Series* **172**, 137–140 (1999).

Riccardo Iudica is a research collaborator at the Institute for Space Studies of Catalonia (IEEC). He received his degree in Electronic Engineering from the University of Catania in 2004 and his M.Sc. degree in Aerospace Science and Technology from the Technical University of Catalonia (UPC) in 2014. He has worked on the first prototype of the HPA algorithm and his main research activities are focused on data and image processing and compression.

Gabriel Artigues is researcher at the Institute for Space Studies of Catalonia (IEEC). He received his degree in telecommunications engineering from the Technical University of Catalonia (UPC) in 2012. He has worked on the implementation of DWTFAPEC and on the feasibility study of the LOFT mission of ESA. His main research activities are focused on data and image compression as well as image processing.

Jordi Portell is researcher at the Institute for Space Studies of Catalonia (IEEC) and the Institute for Cosmos Sciences at the University of Barcelona (ICC-UB), as well as CTO at DAPCOM Data Services. He received his degree in Electronic Engineering from the Technical University of Catalonia (UPC) in 2000, and his Ph.D. degree in Applied Physics also from the UPC in 2005. He is author of 7 journal papers, one book chapter, 26 proceedings and more than 70 technical notes. He is also one of the inventors of the FAPEC patent. His research activities are focused on the Gaia space astrometry mission and data compression.

Enrique García-Berro earned his PhD in Astrophysics from the University of Barcelona in 1987. He has been Postdoctoral Research Associate at the University of Illinois at Urbana-Champaign. He is Professor at the Department of Applied Physics at the Technical University of Catalonia (UPC) since 1991. He is also Research Associate of the Institute for Space Studies of Catalonia (IEEC) since 1996. His research interests have a broad scope ranging from theoretical astrophysics to the design and implementation of scientific payloads for astronomical satellites. He has published more than 170 papers in refereed journals. He is also one of the inventors of the FAPEC patent. Dr. García-Berro is member of the Spanish Astronomical Society and of the American Astronomical Society.