

## REFERÈNCIES BIBLIOGRÀFIQUES

APHA-AWWA-WPCF (1995). *Standard Methods for the Examination of Water & Wastewater*. 19th edition. American Public Health Association. Washington, D.C.

Baptista J.D.C., Donnelly T., Rayne D., Davenport R.J., (2003). *Microbial mechanisms of carbon removal in subsurface flow wetlands*. *Water Science and Technology*, Vol. 48, No. 5, pp 127-134.

Blazejewski R., Murat-Blazejewska S., (1997). *Soil clogging phenomena in constructed wetlands with subsurface flow*. *Water Science Technology*, Vol. 35, No. 5, pp. 183-188.

Brix H., (1990). *Gas exchange through the soil – atmosphere interphase and through dead culms of *Phragmites australis* in a constructed reed bed receiving domestic sewage*. *Water Science Technology*, Vol. 24, No. 2, pp. 259-266.

Capel V., (2004). *Degradabilitat de la matèria orgànica adherida a la grava d'aiguamolls de flux subsuperficial*. Tesina d'Especialitat. Departament d'EHMA. ETSECCPB. UPC, pp. 43-79.

Castro Suárez A., (2003). *Producció de gas metà en aiguamolls construïts de flux subsuperficial per al tractament d'aigües residuals urbanes*. Departament d'EHMA. ETSECCPB. UPC, pp. 6-33.

Chico Muñoz F.L, (2002). *Vías de degradación de la materia orgánica en humedales construidos de flujo subsuperficial*. Tesina d'Especialitat. Departament d'EHMA. ETSECCPB. UPC, pp. 9-16.

Fakharedine N., El Hajjouji H., Ait Baddi G., Revel J.C., Hafidi M, (2005). *Chemical and spectroscopic analysis of organic matter transformations during aerobic digestions of olive-mill waste-waters*. *Process Biochemistry*, 41 (2006) 398-404.

Field J., Sierra Álvarez R., Lettinga G., (1988). *4º Seminario depuración anaerobia de aguas residuales*. Universidad de Valladolid, 52-75 pp.

Fricke K., Santen H., Wallmann R., (2005). *Comparison of selected aerobic and anaerobic procedures for MSW treatment*. *Waste Management* 25 (2005) 799-810.

Gallardo Castillejo R., (2000). *Diseño, construcción y explotación de humedales construidos de flujo subsuperficial*. Departament d'EHMA. ETSECCPB. UPC, pp. 25-31, 72-81.

García J., Aguirre P., Barragán J., Mujeriego R., Matamoros V., Bayona J.M., (2005). *Effect of key design parameters on the efficiency of horizontal subsurface flow constructed wetlands*. *Ecological Engineering* 25 (2005) 405-418.

García J., Chiva J., Aguirre P., Álvarez E., Sierra J.P., Mujeriego R., (2004). *Hydraulic behaviour of horizontal subsurface flow constructed wetlands with different aspect ratio and granular medium size*. *Ecological Engineering* 23 (2004) 177-187.

Gutiérrez O., (2005). *Identificació de paràmetres científics i estequiomètrics del procés de depuració de fangs actius mitjançant tècniques respiromètriques*. Universitat de Girona, dipòsit legal: GI-1166-2005.

Huang Y., Ortiz L., Aguirre P., García J., Mujeriego R., Bayona J.M., (2004). *Effect of design parameters in horizontal flow constructed wetland on the behaviour of volatile fatty acids and volatile alkylsulfides*. Chemosphere 59 (2005) 769-777.

Johansson A.E., Gustavsson A.M., Öquist M.G., Svensson B.H., (2004). *Methane emissions from a constructed wetland treating wastewater - seasonal and spatial distribution and dependence on edaphic factors*. Water Research 38 (2004) 3960-3970.

Kadlec R.H., Knight R.L., (1996). *Treatment Wetlands*. Ed. CRC Press. Boca Raton. 893 pp.

Kalyuzhnyi S.V., Daylyatshina M.A., (1996). *Batch anaerobic digestion of glucose and its mathematical modelling. I. Kinetic investigations*. Bioresource Technology 59 (1997) 73-80.

Kalyuzhnyi S.V., Fedorovich V.V., (1998). *Mathematical modelling of competition between sulphate reduction and methanogenesis in Anaerobic reactors*. Bioresource Technology 65 (1998) 227-242.

Nguyen L., (2001). *Accumulation of organic matter fractions in a gravel-bed constructed wetland*. Water Science Technology, Vol. 44, No. 11-12, pp. 281-287.

Porta A., (2004). *Studio dei rimozione della materia organica in letti di fitodepurazione*. Tesina d'Especialitat. Departament d'EHMA. ETSECCPB. UPC.

Puigagut J., Caselles-Osorio A., Vaello N., García J., (2006). *Size distribution and biodegradability properties of the organic matter in horizontal subsurface flow constructed wetlands*. Secció d'Enginyeria Sanitària i Ambiental.

Reddy K.R., D'Angelo E.M., (1997). *Biochemical indicators to evaluate pollutant removal efficiency in constructed wetlands*. Water Science Technology, Vol. 35, No. 5, pp. 1-10.

Tanner C.C., (2001). *Plant as ecosystem engineers in subsurface-flow treatment wetlands*. Water Science Technology, Vol. 44, No. 11, pp. 9-18.

Tanner C.C., Sukias J.P., (1995). *Accumulation of organic solids in gravel-bed constructed wetlands*. Water Science Technology, Vol. 32, No. 3, pp. 229-239.

U.S. EPA (1993). *Subsurface flow constructed wetlands for wastewater treatment. A technology assessment*. EPA 832-R-93-008. 62 pp.

U.S. EPA (2000). *Wastewater technology fact sheet. Wetlands: Subsurface flow*. EPA 832-F-00-023. 9 pp.

U.S. EPA (2001). *Manual. Constructed wetlands treatment of municipal wastewaters*. EPA 625-R-99-010, 9 pp.